



IEC 63028

Edition 1.0 2017-06

# INTERNATIONAL STANDARD



---

**Wireless power transfer – Airfuel alliance resonant baseline system specification  
(BSS)**

INTERNATIONAL  
ELECTROTECHNICAL  
COMMISSION

---

ICS 29.240.99; 33.160.99; 35.200

ISBN 978-2-8322-4429-6

**Warning! Make sure that you obtained this publication from an authorized distributor.**

## CONTENTS

FOREWORD .....	7
INTRODUCTION .....	9
1 Scope .....	10
2 Normative references .....	10
3 Terms, definitions, symbols and abbreviated terms .....	10
3.1 Terms and definitions .....	10
3.2 Symbols and abbreviated terms .....	13
3.2.1 Symbols .....	13
3.2.2 Abbreviated terms .....	17
4 System description .....	17
5 Conformance and backwards compatibility .....	18
6 Device types .....	19
6.1 PTU classification .....	19
6.2 PRU category .....	20
7 Power transfer specifications .....	20
7.1 System equivalent circuit and reference parameters .....	20
7.2 General system requirements .....	21
7.2.1 Operating frequency .....	21
7.2.2 $Z_{TX\_IN}$ relationship to $R_{RECT}$ .....	21
7.2.3 Power stability .....	21
7.2.4 PTU co-location protection .....	21
7.2.5 PRU self-protection (informative) .....	21
7.3 Resonator requirements .....	21
7.3.1 Resonator coupling efficiency (RCE) .....	21
7.3.2 PTU resonator requirements .....	22
7.3.3 PRU resonator requirements .....	24
7.4 Load parameters .....	25
7.4.1 Load parameters introduction .....	25
7.4.2 Minimum load resistance .....	26
7.4.3 Maximum allowable dynamic load .....	26
7.4.4 Maximum load capacitance .....	26
8 Power control specifications .....	26
8.1 Control objectives .....	26
8.2 PTU specifications .....	26
8.2.1 PTU state .....	26
8.2.2 General state requirements .....	27
8.2.3 PTU power save state .....	28
8.2.4 PTU Low Power state .....	30
8.2.5 PTU Power Transfer state .....	31
8.2.6 PTU Configuration state .....	33
8.2.7 PTU Local Fault state .....	34
8.2.8 PTU latching fault state .....	34
8.2.9 PTU state transitions .....	35
8.2.10 PTU Test Mode .....	38
8.3 PRU specifications .....	38
8.3.1 PRU general requirements .....	38

8.3.2	PRU state model .....	41
8.3.3	Null state .....	42
8.3.4	PRU boot.....	42
8.3.5	PRU On state .....	42
8.3.6	PRU System Error state.....	43
8.3.7	PRU state transitions.....	44
9	Signaling specifications .....	45
9.1	Architecture and state diagrams.....	45
9.1.1	Architecture .....	45
9.1.2	Overall charge process .....	46
9.2	Charge procedure and requirements .....	48
9.2.1	Removing PRU from WPT network .....	48
9.2.2	Power Sharing mode .....	48
9.3	Bluetooth low energy requirements .....	49
9.3.1	Bluetooth low energy requirements introduction.....	49
9.3.2	Bluetooth low energy objectives.....	49
9.3.3	PTU hardware requirement.....	49
9.3.4	PRU hardware requirement.....	49
9.3.5	Basic network structure .....	49
9.3.6	RF requirements .....	49
9.3.7	Timing and sequencing requirements.....	50
9.3.8	Profile structure .....	53
9.4	BLE profile definition.....	53
9.4.1	GATT sub-procedure .....	53
9.4.2	Configuration.....	53
9.4.3	PRU requirements .....	54
9.4.4	PTU requirements.....	55
9.4.5	Connection establishment.....	55
9.4.6	Security considerations.....	57
9.4.7	Charge completion.....	57
9.5	WPT service characteristics .....	58
9.5.1	WPT service characteristics introduction.....	58
9.5.2	PRU advertising payload .....	58
9.5.3	WPT service .....	60
9.5.4	PRU control .....	62
9.5.5	PTU static parameter.....	64
9.5.6	PRU static parameter characteristic.....	69
9.5.7	PRU dynamic parameter characteristic .....	72
9.5.8	PRU alert characteristic .....	76
9.6	Cross connection algorithm.....	78
9.6.1	Cross connection algorithm introduction .....	78
9.6.2	Definitions .....	78
9.6.3	Acceptance of advertisement.....	78
9.6.4	Impedance shift sensing .....	78
9.6.5	Reboot bit handling.....	79
9.6.6	Time set handling .....	79
9.7	Mode transition .....	80
9.7.1	Mode transition introduction.....	80
9.7.2	Mode transition procedure .....	80

9.7.3	BLE reconnection procedure.....	81
10	PTU resonators .....	83
10.1	PTU resonators introduction.....	83
10.2	Class <i>n</i> design template .....	83
10.2.1	Class <i>n</i> design template introduction.....	83
10.2.2	Table of specifications .....	83
10.2.3	PTU resonator structure .....	83
10.3	Approved PTU resonators .....	83
Annex A (informative)	Reference PRU for PTU acceptance testing .....	84
A.1	Category 1 .....	84
A.2	Category 2 .....	84
A.3	Category 3 .....	84
A.3.1	PRU design 3-1 .....	84
A.3.2	Geometry.....	84
A.4	Category 4 .....	87
A.5	Category 5 .....	87
Annex B (informative)	Lost power .....	88
B.1	Overview.....	88
B.2	General.....	88
B.3	Cross connection issues .....	88
B.4	Handoff issues .....	88
B.5	Power noise issues .....	89
B.6	PTU lost power calculation.....	89
B.6.1	Lost power detection threshold .....	89
B.6.2	Lost power detection speed .....	89
B.6.3	PTU lost power calculation .....	89
B.6.4	PTU power transmission detection accuracy.....	89
B.6.5	PRU lost power reports.....	89
B.6.6	Accuracy of reported power .....	90
B.6.7	Other PRU lost power reports .....	90
Annex C (normative)	User experience requirements .....	91
C.1	General.....	91
C.2	User indication .....	91
C.2.1	PRU user indication .....	91
C.2.2	PTU user indication .....	91
Annex D (informative)	RCE calculations.....	92
D.1	RCE calculation (using S-parameters) .....	92
D.2	RCE calculation (using Z-parameters).....	93
D.2.1	Series tuned case .....	94
D.2.2	Other RCE calculations.....	94
D.3	Conversion between S-parameters and Z-parameters .....	94
Figure 1 – Wireless power transfer system.....	18	
Figure 2 – PTU-PRU resonator $P_{TX\_IN}$ .....	19	
Figure 3 – PTU-PRU resonator $P_{RX\_OUT}$ .....	20	
Figure 4 – Equivalent circuit and system parameters .....	20	
Figure 5 – PTU resonator-load considerations .....	24	

Figure 6 – PTU state model .....	27
Figure 7 – Beacon sequences .....	29
Figure 8 – Load variation detection .....	29
Figure 9 – Discovery .....	30
Figure 10 – PTU $I_{TX}$ transition responses .....	31
Figure 11 – PRU state model .....	41
Figure 12 – $V_{RECT}$ operating regions .....	42
Figure 13 – Basic architecture of WPT system .....	45
Figure 14 – Basic state procedure (informative) .....	47
Figure 15 – Registration period timeline example (informative) .....	52
Figure 16 – PTU/PRU services/characteristics communication .....	54
Figure 17 – PRU mode transition – Device Address field set to a non-zero value .....	81
Figure 18 – PRU mode transition – Device Address field set to all zeros .....	82
Figure A.1 – PRU design 3 block diagram .....	84
Figure A.2 – Front view .....	85
Figure A.3 – Back view .....	85
Figure A.4 – Side view .....	86
Figure A.5 – Front view, coil only .....	86
Figure A.6 – Side view, coil only .....	86
 Table 1 – PTU classification .....	19
Table 2 – PRU category .....	20
Table 3 – Minimum RCE (percent and dB) between PRU and PTU .....	22
Table 4 – Maximum load capacitance .....	26
Table 5 – Time requirement to enter PTU Power Transfer state .....	28
Table 6 – Sub-state of PTU Power Transfer .....	32
Table 7 – PTU latching faults .....	37
Table 8 – Example of accuracy of reported current .....	41
Table 9 – PRU system errors .....	45
Table 10 – RF budget (informative) .....	50
Table 11 – Timing constraints .....	52
Table 12 – BLE profile characteristics .....	53
Table 13 – GATT sub-procedure .....	53
Table 14 – PRU advertising payload .....	58
Table 15 – Impedance shift bit .....	60
Table 16 – WPT service UUID .....	60
Table 17 – WPT service .....	61
Table 18 – GAP service .....	62
Table 19 – GATT service .....	62
Table 20 – PRU Control Characteristic .....	63
Table 21 – Detail: bit field for enables .....	63
Table 22 – Detail: bit field for permission .....	64
Table 23 – Detail: bit field for time set .....	64

Table 24 – PTU reporting static values to PRU .....	65
Table 25 – Detail: bit field for optional fields validity.....	65
Table 26 – PTU power .....	66
Table 27 – Max source impedance.....	67
Table 28 – Max load resistance .....	68
Table 29 – AirFuel protocol revision field .....	69
Table 30 – PTU number of devices .....	69
Table 31 – PRU reporting static values to the PTU .....	70
Table 32 – Detail: bit field for optional fields validity.....	70
Table 33 – Detail: bit field for PRU information .....	71
Table 34 – PRU dynamic parameter characteristic .....	73
Table 35 – Detail: bit field for optional fields validity.....	73
Table 36 – Detail: bit field for PRU alert.....	75
Table 37 – Detail: bit field for PRU alert.....	76
Table 38 – Test mode commands .....	76
Table 39 – PRU alert fields .....	77
Table 40 – Detail: bit field for PRU alert notification .....	77
Table 41 – Mode transition.....	78
Table A.1 – PRU table of specifications .....	84

## INTERNATIONAL ELECTROTECHNICAL COMMISSION

**WIRELESS POWER TRANSFER – AIRFUEL ALLIANCE RESONANT  
BASELINE SYSTEM SPECIFICATION (BSS)****FOREWORD**

- 1) The International Electrotechnical Commission (IEC) is a worldwide organization for standardization comprising all national electrotechnical committees (IEC National Committees). The object of IEC is to promote international co-operation on all questions concerning standardization in the electrical and electronic fields. To this end and in addition to other activities, IEC publishes International Standards, Technical Specifications, Technical Reports, Publicly Available Specifications (PAS) and Guides (hereafter referred to as "IEC Publication(s)"). Their preparation is entrusted to technical committees; any IEC National Committee interested in the subject dealt with may participate in this preparatory work. International, governmental and non-governmental organizations liaising with the IEC also participate in this preparation. IEC collaborates closely with the International Organization for Standardization (ISO) in accordance with conditions determined by agreement between the two organizations.
- 2) The formal decisions or agreements of IEC on technical matters express, as nearly as possible, an international consensus of opinion on the relevant subjects since each technical committee has representation from all interested IEC National Committees.
- 3) IEC Publications have the form of recommendations for international use and are accepted by IEC National Committees in that sense. While all reasonable efforts are made to ensure that the technical content of IEC Publications is accurate, IEC cannot be held responsible for the way in which they are used or for any misinterpretation by any end user.
- 4) In order to promote international uniformity, IEC National Committees undertake to apply IEC Publications transparently to the maximum extent possible in their national and regional publications. Any divergence between any IEC Publication and the corresponding national or regional publication shall be clearly indicated in the latter.
- 5) IEC itself does not provide any attestation of conformity. Independent certification bodies provide conformity assessment services and, in some areas, access to IEC marks of conformity. IEC is not responsible for any services carried out by independent certification bodies.
- 6) All users should ensure that they have the latest edition of this publication.
- 7) No liability shall attach to IEC or its directors, employees, servants or agents including individual experts and members of its technical committees and IEC National Committees for any personal injury, property damage or other damage of any nature whatsoever, whether direct or indirect, or for costs (including legal fees) and expenses arising out of the publication, use of, or reliance upon, this IEC Publication or any other IEC Publications.
- 8) Attention is drawn to the Normative references cited in this publication. Use of the referenced publications is indispensable for the correct application of this publication.
- 9) Attention is drawn to the possibility that some of the elements of this IEC Publication may be the subject of patent rights. IEC shall not be held responsible for identifying any or all such patent rights.

International Standard IEC 63028 has been prepared by technical area 15: Wireless power transfer, of IEC technical committee 100: Audio, video and multimedia systems and equipment.

The text of this International Standard is based on the following documents:

FDIS	Report on voting
100/2901/FDIS	100/2941/RVD

Full information on the voting for the approval of this International Standard can be found in the report on voting indicated in the above table.

This document has been drafted in accordance with the ISO/IEC Directives, Part 2.

The committee has decided that the contents of this document will remain unchanged until the stability date indicated on the IEC website under "http://webstore.iec.ch" in the data related to the specific document. At this date, the document will be

- reconfirmed,
- withdrawn,
- replaced by a revised edition, or
- amended.

A bilingual version of this publication may be issued at a later date.

**IMPORTANT – The 'colour inside' logo on the cover page of this publication indicates that it contains colours which are considered to be useful for the correct understanding of its contents. Users should therefore print this document using a colour printer.**

## INTRODUCTION

In today's world, mainstream consumer mobile devices are ubiquitously supported by wireless technologies for data communication and connectivity functions while charging function is primarily supported by wired technologies. The development of wireless power transfer technologies offers increased user convenience for charging mobile devices; technologies include inductive, resonant, uncoupled (RF, ultrasonic, laser) methods.

IEC 63028 defines a specific wireless charging approach based on resonant technology and specifies technical requirements for the AirFuel<sup>TM</sup><sup>1</sup> resonant wireless power transfer (WPT) systems.

---

<sup>1</sup> AirFuel<sup>TM</sup> is the trade name of a product supplied by AirFuel Alliance. This information is given for the convenience of users of this document and does not constitute an endorsement by IEC of the product named.

## **WIRELESS POWER TRANSFER – AIRFUEL ALLIANCE RESONANT BASELINE SYSTEM SPECIFICATION (BSS)**

### **1 Scope**

This document defines technical requirements, behaviors and interfaces used for ensuring interoperability for flexibly coupled wireless power transfer (WPT) systems for AirFuel Resonant WPT. This document is based on AirFuel Wireless Power Transfer System Baseline System Specification (BSS) v1.3.

Products implementing this document are expected to follow applicable regulations and global standards.

### **2 Normative references**

The following documents are referred to in the text in such a way that some or all of their content constitutes requirements of this document. For dated references, only the edition cited applies. For undated references, the latest edition of the referenced document (including any amendments) applies.

AirFuel Wireless Power Transfer System Baseline System Specification (BSS) v1.3 [viewed 2017-03-13]. Available at: <http://www.airfuel.org/technologies/specification-download>

AirFuel Wireless Power Transfer System Baseline System Specification (BSS) v1.2.1 [viewed 2017-03-13]. Available at: <http://www.airfuel.org/technologies/specification-download>

Bluetooth core specification v4.0, or later versions as they are available [viewed 2017-03-13]. Available at: [https://www.bluetooth.org/docman/handlers/downloaddoc.ashx?doc\\_id=229737](https://www.bluetooth.org/docman/handlers/downloaddoc.ashx?doc_id=229737)

CSA4, or later versions as they are available [viewed 2017-03-13]. Available at: [https://www.bluetooth.org/docman/handlers/DownloadDoc.ashx?doc\\_id=269452](https://www.bluetooth.org/docman/handlers/DownloadDoc.ashx?doc_id=269452)