



IEC 62827-2

Edition 1.0 2017-06

# INTERNATIONAL STANDARD



---

## Wireless power transfer – Management – Part 2: Multiple device control management

INTERNATIONAL  
ELECTROTECHNICAL  
COMMISSION

ICS 29.240.99; 33.160.99; 35.100.01

ISBN 978-2-8322-4445-6

**Warning! Make sure that you obtained this publication from an authorized distributor.**

## CONTENTS

FOREWORD.....	6
INTRODUCTION.....	8
1 Scope.....	9
2 Normative references .....	9
3 Terms, definitions and abbreviated terms .....	9
3.1 Definitions.....	9
3.2 Abbreviated terms.....	11
4 Overview .....	11
5 Functionalities .....	13
5.1 General.....	13
5.2 Compatibility.....	13
5.2.1 General .....	13
5.2.2 Indirect control.....	14
5.2.3 Direct control .....	14
5.3 Initialization .....	14
5.3.1 General .....	14
5.3.2 Frequency band scan .....	14
5.3.3 Initiation power transfer .....	14
5.4 Association .....	14
5.4.1 General .....	14
5.4.2 Communication connection .....	14
5.4.3 WPT eligibility check.....	14
5.5 General charging management .....	15
5.5.1 General .....	15
5.5.2 Simultaneous WPT .....	15
5.5.3 Sequential WPT.....	15
5.5.4 Foaming WPT.....	15
5.5.5 Compound WPT .....	15
5.6 Abnormal status management.....	15
5.6.1 General .....	15
5.6.2 Source status detection .....	16
5.6.3 Device status detection.....	16
5.7 Inter–device WPT management .....	16
5.8 Termination.....	17
6 Protocols .....	17
6.1 General.....	17
6.2 ID structure.....	17
6.2.1 Unique coupler ID.....	17
6.2.2 Group ID.....	18
6.2.3 Wireless Power management system ID .....	18
6.2.4 Device ID.....	18
6.3 Frame format .....	18
6.3.1 General .....	18
6.3.2 Frame header .....	19
6.3.3 Frame body .....	19

6.4	Frame type .....	20
6.4.1	General .....	20
6.4.2	Data frame .....	20
6.4.3	Acknowledgement frame.....	20
6.5	Payload format.....	21
6.5.1	General .....	21
6.5.2	Data frame .....	21
6.6	Data block .....	22
6.6.1	General .....	22
6.6.2	Request block.....	22
6.6.3	Response block .....	24
6.6.4	Notification block .....	25
7	Procedures .....	27
7.1	General.....	27
7.2	Association .....	27
7.3	Group ID Set-up .....	28
7.4	General WPT management .....	28
7.4.1	Simultaneous WPT .....	28
7.4.2	Sequential WPT.....	29
7.4.3	Foaming WPT.....	30
7.4.4	Compound WPT .....	31
7.5	Abnormal situations management .....	32
7.5.1	General .....	32
7.5.2	Source status detection .....	32
7.5.3	Device status detection.....	33
7.6	Inter-device WPT management .....	34
7.7	Termination.....	35
Annex A	(informative) Messages.....	36
A.1	General.....	36
A.2	API between application and APP block .....	36
A.2.1	General .....	36
A.2.2	ID display .....	36
A.2.3	Power status display .....	36
A.2.4	WPT mode selection display.....	37
A.2.5	Scheduling information display .....	38
A.2.6	Abnormal situations display .....	39
A.3	Interface between MGMT and MGMT .....	39
A.3.1	General .....	39
A.3.2	WPMS–D identification .....	40
A.3.3	WPT authentication .....	40
A.3.4	Zone recognition.....	42
A.3.5	WPT mode.....	42
A.3.6	Scheduling information .....	43
A.3.7	Abnormal situations management .....	44
A.3.8	WPMS–D full charge notification.....	44
A.3.9	WPT termination notification .....	45
A.3.10	Inter-device WPT .....	45
A.4	Interface between MGMT block and APP block .....	46
A.4.1	General .....	46

A.4.2	Data request.....	46
A.5	Interface between APP layer and MAC layer .....	47
A.5.1	General .....	47
A.5.2	MAC identification request.....	48
A.6	Interface between MGMT block and Coupler Block .....	48
A.6.1	General .....	48
A.6.2	Scheduling control .....	48
A.6.3	Current/voltage sensing.....	49
A.6.4	Abnormal situation control .....	49
A.6.5	WPT termination control .....	50
A.6.6	Full charge .....	50
A.6.7	Inter-device WPT .....	51
Figure 1 – Usage examples of WPMS services .....		12
Figure 2 – WPMS structure .....		13
Figure 3 – Function of inter–device WPT management .....		17
Figure 4 – UCID structure .....		17
Figure 5 – Frame format .....		19
Figure 6 – Data frame format .....		20
Figure 7 – Acknowledgement frame format .....		20
Figure 8 – Payload format of data frame .....		21
Figure 9 – Block format of device status request.....		23
Figure 10 – Block format of WPT request.....		23
Figure 11 – Block format of coil control request .....		23
Figure 12 – Block format of Group ID set–up request.....		23
Figure 13 – Block format of inter–device WPT request.....		24
Figure 14 – Block format of connection response .....		24
Figure 15 – Block format of device status response .....		24
Figure 16 – Block format of WPT response .....		24
Figure 17 – Block format of coil control response.....		25
Figure 18 – Block format of coil control response.....		25
Figure 19 – Block format of inter–device WPT response .....		25
Figure 20 – Block format of COM ID notification.....		25
Figure 21 – Block format of WPT ID notification .....		26
Figure 22 – Block format of WPT mode notification .....		26
Figure 23 – Block format of WPT schedule notification.....		26
Figure 24 – Block format of WPT termination request .....		26
Figure 25 – Block format of full charge notification.....		26
Figure 26 – Block format of discharge rate variation notification.....		27
Figure 27 – Association .....		27
Figure 28 – Group ID set–up.....		28
Figure 29 – Simultaneous WPT.....		29
Figure 30 – Sequential WPT .....		30
Figure 31 – Foaming WPT .....		31
Figure 32 – Compound WPT .....		32

Figure 33 – Source status detection .....	33
Figure 34 – Full charge detection .....	34
Figure 35 – Discharge rate variation detection .....	34
Figure 36 – Inter-device WPT .....	35
Figure 37 – Termination .....	35
Table 1 – Group ID .....	18
Table 2 – ID structure .....	18
Table 3 – Frame type value .....	20
Table 4 – Data codes .....	22
Table A.1 – Values for ID display .....	36
Table A.2 – Values for power status display .....	37
Table A.3 – Values for WPT mode selection display .....	38
Table A.4 – Values for scheduling information display .....	38
Table A.5 – Values for abnormal situation display .....	39
Table A.6 – Values for WPMS–D identification .....	40
Table A.7 – Values for WPT authentication .....	41
Table A.8 – Values for WPMS–D power status information .....	41
Table A.9 – Values for zone recognition .....	42
Table A.10 – Values for WPT mode .....	43
Table A.11 – Values for scheduling information .....	43
Table A.12 – Values for abnormal situations management .....	44
Table A.13 – Values for WPMS–D full charge notification .....	45
Table A.14 – Values for WPT termination notification .....	45
Table A.15 – Values for inter-device WPT .....	46
Table A.16 – Values for data request .....	47
Table A.17 – Values of MAC identification .....	47
Table A.18 – Mac Type code .....	48
Table A.19 – Values for scheduling control .....	48
Table A.20 – Values for current/voltage sensing .....	49
Table A.21 – Values for abnormal situation control .....	50
Table A.22 – Values for WPT termination control .....	50
Table A.23 – Value for full charge notification .....	51
Table A.24 – Values for inter-device WPT .....	51

# INTERNATIONAL ELECTROTECHNICAL COMMISSION

## WIRELESS POWER TRANSFER – MANAGEMENT –

### Part 2: Multiple device control management

#### FOREWORD

- 1) The International Electrotechnical Commission (IEC) is a worldwide organization for standardization comprising all national electrotechnical committees (IEC National Committees). The object of IEC is to promote international co-operation on all questions concerning standardization in the electrical and electronic fields. To this end and in addition to other activities, IEC publishes International Standards, Technical Specifications, Technical Reports, Publicly Available Specifications (PAS) and Guides (hereafter referred to as "IEC Publication(s)"). Their preparation is entrusted to technical committees; any IEC National Committee interested in the subject dealt with may participate in this preparatory work. International, governmental and non-governmental organizations liaising with the IEC also participate in this preparation. IEC collaborates closely with the International Organization for Standardization (ISO) in accordance with conditions determined by agreement between the two organizations.
- 2) The formal decisions or agreements of IEC on technical matters express, as nearly as possible, an international consensus of opinion on the relevant subjects since each technical committee has representation from all interested IEC National Committees.
- 3) IEC Publications have the form of recommendations for international use and are accepted by IEC National Committees in that sense. While all reasonable efforts are made to ensure that the technical content of IEC Publications is accurate, IEC cannot be held responsible for the way in which they are used or for any misinterpretation by any end user.
- 4) In order to promote international uniformity, IEC National Committees undertake to apply IEC Publications transparently to the maximum extent possible in their national and regional publications. Any divergence between any IEC Publication and the corresponding national or regional publication shall be clearly indicated in the latter.
- 5) IEC itself does not provide any attestation of conformity. Independent certification bodies provide conformity assessment services and, in some areas, access to IEC marks of conformity. IEC is not responsible for any services carried out by independent certification bodies.
- 6) All users should ensure that they have the latest edition of this publication.
- 7) No liability shall attach to IEC or its directors, employees, servants or agents including individual experts and members of its technical committees and IEC National Committees for any personal injury, property damage or other damage of any nature whatsoever, whether direct or indirect, or for costs (including legal fees) and expenses arising out of the publication, use of, or reliance upon, this IEC Publication or any other IEC Publications.
- 8) Attention is drawn to the Normative references cited in this publication. Use of the referenced publications is indispensable for the correct application of this publication.
- 9) Attention is drawn to the possibility that some of the elements of this IEC Publication may be the subject of patent rights. IEC shall not be held responsible for identifying any or all such patent rights.

International Standard IEC 62827-2 has been prepared by technical area 15: Wireless power transfer, of IEC technical committee 100: Audio, video and multimedia systems and equipment.

The text of this International Standard is based on the following documents:

FDIS	Report on voting
100/2900/FDIS	100/2939/RVD

Full information on the voting for the approval of this International Standard can be found in the report on voting indicated in the above table.

This document has been drafted in accordance with the ISO/IEC Directives, Part 2.

The committee has decided that the contents of this document will remain unchanged until the stability date indicated on the IEC website under "<http://webstore.iec.ch>" in the data related to the specific document. At this date, the document will be

- reconfirmed,
- withdrawn,
- replaced by a revised edition, or
- amended.

A bilingual version of this publication may be issued at a later date.

**IMPORTANT – The 'colour inside' logo on the cover page of this publication indicates that it contains colours which are considered to be useful for the correct understanding of its contents. Users should therefore print this document using a colour printer.**

## INTRODUCTION

The IEC 62827 (Wireless Power Transfer – Management) series provides the management protocol for a wireless power transfer system in which power sources can deliver power to receivers at a distance. The IEC 62827 series consists of the following parts:

- Part 1: Common components
- Part 2: Multiple device control management
- Part 3: Multiple source control management

Part 1 of IEC 62827 defines the definition and functionality for wireless power transfer systems.

Part 2 of IEC 62827 specifies the management protocol of wireless power transfer for multiple devices.

Part 3 of IEC 62827 specifies the management protocol of wireless power transfer for multiple sources.



## **WIRELESS POWER TRANSFER – MANAGEMENT –**

### **Part 2: Multiple device control management**

#### **1 Scope**

This part of IEC 62827 defines a wireless power management protocol for wireless power transfer to multiple devices in a wireless power management system. Various functions of wireless power management systems are justified. The wireless power management frames and messages that work between the management block of a power source and the management block or the coupler block of a device, or the coupler block of a power source, are defined as well to execute various functions. Also, the procedures for each functionality are described based on its frames and messages.

#### **2 Normative references**

The following documents are referred to in the text in such a way that some or all of their content constitutes requirements of this document. For dated references, only the edition cited applies. For undated references, the latest edition of the referenced document (including any amendments) applies.

IEC 62827-1, *Wireless power transfer – Management – Part 1: Common components*