



IEC 62106-3

Edition 1.0 2018-09

INTERNATIONAL STANDARD

**Radio data system (RDS) – VHF/FM sound broadcasting in the frequency range
from 64,0 MHz to 108,0 MHz –
Part 3: Usage and registration of Open Data Applications (ODAs)**

INTERNATIONAL
ELECTROTECHNICAL
COMMISSION

ICS 33.160.40

ISBN 978-2-8322-6068-5

Warning! Make sure that you obtained this publication from an authorized distributor.

CONTENTS

FOREWORD.....	3
INTRODUCTION.....	5
1 Scope.....	7
2 Normative references	7
3 Terms, definitions, abbreviated terms and conventions	7
3.1 Terms and definitions.....	7
3.2 Abbreviated terms.....	7
3.3 Notation and conventions.....	7
4 ODA usage.....	8
4.1 General.....	8
4.2 ODA group structures	8
4.3 ODA coding for group type A or B	9
4.3.1 General	9
4.3.2 Group type 3A: ODA Application Identification (AID).....	9
4.3.3 ODA group availability signalled in group type 3A for legacy data	10
4.4 ODA coding for group type C on data-streams 1, 2 and 3.....	11
4.4.1 General	11
4.4.2 Group type C ODA Application Identification (AID) to channel number assignment on data-streams 1, 2 and 3	12
5 ODA registration	12
5.1 General.....	12
5.2 ODA-AID codes reserved for testing with no registration being required.....	12
Annex A (informative) Open data registration.....	13
Bibliography.....	20
Figure 1 – 37-bit ODA group type A structure.....	8
Figure 2 – 21-bit ODA group type B structure.....	8
Figure 3 – 56-bit or 7-byte ODA group type C structure.....	8
Figure 4 – Group type 3A for Application group type code, AID and 16-bits of ODA data	9
Table 1 – ODA group availability signalled in group type 3A for legacy ODAs	11

INTERNATIONAL ELECTROTECHNICAL COMMISSION

**RADIO DATA SYSTEM (RDS) –
VHF/FM SOUND BROADCASTING IN THE FREQUENCY
RANGE FROM 64,0 MHz TO 108,0 MHz –****Part 3: Usage and registration of Open Data Applications (ODAs)**

FOREWORD

- 1) The International Electrotechnical Commission (IEC) is a worldwide organization for standardization comprising all national electrotechnical committees (IEC National Committees). The object of IEC is to promote international co-operation on all questions concerning standardization in the electrical and electronic fields. To this end and in addition to other activities, IEC publishes International Standards, Technical Specifications, Technical Reports, Publicly Available Specifications (PAS) and Guides (hereafter referred to as "IEC Publication(s)"). Their preparation is entrusted to technical committees; any IEC National Committee interested in the subject dealt with may participate in this preparatory work. International, governmental and non-governmental organizations liaising with the IEC also participate in this preparation. IEC collaborates closely with the International Organization for Standardization (ISO) in accordance with conditions determined by agreement between the two organizations.
- 2) The formal decisions or agreements of IEC on technical matters express, as nearly as possible, an international consensus of opinion on the relevant subjects since each technical committee has representation from all interested IEC National Committees.
- 3) IEC Publications have the form of recommendations for international use and are accepted by IEC National Committees in that sense. While all reasonable efforts are made to ensure that the technical content of IEC Publications is accurate, IEC cannot be held responsible for the way in which they are used or for any misinterpretation by any end user.
- 4) In order to promote international uniformity, IEC National Committees undertake to apply IEC Publications transparently to the maximum extent possible in their national and regional publications. Any divergence between any IEC Publication and the corresponding national or regional publication shall be clearly indicated in the latter.
- 5) IEC itself does not provide any attestation of conformity. Independent certification bodies provide conformity assessment services and, in some areas, access to IEC marks of conformity. IEC is not responsible for any services carried out by independent certification bodies.
- 6) All users should ensure that they have the latest edition of this publication.
- 7) No liability shall attach to IEC or its directors, employees, servants or agents including individual experts and members of its technical committees and IEC National Committees for any personal injury, property damage or other damage of any nature whatsoever, whether direct or indirect, or for costs (including legal fees) and expenses arising out of the publication, use of, or reliance upon, this IEC Publication or any other IEC Publications.
- 8) Attention is drawn to the Normative references cited in this publication. Use of the referenced publications is indispensable for the correct application of this publication.
- 9) Attention is drawn to the possibility that some of the elements of this IEC Publication may be the subject of patent rights. IEC shall not be held responsible for identifying any or all such patent rights.

International Standard IEC 62106-3 has been prepared by technical area 1: Terminals for audio, video and data services and contents, of IEC technical committee 100: Audio, video and multimedia systems and equipment.

This first edition, together with IEC 62106-1, IEC 62106-2, IEC 62106-4, IEC 62106-5 and IEC 62106-6, cancels and replaces IEC 62106:2015, and constitutes a technical revision.

This edition includes the following significant technical changes with respect to IEC 62106:2015:

- Provision has been made to carry RDS on multiple data-streams (RDS2).
- For Open Data Applications, in addition to the already existing 37-bit and 21-bit data group structures a new 56-bit or 7-byte data group structure has been added.

- New are AF coding below 87,6 MHz (down to 64,1 MHz) using ODA-AID. RT+ can now be used with RT and eRT, 0x6365, see IEC 62106-6.

The text of this standard is based on the following documents:

CDV	Report on voting
100/2911/CDV	100/3057/RVC

Full information on the voting for the approval of this International Standard can be found in the report on voting indicated in the above table.

This document has been drafted in accordance with the ISO/IEC Directives, Part 2.

A list of all parts in the IEC 62106 series, published under the general title *Radio data system (RDS) – VHF/FM sound broadcasting in the frequency range from 64,0 MHz to 108,0 MHz*, can be found on the IEC website.

The committee has decided that the contents of this document will remain unchanged until the stability date indicated on the IEC website under "<http://webstore.iec.ch>" in the data related to the specific document. At this date, the document will be

- reconfirmed,
- withdrawn,
- replaced by a revised edition, or
- amended.

A bilingual version of this publication may be issued at a later date.

INTRODUCTION

Since the mid-1980s a fascinating development has taken place. Most of the multimedia applications and standards have been created or redefined significantly. Hardware has become extremely powerful with dedicated software and middleware. In the mid-1980s, Internet as well as its protocols did not exist. Navigation systems became affordable in the late 1990s, and a full range of attractive smartphones now exist. The computing power of all these new products is comparable with that of the mainframe installations in that era.

Listener expectations have grown faster than the technology. Visual experience is now very important, like the Internet look and feel. Scrolling text or delivering just audio is nowadays perceived as insufficient for FM radio, specifically for smartphone users. New types of radio receivers with added value features are therefore required. RDS has so far proven to be very successful.

FM radio with RDS is an analogue-digital hybrid system, which is still a valid data transmission technology and only the applications need adaptation. Now the time has come to solve the only disadvantage, the lack of sufficient data capacity. With RDS2, the need to increase the data capacity can be fulfilled.

RDS was introduced in the early 1980s. During the introductory phase in Europe, the car industry became very involved and that was the start of an extremely successful roll-out. Shortly afterwards, RDS (RBDS) was launched in the USA [1, 2, 3, 4, 5]¹.

The RDS Forum has investigated a solution to the issue of limited data capacity. For RDS2, both sidebands around the RDS 57 kHz subcarrier can be repeated a few times, up to three, centred on additional subcarriers higher up in the FM multiplex while still remaining compatible with the ITU Recommendations.

The core elements of RDS2 are the additional subcarriers, which will enable a significant increase of RDS data capacity to be achieved, and then only new additional data applications will have to be created, using the RDS-ODA feature, which has been part of the RDS standard for many years.

In order to update IEC 62106:2015 to the specifications of RDS2, IEC 62106 has been restructured as follows:

Part 1: Modulation characteristics and baseband coding

Part 2: RDS message format, coding and definition of RDS features

Part 3: Coding and registration of Open Data Applications ODAs

Part 4: Registered code tables

Part 5: Marking of RDS and RDS2 devices

Part 6: Compilation of technical specifications for Open Data Applications in the public domain

The following future parts are planned:

Part 7: RBDS

Part 8: Universal Encoder Communication Protocol UECP

¹ Numbers in square brackets refer to the Bibliography.

The original specifications of the RDS system have been maintained and the extra functionalities of RDS2 have been added.

Obsolete or unused functions from the original RDS standard IEC 62106:2015 have been deleted. The presentation in Parts 1, 2 and 3 follows the OSI basic reference model for information processing systems [6].

**RADIO DATA SYSTEM (RDS) –
VHF/FM SOUND BROADCASTING IN THE FREQUENCY
RANGE FROM 64,0 MHz TO 108,0 MHz –**

Part 3: Usage and registration of Open Data Applications (ODAs)

1 Scope

This part of IEC 62106 defines the Open Data Application (ODA) feature of the Radio Data System (RDS).

The ODA feature in essence allows raw data to be transmitted via a transparent data channel from a service provider to a suitably equipped receiver without there being any prior knowledge of the data content by the IEC 62106 standard. This document defines the method of packaging the data within the RDS group structure and the identification of the data (using the Application Identification, AID) such that it can be addressed by an appropriate decoder on the receiver.

2 Normative references

The following documents are referred to in the text in such a way that some or all of their content constitutes requirements of this document. For dated references, only the edition cited applies. For undated references, the latest edition of the referenced document (including any amendments) applies.

IEC 62106 (all parts), *Radio Data System (RDS) – VHF/FM sound broadcasting in the frequency range from 64,0 MHz to 108,0 MHz*