



IEC 62358

Edition 3.0 2026-01

INTERNATIONAL STANDARD

Ferrite cores - Standard inductance factor for gapped cores and its tolerance

CONTENTS

FOREWORD.....	2
INTRODUCTION.....	4
1 Scope.....	5
2 Normative references	5
3 Terms and definitions	5
4 Measuring method	5
5 A_L value and its tolerance	5
5.1 General.....	5
5.2 Tolerance	5
5.3 E-core.....	5
5.4 ETD-core and EER-core	6
5.5 EP-core	6
5.6 RM-core.....	6
5.7 Pot-core.....	6
5.8 PQ-core	6
5.9 Low-profile core	6
5.10 PM-cores	6
5.11 EC-cores	6
5.12 EFD-cores	6
Bibliography.....	19
Table 1 – Tolerance versus letter code	5
Table 2 – A_L and its tolerance for E-cores (IEC 63093-8).....	7
Table 3 – A_L and its tolerance for ETD-cores (IEC 63093-6) and EER-cores (IEC 63093-7)	8
Table 4 – A_L and its tolerance for EP-cores (IEC 63093-5)	9
Table 5 – A_L and its tolerance for RM-cores (IEC 63093-4).....	10
Table 6 – A_L and its tolerance for Pot-cores (IEC 63093-2).....	10
Table 7 – A_L and its tolerance for PQ-cores (IEC 63093-13)	11
Table 8 – A_L and its tolerance for EL-cores (IEC 63093-9).....	12
Table 9 – A_L and its tolerance for EL-I (plate)-cores (IEC 63093-9)	12
Table 10 – A_L and its tolerance for low-profile ER-I (plate)-cores (IEC 63093-9)	13
Table 11 – A_L and its tolerance for low-profile ER-cores (IEC 63093-9)	14
Table 12 – A_L and its tolerance for low-profile E-I (plate)-cores (IEC 63093-9)	15
Table 13 – A_L and its tolerance for low-profile E-cores (IEC 63093-9).....	15
Table 14 – A_L and its tolerance for low-profile RM cores (IEC 63093-4).....	16
Table 15 – A_L and its tolerance for low-profile PQ-I (plate)-cores (IEC 63093-13)	16
Table 16 – A_L and its tolerance for PM-cores (IEC 63093-10)	17
Table 17 – A_L and its tolerance for EC-cores (IEC 63093-11)	17
Table 18 – A_L and its tolerance for EFD-cores (IEC 63093-14)	18

INTERNATIONAL ELECTROTECHNICAL COMMISSION

**Ferrite cores -
Standard inductance factor for gapped cores and its tolerance**

FOREWORD

- 1) The International Electrotechnical Commission (IEC) is a worldwide organization for standardization comprising all national electrotechnical committees (IEC National Committees). The object of IEC is to promote international co-operation on all questions concerning standardization in the electrical and electronic fields. To this end and in addition to other activities, IEC publishes International Standards, Technical Specifications, Technical Reports, Publicly Available Specifications (PAS) and Guides (hereafter referred to as "IEC Publication(s)"). Their preparation is entrusted to technical committees; any IEC National Committee interested in the subject dealt with may participate in this preparatory work. International, governmental and non-governmental organizations liaising with the IEC also participate in this preparation. IEC collaborates closely with the International Organization for Standardization (ISO) in accordance with conditions determined by agreement between the two organizations.
- 2) The formal decisions or agreements of IEC on technical matters express, as nearly as possible, an international consensus of opinion on the relevant subjects since each technical committee has representation from all interested IEC National Committees.
- 3) IEC Publications have the form of recommendations for international use and are accepted by IEC National Committees in that sense. While all reasonable efforts are made to ensure that the technical content of IEC Publications is accurate, IEC cannot be held responsible for the way in which they are used or for any misinterpretation by any end user.
- 4) In order to promote international uniformity, IEC National Committees undertake to apply IEC Publications transparently to the maximum extent possible in their national and regional publications. Any divergence between any IEC Publication and the corresponding national or regional publication shall be clearly indicated in the latter.
- 5) IEC itself does not provide any attestation of conformity. Independent certification bodies provide conformity assessment services and, in some areas, access to IEC marks of conformity. IEC is not responsible for any services carried out by independent certification bodies.
- 6) All users should ensure that they have the latest edition of this publication.
- 7) No liability shall attach to IEC or its directors, employees, servants or agents including individual experts and members of its technical committees and IEC National Committees for any personal injury, property damage or other damage of any nature whatsoever, whether direct or indirect, or for costs (including legal fees) and expenses arising out of the publication, use of, or reliance upon, this IEC Publication or any other IEC Publications.
- 8) Attention is drawn to the Normative references cited in this publication. Use of the referenced publications is indispensable for the correct application of this publication.
- 9) IEC draws attention to the possibility that the implementation of this document may involve the use of (a) patent(s). IEC takes no position concerning the evidence, validity or applicability of any claimed patent rights in respect thereof. As of the date of publication of this document, IEC had not received notice of (a) patent(s), which may be required to implement this document. However, implementers are cautioned that this may not represent the latest information, which may be obtained from the patent database available at <https://patents.iec.ch>. IEC shall not be held responsible for identifying any or all such patent rights.

IEC 62358 has been prepared by IEC technical committee 51: Magnetic components, ferrite and magnetic powder materials. It is an International Standard.

This third edition cancels and replaces the second edition published in 2012. This edition constitutes a technical revision.

This edition includes the following significant technical changes with respect to the previous edition:

- a) addition of A_L value (inductance factor) and its tolerance for PM-cores;
- b) addition of A_L value (inductance factor) and its tolerance for EC-cores;
- c) addition of A_L value (inductance factor) and its tolerance for EFD-cores.

The text of this International Standard is based on the following documents:

Draft	Report on voting
51/1583/FDIS	51/1595/RVD

Full information on the voting for its approval can be found in the report on voting indicated in the above table.

The language used for the development of this International Standard is English.

This document was drafted in accordance with ISO/IEC Directives, Part 2, and developed in accordance with ISO/IEC Directives, Part 1 and ISO/IEC Directives, IEC Supplement, available at www.iec.ch/members_experts/refdocs. The main document types developed by IEC are described in greater detail at www.iec.ch/publications.

The committee has decided that the contents of this document will remain unchanged until the stability date indicated on the IEC website under webstore.iec.ch in the data related to the specific document. At this date, the document will be

- reconfirmed,
- withdrawn, or
- revised.

INTRODUCTION

The A_L value (inductance factor) and its tolerance is a critical design parameter for gapped ferrite core sets. For any core size, there is a wide range of possible gapped A_L values, and there is no technical reason why a user could not select any precise value within the possible range. But as a practical matter, there are advantages to the users that certain values within the range are identified to be standard and to the users in selecting those values where possible.

The potential advantages include faster delivery from supplier inventories of standard gapped parts, greater ease of obtaining small quantities for development sampling and low-volume projects, interchangeability among multiple applications, reduced risk of dead inventories, economies of scale from producing larger batches, and standardized tolerancing across multiple suppliers.

It is important that users specify A_L values by selecting them from this document when possible. The tolerances shown in this document are selected for suitable performance with best cost and full interchangeability. Suppliers may offer tighter tolerances for their standard parts while remaining in compliance with the standard. Users can require tighter tolerances for specific applications.

In cases where users or suppliers specify a physical gap length with tolerances, then the A_L value will only be approximate and without tolerance. It is generally true that better measurement precision and better consistency in application performance is achieved by specifying the A_L value and not the gap dimension. The exceptions are cases in which the gap is quite large, where users can find that their application coil gives a more consistent result if the gap dimension is controlled directly and the A_L value as measured in the supplier's standard coil is allowed to vary.

1 Scope

This document provides standard A_L values (inductance factors) and their tolerances of Pot, RM, ETD, E, EER, EP, PQ, PM, EC, EFD and low-profile gapped ferrite cores.

2 Normative references

The following documents are referred to in the text in such a way that some or all of their content constitutes requirements of this document. For dated references, only the edition cited applies. For undated references, the latest edition of the referenced document (including any amendments) applies.

IEC 62044-2, *Cores made of soft magnetic materials - Measuring methods - Part 2: Magnetic properties at low excitation level*

ISO 497, *Guide to the choice of series of preferred numbers and of series containing more rounded values of preferred numbers*

Bibliography

IEC 63093-2, *Ferrite cores - Guidelines on dimensions and the limits of surface irregularities - Part 2: Pot-cores for use in telecommunications, power supply, and filter applications*

IEC 63093-4, *Ferrite cores - Guidelines on dimensions and the limits of surface irregularities - Part 4: RM-cores*

IEC 63093-5, *Ferrite cores - Guidelines on dimensions and the limits of surface irregularities - Part 5: EP-cores and associated parts for use in inductors and transformers*

IEC 63093-6, *Ferrite cores - Guidelines on dimensions and the limits of surface irregularities - Part 6: ETD-cores for use in power supplies*

IEC 63093-7, *Ferrite cores - Guidelines on dimensions and the limits of surface irregularities - Part 7: EER-cores*

IEC 63093-8, *Ferrite cores - Guidelines on dimensions and the limits of surface irregularities - Part 8: E-cores*

IEC 63093-9, *Ferrite cores - Guidelines on dimensions and the limits of surface irregularities - Part 9: Planar cores*

IEC 63093-10, *Ferrite cores - Guidelines on dimensions and the limits of surface irregularities - Part 10: PM-cores and associated parts*

IEC 63093-11, *Ferrite cores - Guidelines on dimensions and the limits of surface irregularities - Part 11: EC-cores for use in power supply applications*

IEC 63093-13, *Ferrite cores - Guidelines on dimensions and the limits of surface irregularities - Part 13: PQ-cores*

IEC 63093-14, *Ferrite cores - Guidelines on dimensions and the limits of surface irregularities - Part 14: EFD-cores*
