



IEC 62680-1-3

Edition 7.0 2026-02

# INTERNATIONAL STANDARD

---

**Universal Serial Bus interfaces for data and power -  
Part 1-3: Common components - USB Type-C® cable and connector  
specification**



## **THIS PUBLICATION IS COPYRIGHT PROTECTED**

**Copyright © 2026 IEC, Geneva, Switzerland**

All rights reserved. Unless otherwise specified, no part of this publication may be reproduced or utilized in any form or by any means, electronic or mechanical, including photocopying and microfilm, without permission in writing from either IEC or IEC's member National Committee in the country of the requester. If you have any questions about IEC copyright or have an enquiry about obtaining additional rights to this publication, please contact the address below or your local IEC member National Committee for further information.

IEC Secretariat  
3, rue de Varembeé  
CH-1211 Geneva 20  
Switzerland

Tel.: +41 22 919 02 11  
[info@iec.ch](mailto:info@iec.ch)  
[www.iec.ch](http://www.iec.ch)

### **About the IEC**

The International Electrotechnical Commission (IEC) is the leading global organization that prepares and publishes International Standards for all electrical, electronic and related technologies.

### **About IEC publications**

The technical content of IEC publications is kept under constant review by the IEC. Please make sure that you have the latest edition, a corrigendum or an amendment might have been published.

#### **IEC publications search -**

[webstore.iec.ch/advsearchform](http://webstore.iec.ch/advsearchform)

The advanced search enables to find IEC publications by a variety of criteria (reference number, text, technical committee, ...). It also gives information on projects, replaced and withdrawn publications.

#### **IEC Just Published - [webstore.iec.ch/justpublished](http://webstore.iec.ch/justpublished)**

Stay up to date on all new IEC publications. Just Published details all new publications released. Available online and once a month by email.

#### **IEC Customer Service Centre - [webstore.iec.ch/csc](http://webstore.iec.ch/csc)**

If you wish to give us your feedback on this publication or need further assistance, please contact the Customer Service Centre: [sales@iec.ch](mailto:sales@iec.ch).

#### **IEC Products & Services Portal - [products.iec.ch](http://products.iec.ch)**

Discover our powerful search engine and read freely all the publications previews, graphical symbols and the glossary. With a subscription you will always have access to up to date content tailored to your needs.

#### **Electropedia - [www.electropedia.org](http://www.electropedia.org)**

The world's leading online dictionary on electrotechnology, containing more than 22 500 terminological entries in English and French, with equivalent terms in 25 additional languages. Also known as the International Electrotechnical Vocabulary (IEV) online.

**Warning! Make sure that you obtained this publication from an authorized distributor.**

INTERNATIONAL ELECTROTECHNICAL COMMISSION

---

**Universal Serial Bus interfaces for data and power -  
Part 1-3: Common components - USB Type-C® cable and connector  
specification**

**FOREWORD**

- 1) The International Electrotechnical Commission (IEC) is a worldwide organization for standardization comprising all national electrotechnical committees (IEC National Committees). The object of IEC is to promote international co-operation on all questions concerning standardization in the electrical and electronic fields. To this end and in addition to other activities, IEC publishes International Standards, Technical Specifications, Technical Reports, Publicly Available Specifications (PAS) and Guides (hereafter referred to as "IEC Publication(s)"). Their preparation is entrusted to technical committees; any IEC National Committee interested in the subject dealt with may participate in this preparatory work. International, governmental and non-governmental organizations liaising with the IEC also participate in this preparation. IEC collaborates closely with the International Organization for Standardization (ISO) in accordance with conditions determined by agreement between the two organizations.
- 2) The formal decisions or agreements of IEC on technical matters express, as nearly as possible, an international consensus of opinion on the relevant subjects since each technical committee has representation from all interested IEC National Committees.
- 3) IEC Publications have the form of recommendations for international use and are accepted by IEC National Committees in that sense. While all reasonable efforts are made to ensure that the technical content of IEC Publications is accurate, IEC cannot be held responsible for the way in which they are used or for any misinterpretation by any end user.
- 4) In order to promote international uniformity, IEC National Committees undertake to apply IEC Publications transparently to the maximum extent possible in their national and regional publications. Any divergence between any IEC Publication and the corresponding national or regional publication shall be clearly indicated in the latter.
- 5) IEC itself does not provide any attestation of conformity. Independent certification bodies provide conformity assessment services and, in some areas, access to IEC marks of conformity. IEC is not responsible for any services carried out by independent certification bodies.
- 6) All users should ensure that they have the latest edition of this publication.
- 7) No liability shall attach to IEC or its directors, employees, servants or agents including individual experts and members of its technical committees and IEC National Committees for any personal injury, property damage or other damage of any nature whatsoever, whether direct or indirect, or for costs (including legal fees) and expenses arising out of the publication, use of, or reliance upon, this IEC Publication or any other IEC Publications.
- 8) Attention is drawn to the Normative references cited in this publication. Use of the referenced publications is indispensable for the correct application of this publication.
- 9) IEC draws attention to the possibility that the implementation of this document may involve the use of (a) patent(s). IEC takes no position concerning the evidence, validity or applicability of any claimed patent rights in respect thereof. As of the date of publication of this document, IEC had received notice of (a) patent(s), which may be required to implement this document. However, implementers are cautioned that this may not represent the latest information, which may be obtained from the patent database available at <https://patents.iec.ch>. IEC shall not be held responsible for identifying any or all such patent rights.

IEC 62680-1-3 has been prepared by technical area 18: Multimedia home systems and applications for end-user networks, of IEC technical committee 100: Audio, video and multimedia systems and equipment. It is an International Standard.

The text of this standard was prepared by the USB Implementers Forum (USB-IF). The structure and editorial rules used in this publication reflect the practice of the organization which submitted it.

The text of this International Standard is based on the following documents:

Draft	Report on voting
100/4332/CDV	100/4381/RVC

Full information on the voting for its approval can be found in the report on voting indicated in the above table.

A list of all parts in the IEC 62680 series, published under the general title *Universal serial bus interfaces for data and power*, can be found on the IEC website.

The committee has decided that the contents of this document will remain unchanged until the stability date indicated on the IEC website under [webstore.iec.ch](http://webstore.iec.ch) in the data related to the specific document. At this date, the document will be

- reconfirmed,
- withdrawn, or
- revised.

# **Universal Serial Bus Type-C Cable and Connector Specification**

**Release 2.4  
October 2024**

**Copyright © 2014-2024, USB 3.0 Promoter Group:**

**Apple Inc., HP Inc., Intel Corporation, Microsoft Corporation,  
Renesas, STMicroelectronics, and Texas Instruments**

**All rights reserved.**

NOTE: Adopters may only use the USB Type-C® cable and connector to implement USB or third-party functionality as expressly described in this Specification; all other uses are prohibited.

LIMITED COPYRIGHT LICENSE: The USB 3.0 Promoters grant a conditional copyright license under the copyrights embodied in the USB Type-C Cable and Connector Specification to use and reproduce the Specification for the sole purpose of, and solely to the extent necessary for, evaluating whether to implement the Specification in products that would comply with the specification. Without limiting the foregoing, use of the Specification for the purpose of filing or modifying any patent application to target the Specification or USB compliant products is not authorized. Except for this express copyright license, no other rights or licenses are granted, including without limitation any patent licenses. In order to obtain any additional intellectual property licenses or licensing commitments associated with the Specification a party must execute the USB 3.0 Adopters Agreement. NOTE: By using the Specification, you accept these license terms on your own behalf and, in the case where you are doing this as an employee, on behalf of your employer.

**INTELLECTUAL PROPERTY DISCLAIMER**

THIS SPECIFICATION IS PROVIDED TO YOU "AS IS" WITH NO WARRANTIES WHATSOEVER, INCLUDING ANY WARRANTY OF MERCHANTABILITY, NON-INFRINGEMENT, OR FITNESS FOR ANY PARTICULAR PURPOSE. THE AUTHORS OF THIS SPECIFICATION DISCLAIM ALL LIABILITY, INCLUDING LIABILITY FOR INFRINGEMENT OF ANY PROPRIETARY RIGHTS, RELATING TO USE OR IMPLEMENTATION OF INFORMATION IN THIS SPECIFICATION. THE PROVISION OF THIS SPECIFICATION TO YOU DOES NOT PROVIDE YOU WITH ANY LICENSE, EXPRESS OR IMPLIED, BY ESTOPPEL OR OTHERWISE, TO ANY INTELLECTUAL PROPERTY RIGHTS.

All implementation examples and reference designs contained within this Specification are included as part of the limited patent license for those companies that execute the USB 3.0 Adopters Agreement.

USB Type-C®, USB-C® and USB4® are trademarks of the Universal Serial Bus Implementers Forum (USB-IF). DisplayPort™ is a trademark of VESA. All product names are trademarks, registered trademarks, or service marks of their respective owners.

Thunderbolt™ is a trademark of Intel Corporation. You may only use the Thunderbolt™ trademark or logo in conjunction with products designed to this specification that complete proper certification and executing a Thunderbolt™ trademark license – see <https://www.usb.org/compliance> for further information.

## Contents

Specification Editor .....	20
Specification Work Group Contributors.....	20
Pre-Release Draft Industry Reviewing Companies That Provided Feedback.....	28
Revision History.....	29
<b>1 Introduction.....</b>	<b>30</b>
1.1 Purpose .....	30
1.2 Scope .....	30
1.3 Related Documents .....	30
1.4 Conventions.....	31
1.4.1 Precedence .....	31
1.4.2 Keywords .....	31
1.4.3 Numbering.....	32
1.5 Terms and Abbreviations .....	32
<b>2 Overview .....</b>	<b>38</b>
2.1 Introduction .....	38
2.2 USB Type-C Receptacles, Plugs and Cables .....	39
2.3 Configuration Process.....	40
2.3.1 Source-to-Sink Attach/Detach Detection.....	41
2.3.2 Plug Orientation/Cable Twist Detection.....	41
2.3.3 Initial Power (Source-to-Sink) Detection and Establishing the Data (Host-to-Device) Relationship 41	41
2.3.4 USB Type-C VBUS Current Detection and Usage.....	42
2.3.5 <i>USB PD</i> Communications.....	42
2.3.6 Functional Extensions .....	43
2.4 VBUS.....	43
2.5 VCONN.....	43
2.6 Hubs.....	44
<b>3 Mechanical.....</b>	<b>45</b>
3.1 Overview.....	45
3.1.1 Compliant Connectors.....	45
3.1.2 Compliant Cable Assemblies .....	45
3.1.3 Compliant USB Type-C to Legacy Cable Assemblies.....	46
3.1.4 Compliant USB Type-C to Legacy Adapter Assemblies.....	47
3.2 USB Type-C Connector Mating Interfaces.....	47
3.2.1 Interface Definition.....	47
3.2.2 Reference Designs .....	71

3.2.3	Pin Assignments and Descriptions .....	78
3.3	Cable Construction and Wire Assignments .....	79
3.3.1	Cable Construction ( <i>Informative</i> ).....	79
3.3.2	Wire Assignments .....	81
3.3.3	Wire Gauges and Cable Diameters ( <i>Informative</i> ).....	82
3.4	Standard USB Type-C Cable Assemblies.....	84
3.4.1	USB Full-Featured Type-C Cable Assembly.....	84
3.4.2	USB 2.0 Type-C Cable Assembly .....	86
3.4.3	USB Type-C Captive Cable Assembly .....	86
3.4.4	USB Type-C Thumb Drive Assembly .....	87
3.5	Legacy Cable Assemblies.....	87
3.5.1	USB Type-C to USB 3.1 Standard-A Cable Assembly .....	88
3.5.2	USB Type-C to USB 2.0 Standard-A Cable Assembly .....	89
3.5.3	USB Type-C to USB 3.1 Standard-B Cable Assembly .....	90
3.5.4	USB Type-C to USB 2.0 Standard-B Cable Assembly .....	91
3.5.5	USB Type-C to USB 2.0 Mini-B Cable Assembly.....	92
3.5.6	USB Type-C to USB 3.1 Micro-B Cable Assembly .....	93
3.5.7	USB Type-C to USB 2.0 Micro-B Cable Assembly .....	94
3.6	Legacy Adapter Assemblies.....	94
3.6.1	USB Type-C to USB 3.1 Standard-A Receptacle Adapter Assembly .....	94
3.6.2	USB Type-C to USB 2.0 Micro-B Receptacle Adapter Assembly .....	96
3.7	Electrical Characteristics.....	96
3.7.1	Raw Cable ( <i>Informative</i> ).....	97
3.7.2	USB Type-C to USB Type-C Passive Cable Assemblies .....	98
3.7.3	Mated Connector ( <i>Informative – USB 3.2 Gen2 and USB4 Gen2</i> ).....	120
3.7.4	Receptacle Connector SI Requirements and Testing ( <i>Normative – USB4 Gen3/Gen4</i> ).....	124
3.7.5	USB Type-C to USB Legacy Cable Assemblies ( <i>Normative</i> ) .....	126
3.7.6	USB Type-C to USB Legacy Adapter Assemblies ( <i>Normative</i> ) .....	130
3.7.7	Shielding Effectiveness Requirements ( <i>Normative</i> ) .....	133
3.7.8	DC Electrical Requirements ( <i>Normative</i> ).....	135
3.8	Mechanical and Environmental Requirements ( <i>Normative</i> ).....	138
3.8.1	Mechanical Requirements .....	138
3.8.2	Environmental Requirements.....	143
3.9	Docking Applications ( <i>Informative</i> ) .....	144
3.10	Implementation Notes and Design Guides .....	145
3.10.1	EMC Management ( <i>Informative</i> ) .....	145

3.10.2	Stacked and Side-by-Side Connector Physical Spacing ( <i>Informative</i> ) .....	148
3.10.3	Cable Mating Considerations ( <i>Informative</i> ) .....	148
3.11	Extended Power Range (EPR) Cables .....	150
3.11.1	Electrical Requirements.....	150
3.11.2	EPR Cable Identification Requirements.....	150
4	Functional .....	151
4.1	Signal Summary.....	151
4.2	Signal Pin Descriptions .....	151
4.2.1	USB 3.2/USB4 Pins .....	151
4.2.2	USB 2.0 Pins.....	152
4.2.3	Auxiliary Signal Pins .....	152
4.2.4	Power and Ground Pins .....	152
4.2.5	Configuration Pins .....	152
4.3	Sideband Use (SBU).....	152
4.4	Power and Ground.....	153
4.4.1	IR Drop.....	153
4.4.2	VBUS .....	154
4.4.3	VCONN .....	155
4.5	Configuration Channel (CC) .....	160
4.5.1	Architectural Overview.....	160
4.5.2	CC Functional and Behavioral Requirements .....	172
4.5.3	USB Port Interoperability Behavior .....	208
4.6	Power .....	226
4.6.1	Power Requirements during USB Suspend.....	227
4.6.2	VBUS Power Provided Over a USB Type-C Cable .....	228
4.7	USB Hubs .....	233
4.8	Power Sourcing and Charging.....	234
4.8.1	DFP as a Power Source.....	234
4.8.2	Non-USB Charging Methods .....	236
4.8.3	Sinking Host.....	237
4.8.4	Sourcing Device.....	237
4.8.5	Charging a System with a Dead Battery .....	237
4.8.6	USB Type-C Multi-Port Chargers .....	237
4.9	Electronically Marked Cables .....	241
4.9.1	Parameter Values.....	242
4.9.2	Active Cables.....	242

4.10	VCONN-Powered Accessories (VPAs) and VCONN-Powered USB Devices (VPDs).....	243
4.10.1	VCONN-Powered Accessories (VPAs).....	243
4.10.2	VCONN-Powered Devices (VPDs).....	243
4.11	Parameter Values .....	245
4.11.1	Termination Parameters .....	245
4.11.2	Timing Parameters.....	247
4.11.3	Voltage Parameters .....	251
5	USB4 Discovery and Entry .....	258
5.1	Overview of the Discovery and Entry Process .....	258
5.2	USB4 Functional Requirements .....	259
5.2.1	USB4 Host Functional Requirements.....	259
5.2.2	USB Device Functional Requirements.....	259
5.2.3	USB4 Alternate Mode Support.....	259
5.3	USB4 Power Requirements.....	260
5.3.1	Source Power Requirements .....	260
5.3.2	Sink Power Requirements .....	260
5.3.3	Device Power Management Requirements .....	260
5.4	USB4 Discovery and Entry Flow Requirements .....	261
5.4.1	USB Type-C Initial Connection .....	261
5.4.2	USB Power Delivery Contract.....	261
5.4.3	USB4 Discovery and Entry Flow .....	261
5.4.4	USB4 Post-Entry Operation.....	267
5.5	USB4 Hub Connection Requirements.....	267
5.5.1	USB4 Hub Port Initial Connection Requirements.....	267
5.5.2	USB4 Hub UFP and Host Capabilities Discovery.....	267
5.5.3	Hub DFP Connection Requirements .....	268
5.5.4	Hub Ports Connection Behavior Flow Examples.....	269
5.5.5	Connecting to Downstream USB4 Hubs .....	275
5.5.6	Fallback Functional Requirements for USB4 Hubs .....	275
5.6	USB4 Device Connection Requirements .....	276
5.6.1	Fallback Mapping of USB4 Peripheral Functions of USB Device Class Types .....	276
5.7	Parameter Values .....	277
5.7.1	Timing Parameters .....	277
6	Active Cables.....	278
6.1	General Specifications for All Active Cables.....	278
6.1.1	Discovering Active Cable Characteristics.....	278

6.1.2	Electrical Requirements .....	280
6.1.3	Mechanical Requirements .....	312
6.2	Additional Specifications for Copper and Hybrid-Optical Active Cables.....	313
6.2.1	Active Cable Block Diagram .....	314
6.2.2	<i>USB4</i> Asymmetric Mode Support .....	314
6.2.3	Active Cable <i>USB PD</i> Requirements.....	314
6.2.4	Active Cable Behaviors in Response to <i>USB PD</i> Events.....	314
6.2.5	Active Cable Power Requirements.....	315
6.3	Additional Specifications for Optically Isolated Active Cables .....	315
6.3.1	OIAC Block Diagrams .....	316
6.3.2	OIAC Limitations and General Requirements .....	318
6.3.3	OIAC Cable Power Requirements .....	319
6.3.4	OIAC <i>USB PD</i> Requirements.....	319
6.3.5	OIAC Connection Flow and State Diagrams .....	329
6.3.6	Additional Electrical Requirements for OIAC .....	348
6.3.7	Additional Mechanical Requirements for OIAC .....	351
A	Liquid Corrosion Mitigation Mode.....	352
A.1	Overview.....	352
A.2	Detail .....	352
A.3	Liquid Detection Methods.....	354
A.3.1	Liquid Measurement Method .....	354
A.3.2	Pulsed Measurement Method.....	354
A.3.3	Impedance Measurement Method.....	355
A.4	Liquid Detection Pins in the Connector .....	358
B	Debug Accessory Mode .....	361
B.1	Overview.....	361
B.2	Functional .....	361
B.2.1	Signal Summary .....	361
B.2.2	Port Interoperability.....	362
B.2.3	Debug Accessory Mode Entry.....	362
B.2.4	Connection State Diagrams.....	362
B.2.5	DTS Port Interoperability Behaviors.....	371
B.2.6	Orientation Detection.....	380
B.3	Security/Privacy Requirements.....	380
C	USB Type-C Digital Audio.....	381
C.1	Overview.....	381

C.2	USB Type-C Digital Audio Specifications.....	381
D	Thermal Design Considerations for Active Cables.....	382
D.1	Introduction .....	382
D.2	Model.....	382
D.2.1	Assumptions.....	382
D.2.2	Model Architecture.....	383
D.2.3	Heat Sources.....	383
D.2.4	Heat Flow.....	384
D.3	USB 3.2 Single-Lane Active Cable.....	385
D.3.1	USB 3.2 Single-Lane Active Cable Design Considerations .....	385
D.4	Dual-Lane Active Cables.....	388
D.4.1	USB 3.2 Dual-Lane Active Cable Design Considerations .....	388
D.4.2	USB 3.2 Dual-Lane Active Cable in a Multiple Port Configuration.....	390
D.5	USB 3.2 Host and Device Design Considerations .....	391
D.5.1	Heat Spreading or Heat Sinking from Host or Device.....	391
D.5.2	Motherboard Temperature Control .....	392
D.5.3	Wider Port Spacing for Multi-Port Applications .....	392
D.5.4	Power Policies .....	392
E	Alternate Modes.....	393
E.1	Alternate Mode Architecture .....	393
E.2	Alternate Mode Requirements.....	393
E.2.1	Alternate Mode Pin Reassignment.....	394
E.2.2	Alternate Mode Electrical Requirements.....	394
E.3	Parameter Values .....	397
E.4	Example Alternate Mode – USB DisplayPort™ Dock .....	398
E.4.1	USB DisplayPort™ Dock Example.....	398
E.4.2	Functional Overview.....	398
E.4.3	Operational Summary .....	399
E.5	Example Alternate Mode Entry Flow with Cable Warnings.....	400
E.5.1	Operational Summary .....	401
F	Thunderbolt™ 3 Compatibility Discovery and Entry.....	402
F.1	TBT3 Compatibility Mode Functional Requirements .....	402
F.1.1	TBT3-Compatible Power Requirements.....	402
F.1.2	TBT3-Compatible Host Requirements .....	402
F.1.3	TBT3-Compatible Device Upstream Requirements.....	402
F.1.4	TBT3-Compatible Device Downstream Requirements.....	402

F.1.5	<i>TBT3</i> -Compatible Self-Powered Device Without Predefined Upstream Port Rules .....	403
F.1.6	<i>TBT3</i> -Compatible Devices with a Captive Cable .....	403
F.2	<i>TBT3</i> Discovery and Entry Flow.....	403
F.2.1	<i>TBT3</i> Passive Cable Discover Identity Responses .....	404
F.2.2	<i>TBT3</i> Active Cable Discover Identity Responses.....	407
F.2.3	<i>TBT3</i> Device Discover Identity Responses .....	410
F.2.4	<i>TBT3</i> Discover SVID Responses.....	411
F.2.5	<i>TBT3</i> Device Discover Mode Responses .....	412
F.2.6	<i>TBT3</i> Cable Discover Mode Responses .....	413
F.2.7	<i>TBT3</i> Cable Enter Mode Command.....	414
F.2.8	<i>TBT3</i> Device Enter Mode Command .....	415
F.2.9	<i>TBT3</i> Cable Functional Difference Summary .....	417
G	Extracting Pulse Response from Sampled Data and Calculating Non-Linearity Noise.....	418
H	<i>USB PD</i> High-Voltage Design Considerations .....	420
H.1	Potential for Arcing Damage During Cable Withdrawal.....	420
H.2	Arcing During <i>USB Type-C</i> Cable Withdrawal .....	420
H.3	Mitigating Arcing Damage During Cable Withdrawal Due to Sink Discharge.....	422
H.3.1	Limiting Sink Discharge Rate.....	423
H.3.2	Load Removal .....	424
H.3.3	Limiting Source Current Capability .....	427
I	<i>USB PD</i> Encoding Guidelines for <i>USB Type-C</i> Product Types .....	428
I.1	<i>USB Type-C</i> Product Type Definitions and <i>USB PD</i> Encodings.....	428
I.2	<i>USB PD</i> Encoding Guidelines Tables.....	429
I.3	Detailed Examples.....	436
I.3.1	<i>USB 3.2</i> Host – no DC – Power Consumer : DRP (Source or Sink) / Not DRD (DFP).....	436
I.3.2	<i>USB 3.2</i> Peripheral – Power Provider : DRP (Source or Sink) / Not DRD (UFP).....	436
I.3.3	<i>USB4</i> Host – Power Consumer : DRP (Source or Sink) / Not DRD (DFP) .....	437
I.3.4	<i>USB4</i> Host – <i>USB4</i> DC – Partial or no <i>USB</i> Equivalent : DRP (Source or Sink) / DRD.....	437
I.3.5	<i>USB4</i> Peripheral : UFP (Sink) .....	438
I.3.6	<i>USB4</i> Dock (Upstream) – Power Provider : DRP (Source or Sink) / Not DRD (UFP) .....	439
I.3.7	<i>USB4</i> Hub (Downstream) – DFP (Source) .....	439
J	Design Assumptions for the <i>USB4</i> Gen4 LRD Cable Specification .....	441

### Figures

Figure 2-1	<i>USB Type-C</i> Receptacle Interface (Front View).....	38
Figure 2-2	<i>USB Full-Featured Type-C</i> Plug Interface (Front View).....	39
Figure 3-1	<i>USB Type-C</i> Receptacle Interface Dimensions.....	50
Figure 3-2	Reference Design <i>USB Type-C</i> Plug External EMC Spring Contact Zones.....	54

Figure 3-3 USB Full-Featured Type-C Plug Interface Dimensions.....	55
Figure 3-4 Right-Angle USB Type-C Plug Dimensional Requirements.....	58
Figure 3-5 Reference Footprint for a USB Type-C Vertical Mount Receptacle ( <i>Informative</i> ).....	59
Figure 3-6 Reference Footprint for a USB Type-C Dual-Row SMT Right-Angle Receptacle ( <i>Informative</i> ).....	60
Figure 3-7 Reference Footprint for a USB Type-C Hybrid Right-Angle Receptacle ( <i>Informative</i> ).....	61
Figure 3-8 Reference Footprint for a USB Type-C Mid-Mount Dual-Row SMT Receptacle ( <i>Informative</i> ).....	62
Figure 3-9 Reference Footprint for a USB Type-C Mid-Mount Hybrid Receptacle ( <i>Informative</i> ).....	63
Figure 3-10 Reference Footprint for a <i>USB 2.0</i> Type-C Through Hole Right Angle Receptacle ( <i>Informative</i> )....	64
Figure 3-11 Reference Footprint for a <i>USB 2.0</i> Type-C Single Row Right Angle Receptacle ( <i>Informative</i> ).....	65
Figure 3-12 <i>USB 2.0</i> Type-C Plug Interface Dimensions.....	67
Figure 3-13 USB Type-C Plug EMC Shielding Spring Tip Requirements.....	70
Figure 3-14 Reference Design of Receptacle Mid-Plate.....	71
Figure 3-15 Reference Design of Retention Latch.....	72
Figure 3-16 Illustration of the Latch Soldered to the Paddle Card Ground.....	72
Figure 3-17 Reference Design of the USB Full-Featured Type-C Plug Internal EMC Spring.....	73
Figure 3-18 Reference Design of the <i>USB 2.0</i> Type-C Plug Internal EMC Spring.....	74
Figure 3-19 Reference Design of Internal EMC Pad.....	75
Figure 3-20 Reference Design of a USB Type-C Receptacle with External EMC Springs.....	76
Figure 3-21 Reference Design of a USB Full-Featured Type-C Plug Paddle Card.....	77
Figure 3-22 Illustration of a USB Full-Featured Type-C Cable Cross Section, a Coaxial Wire Example with VCONN.....	80
Figure 3-23 Illustration of a USB Full-Featured Type-C Cable Cross Section, a Coaxial Wire Example without VCONN.....	80
Figure 3-24 USB Full-Featured Type-C Standard Cable Assembly.....	84
Figure 3-25 USB Type-C to <i>USB 3.1</i> Standard-A Cable Assembly.....	88
Figure 3-26 USB Type-C to <i>USB 2.0</i> Standard-A Cable Assembly.....	89
Figure 3-27 USB Type-C to <i>USB 3.1</i> Standard-B Cable Assembly.....	90
Figure 3-28 USB Type-C to <i>USB 2.0</i> Standard-B Cable Assembly.....	91
Figure 3-29 USB Type-C to <i>USB 2.0</i> Mini-B Cable Assembly.....	92
Figure 3-30 USB Type-C to <i>USB 3.1</i> Micro-B Cable Assembly.....	93
Figure 3-31 USB Type-C to <i>USB 2.0</i> Micro-B Cable Assembly.....	94
Figure 3-32 USB Type-C to <i>USB 3.1</i> Standard-A Receptacle Adapter Assembly.....	95
Figure 3-33 USB Type-C to <i>USB 2.0</i> Micro-B Receptacle Adapter Assembly.....	96
Figure 3-34 Illustration of Test Points for a Mated Cable Assembly.....	98
Figure 3-35 Recommended Differential Insertion Loss Requirement ( <i>USB 3.2</i> Gen2 and <i>USB4</i> Gen2).....	99
Figure 3-36 Recommended Differential Return Loss Requirement.....	99
Figure 3-37 Recommended Differential Crosstalk Requirement.....	100
Figure 3-38 Recommended Differential Near-End and Far-End Crosstalk Requirement between USB D+/D- Pair and TX/RX Pair.....	101
Figure 3-39 Recommended Differential Insertion Loss Requirement ( <i>USB4</i> Gen3/Gen4).....	101
Figure 3-40 Illustration of Insertion Loss Fit at Nyquist Frequency.....	102
Figure 3-41 Input Pulse Spectrum.....	103
Figure 3-42 IMR Limit as Function of ILfitatNq.....	104
Figure 3-43 IRL Limit as Function of ILfitatNq.....	106
Figure 3-44 Differential-to-Common Mode Conversion Requirement.....	106
Figure 3-45 IMR Limit as Function of ILfit at 10 GHz ( <i>USB4</i> Gen3/Gen4).....	110
Figure 3-46 Definition of Port, Victim, and Aggressor.....	111
Figure 3-47 IXT_DP and IXT_USB Limit as Function of ILfit at 10 GHz ( <i>USB4</i> Gen3/Gen4).....	111
Figure 3-48 IRL Limit as Function of ILfit at 10 GHz ( <i>USB4</i> Gen3/Gen4).....	112
Figure 3-49 Differential-to-Common Mode Conversion Requirement ( <i>USB4</i> Gen3/Gen4).....	112
Figure 3-50 Cable Assembly in System.....	113

Figure 3-51 Requirement for Differential Coupling between CC and D+/D- .....	116
Figure 3-52 Requirement for Single-Ended Coupling between CC and D- in <i>USB 2.0</i> Type-C Cables.....	116
Figure 3-53 Requirement for Single-Ended Coupling between CC and D- in USB Full-Featured Type-C Cables .....	117
Figure 3-54 Requirement for Differential Coupling between VBUS and D+/D- .....	117
Figure 3-55 Requirement for Single-Ended Coupling between SBU_A and SBU_B.....	118
Figure 3-56 Requirement for Single-Ended Coupling between SBU_A/SBU_B and CC.....	119
Figure 3-57 Requirement for Coupling between SBU_A and differential D+/D-, and SBU_B and differential D+/D- .....	119
Figure 3-58 Illustration of USB Type-C Mated Connector.....	120
Figure 3-59 Recommended Impedance Limits of a USB Type-C Mated Connector.....	121
Figure 3-60 Recommended Ground Void Dimensions for USB Type-C Receptacle .....	121
Figure 3-61 Recommended Differential Near-End and Far-End Crosstalk Limits between D+/D- Pair and TX/RX Pairs.....	123
Figure 3-62 Recommended Limits for Differential-to-Common-Mode Conversion.....	124
Figure 3-63 IMR Limit as Function of ILfitatNq for USB Type-C to Legacy Cable Assembly .....	129
Figure 3-64 IRL Limit as Function of ILfitatNq for USB Type-C to Legacy Cable Assembly.....	129
Figure 3-65 Cable Assembly Shielding Effectiveness Testing.....	133
Figure 3-66 Shielding Effectiveness Pass/Fail Criteria.....	134
Figure 3-67 LLCR Measurement Diagram.....	135
Figure 3-68 Temperature Measurement Point.....	136
Figure 3-69 Example Current Rating Test Fixture Trace Configuration .....	137
Figure 3-70 Example of 4-Axis Continuity Test Fixture .....	139
Figure 3-71 Torque Force Application Distance for Right-Angle Plugs.....	141
Figure 3-71 Example Wrenching Strength Test Fixture for Plugs without Overmold.....	142
Figure 3-72 Reference Wrenching Strength Continuity Test Fixture.....	142
Figure 3-73 Example of Wrenching Strength Test Mechanical Failure Point .....	143
Figure 3-74 Wrenching Strength Test with Cable in Fixture.....	143
Figure 3-75 USB Type-C Cable Receptacle Flange Example.....	145
Figure 3-76 EMC Guidelines for Side Latch and Mid-Plate.....	146
Figure 3-77 EMC Finger Connections to Plug Shell.....	147
Figure 3-78 EMC Pad Connections to Receptacle Shell .....	147
Figure 3-79 Examples of Connector Apertures.....	148
Figure 3-80 Recommended Minimum Spacing between Connectors.....	148
Figure 3-81 Recommended Minimum Plug Overmold Clearance .....	149
Figure 3-82 Cable Plug Overmold and an Angled Surface.....	149
Figure 4-1 Cable IR Drop.....	153
Figure 4-2 Cable IR Drop for powered cables.....	153
Figure 4-3 Logical Model for Single-Lane Data Bus Routing across USB Type-C-based Ports.....	161
Figure 4-4 Logical Model for USB Type-C-based Ports for a Single-Lane Direct Connect Device.....	161
Figure 4-5 Pull-Up/Pull-Down CC Model.....	163
Figure 4-6 Current Source/Pull-Down CC Model.....	163
Figure 4-7 Source Functional Model for CC1 and CC2 .....	166
Figure 4-8 Source Functional Model Supporting <i>USB PD PR_Swap</i> .....	167
Figure 4-9 Sink Functional Model for CC1 and CC2 .....	167
Figure 4-10 Sink Functional Model Supporting <i>USB PD PR_Swap</i> and <i>VCONN_Swap</i> .....	168
Figure 4-11 DRP Functional Model for CC1 and CC2.....	169
Figure 4-12 Connection State Diagram: Source.....	174
Figure 4-13 Connection State Diagram: Sink .....	175
Figure 4-14 Connection State Diagram: Sink with Accessory Support .....	176
Figure 4-15 Connection State Diagram: DRP .....	177

Figure 4-16 Connection State Diagram: DRP with Accessory and Try.SRC Support .....	178
Figure 4-17 Connection State Diagram: DRP with Accessory and Try.SNK Support.....	179
Figure 4-18 Connection State Diagram: Charge-Through VPD .....	180
Figure 4-19 Sink Power Sub-States .....	203
Figure 4-20 Passive Cable eMarker State Diagram.....	205
Figure 4-21 Active Cable eMarker State Diagram.....	205
Figure 4-22 Cable Ra Management State Diagram .....	206
Figure 4-23 Source to Sink Functional Model.....	209
Figure 4-24 Source to DRP Functional Model.....	210
Figure 4-25 DRP to Sink Functional Model.....	211
Figure 4-26 DRP to DRP Functional Model – CASE 1 .....	212
Figure 4-27 DRP to DRP Functional Model – CASES 2 & 3.....	213
Figure 4-28 Source to Source Functional Model .....	215
Figure 4-29 Sink to Sink Functional Model.....	215
Figure 4-30 DRP to VPD Model .....	216
Figure 4-31 Example DRP to Charge-Through VPD Model .....	217
Figure 4-32 Source to Legacy Device Port Functional Model .....	224
Figure 4-33 Legacy Host Port to Sink Functional Model.....	224
Figure 4-34 DRP to Legacy Device Port Functional Model .....	225
Figure 4-35 Legacy Host Port to DRP Functional Model.....	226
Figure 4-36 Sink Monitoring for Current in Pull-Up/Pull-Down CC Model.....	229
Figure 4-37 Sink Monitoring for Current in Current Source/Pull-Down CC Model.....	230
Figure 4-38 <i>USB PD</i> over CC Pins .....	231
Figure 4-39 <i>USB PD</i> BMC Signaling over CC .....	231
Figure 4-40 USB Type-C Cable's Output as a Function of Load for Non-PD-based USB Type-C Charging.....	235
Figure 4-41 0 – 3 A <i>USB PD</i> -based Charger USB Type-C Cable's Output as a Function of Load .....	236
Figure 4-42 3 – 5 A <i>USB PD</i> -based Charger USB Type-C Cable's Output as a Function of Load .....	236
Figure 4-43 Electronically Marked Cable with VCONN connected through the cable .....	242
Figure 4-44 Electronically Marked Cable with SOP' at both ends .....	242
Figure 4-45 Example Charge-Through VCONN-Power USB Device Use Case .....	245
Figure 4-46 Example Source Implementation.....	247
Figure 4-47 Exiting from <i>Attached.SRC</i> with slow discharging VBULK .....	248
Figure 4-48 Exiting from <i>Attached.SRC</i> with fast discharging VBULK .....	248
Figure 4-49 DRP Timing.....	249
Figure 4-50 Pull-Up/Pull-Down Voltage Detection Model.....	251
Figure 4-51 Current Source Voltage Detection Model .....	251
Figure 5-1 <i>USB4</i> Discovery and Entry Flow Model.....	262
Figure 5-2 <i>USB4</i> Hub with <i>USB4</i> Host and Device Connection Flow Alignment .....	270
Figure 5-3 <i>USB4</i> Hub with <i>USB 3.2</i> Host and <i>USB4</i> Device Connection Flow Alignment .....	271
Figure 5-4 <i>USB4</i> Hub with <i>USB4</i> Host and <i>USB 3.2</i> Device Connection Flow Alignment .....	272
Figure 5-5 <i>USB4</i> Hub with <i>USB 3.2</i> Host and Device Connection Flow Alignment .....	273
Figure 5-6 <i>USB4</i> Hub with <i>USB4</i> Host and DP Alt Mode Device Connection Flow Alignment .....	274
Figure 5-7 <i>USB4</i> Hub with <i>USB 3.2</i> Host and DP Alt Mode Device Connection Flow Alignment .....	275
Figure 6-1 Active Cable Topologies .....	281
Figure 6-2 SuperSpeed USB Electrical Test Points .....	284
Figure 6-3 SuperSpeed USB Compliance Test Setup .....	284
Figure 6-4 Compliance Points Definition.....	287
Figure 6-5 RX Differential Return-Loss Mask.....	288
Figure 6-6 Re-timer-based Active Cable Compliance Test Setup .....	289
Figure 6-7 Example of Transmitter Frequency Variation During Clock Switching.....	291
Figure 6-8 Active Cable Functional Test Setup.....	292

Figure 6-9 Linear Re-driver-based Active Cable Compliance Setup .....	293
Figure 6-10 Gain Parameters Specified for the Linear Re-driver Active Cable .....	296
Figure 6-11 OUTPUT_NOISE Limit Versus $IL_{fitatNq}$ .....	297
Figure 6-12 Gain Parameters for <i>USB4</i> Gen4 LRD Active Cables .....	300
Figure 6-13 <i>USB4</i> LRD Active Cable Snooping of TxFFE Negotiation .....	305
Figure 6-14 <i>USB4</i> State Machine per Channel ( <i>Informative</i> ) .....	306
Figure 6-15 <i>USB4</i> Gen4 CL1/CL2 Exit Flow with LRD Active Cable .....	308
Figure 6-16 <i>USB4</i> Symmetric to Asymmetric Transition .....	309
Figure 6-17 <i>USB4</i> Asymmetric to Symmetric Transition .....	311
Figure 6-18 OIAC <i>USB PD</i> Message Forwarding .....	324
Figure 6-19 OIAC Successful Data Role Swap .....	327
Figure 6-20 OIAC Rejected Data Role Swap .....	327
Figure 6-21 OIAC Wait Data Role Swap .....	328
Figure 6-22 OIAC Initiator Reject Data Role Swap .....	328
Figure 6-23 OIAC Initiator Wait Data Role Swap .....	329
Figure 6-24 OIAC Discovery – Phase 1 .....	331
Figure 6-25 OIAC Reboot – Phase 2 .....	332
Figure 6-26 OIAC Plug-A Configured as DFP – Phase 3 .....	333
Figure 6-27 OIAC Plug-A Configured as UFP – Phase 3 .....	334
Figure 6-28 OIAC Plug-A No Connection Possible Billboard – Phase 3 .....	335
Figure 6-29 OIAC Plug-A State Diagram Part 1 (Phase 1 and 2) .....	336
Figure 6-30 OIAC Plug-A State Diagram Part 2 (Phase 3) .....	337
Figure 6-31 OIAC Plug-B State Diagram .....	343
Figure 6-32 Illustration of Usages for OIAC that Require an Adapter or Hub .....	350
Figure A-1 Electrolytic Liquid Corrosion Example .....	352
Figure A-2 Corrosion Mitigation in Pull-Up/Pull-Down CC Model .....	353
Figure A-3 Corrosion Mitigation in Current Source/Pull-Down CC Model .....	353
Figure A-4 Corrosion Mitigation in Current Source/Pull-Down CC Model with Alternate Mitigation .....	353
Figure A-5 Liquid Detection by Leakage Measurement .....	354
Figure A-6 Liquid Detection by Pulsed Measurement .....	355
Figure A-7 Example Measurement of a Dry Port .....	356
Figure A-8 Example Measurement of a Port with Reverse Osmosis Water .....	356
Figure A-9 Example Measurement of a Port with Tap Water .....	357
Figure A-10 Example Measurement of a Port with Artificial Sweat .....	357
Figure A-11 Example Measurement of a Port with Ocean Water .....	358
Figure A-12 Example Liquid Detect Pin(s)/Pad(s) Location Area .....	359
Figure A-13 Example Liquid Detect Pad Along All Connector Pins .....	359
Figure A-14 Example Liquid Detect Pins Adjacent to $V_{BUS}/SBU/CC$ .....	360
Figure A-15 Example Liquid Detect Connector Surface Mount View .....	360
Figure B-1 USB Type-C Debug Accessory Layered Behavior .....	361
Figure B-2 DTS Plug Interface .....	361
Figure B-3 Connection State Diagram: DTS Source .....	363
Figure B-4 Connection State Diagram: DTS Sink .....	364
Figure B-5 Connection State Diagram: DTS DRP .....	365
Figure B-6 TS Sink Power Sub-States .....	369
Figure D-1 Active Cable Model (Single Port, Top Mount Receptacle) .....	383
Figure D-2 Model Architecture .....	383
Figure D-3 Heat Sources and Heat Flow Paths .....	384
Figure D-4 Vertically Stacked Horizontal Connectors 3x1 Configuration (VERT) .....	385
Figure D-5 Horizontally Stacked Vertical Connectors 1x3 Configuration (HZ90) .....	386
Figure D-6 Horizontally Stacked Horizontal Connectors 1x3 Configuration (HORZ) .....	386

Figure D-7 <i>USB 3.2</i> Single-Lane 3A Active Cable in a 3-Port Configuration.....	387
Figure D-8 <i>USB 3.2</i> Single-Lane 5A Active Cable in a 3-Port Configuration.....	387
Figure D-9 Impact of Overmold Power $P_0$ and Thermal Boundary Temperature $T_{MB}$ at 3 A VBUS in a Single Port Configuration .....	389
Figure D-10 Impact of Overmold Power $P_0$ and Thermal Boundary Temperature $T_{MB}$ at 5 A VBUS in a Single Port Configuration .....	389
Figure D-11 <i>USB 3.2</i> Active Cable Dongle Design (One End Shown) .....	390
Figure D-12 <i>USB 3.2</i> Dual-Lane 3A Active Cable in a 3-Port Configuration.....	390
Figure D-13 <i>USB 3.2</i> Dual-Lane 5A Active Cable in a 3-Port Configuration.....	391
Figure D-14 Example: Additional Heat Spreader on Receptacle in Host or Device .....	392
Figure D-15 Example: Heat Sinking on Chassis of Host or Device.....	392
Figure E-1 Pins Available for Reconfiguration over the Full-Featured Cable .....	394
Figure E-2 Pins Available for Reconfiguration for Direct Connect Applications .....	394
Figure E-3 Alternate Mode Implementation using a USB Type-C to USB Type-C Cable .....	396
Figure E-4 Alternate Mode Implementation using a USB Type-C to Alternate Mode Cable or Device.....	396
Figure E-5 USB DisplayPort Dock Example .....	398
Figure E-6 <i>USB4</i> DFP Mode Entry Flow Example.....	400
Figure F-1 <i>TBT3</i> Discovery Flow .....	404
Figure H-1 Arcing Damage to USB Type-C VBUS Contacts .....	420
Figure H-2 Arcing Due to Discharge.....	421
Figure H-3 Arcing Prevention During Sink Discharge by Limiting Slew Rate .....	423
Figure H-4 Arcing Prevention During Sink Discharge by Load Removal.....	425

## Tables

Table 2-1 Summary of power supply options.....	43
Table 3-1 USB Type-C Standard Cable Assemblies.....	46
Table 3-2 USB Type-C Legacy Cable Assemblies .....	47
Table 3-3 USB Type-C Legacy Adapter Assemblies .....	47
Table 3-4 USB Type-C Receptacle Interface Pin Assignments.....	78
Table 3-5 USB Type-C Receptacle Interface Pin Assignments for <i>USB 2.0</i> -only Support .....	79
Table 3-6 USB Type-C Standard Cable Wire Assignments .....	81
Table 3-7 USB Type-C Cable Wire Assignments for Legacy Cables/Adapters.....	82
Table 3-8 Reference Wire Gauges for standard USB Type-C Cable Assemblies.....	83
Table 3-9 Reference Wire Gauges for standard USB Type-C to Legacy Cable Assemblies .....	83
Table 3-10 USB Full-Featured Type-C Standard Cable Assembly Wiring.....	85
Table 3-11 <i>USB 2.0</i> Type-C Standard Cable Assembly Wiring.....	86
Table 3-12 USB Type-C to <i>USB 3.1</i> Standard-A Cable Assembly Wiring .....	88
Table 3-13 USB Type-C to <i>USB 2.0</i> Standard-A Cable Assembly Wiring .....	89
Table 3-14 USB Type-C to <i>USB 3.1</i> Standard-B Cable Assembly Wiring .....	90
Table 3-15 USB Type-C to <i>USB 2.0</i> Standard-B Cable Assembly Wiring .....	91
Table 3-16 USB Type-C to <i>USB 2.0</i> Mini-B Cable Assembly Wiring.....	92
Table 3-17 USB Type-C to <i>USB 3.1</i> Micro-B Cable Assembly Wiring .....	93
Table 3-18 USB Type-C to <i>USB 2.0</i> Micro-B Cable Assembly Wiring .....	94
Table 3-19 USB Type-C to <i>USB 3.1</i> Standard-A Adapter Assembly Wiring .....	95
Table 3-20 USB Type-C to <i>USB 2.0</i> Micro-B Receptacle Adapter Assembly Wiring .....	96
Table 3-21 Differential Insertion Loss Examples for USB TX/RX with Twisted Pair Construction .....	97
Table 3-22 Differential Insertion Loss Examples for USB TX/RX with Coaxial Construction .....	98
Table 3-23 Key Parameters in COM Configuration File .....	114
Table 3-24 Electrical Requirements for CC and SBU Wires.....	115

Table 3-25 Coupling Matrix for Low Speed Signals.....	115
Table 3-26 Maximum Mutual Inductance (M) between VBUS and Low Speed Signal Lines .....	118
Table 3-27 USB D+/D- Signal Integrity Requirements for USB Type-C to USB Type-C Passive Cable Assemblies.....	120
Table 3-28 USB Type-C Mated Connector Recommended Signal Integrity Characteristics ( <i>Informative</i> ) .....	122
Table 3-29 USB Type-C Receptacle Connector Signal Integrity Characteristics for <i>USB4</i> Gen3 ( <i>Normative</i> ) ..	125
Table 3-30 USB D+/D- Signal Integrity Requirements for USB Type-C to Legacy USB Cable Assemblies ( <i>Normative</i> ).....	126
Table 3-31 Design Targets for USB Type-C to <i>USB 3.1</i> Gen2 Legacy Cable Assemblies ( <i>Informative</i> ).....	127
Table 3-32 USB Type-C to <i>USB 3.1</i> Gen2 Legacy Cable Assembly Signal Integrity Requirements ( <i>Normative</i> ) .....	128
Table 3-33 USB D+/D- Signal Integrity Requirements for USB Type-C to Legacy USB Adapter Assemblies ( <i>Normative</i> ).....	130
Table 3-34 Design Targets for USB Type-C to <i>USB 3.1</i> Standard-A Adapter Assemblies ( <i>Informative</i> ) .....	131
Table 3-35 USB Type-C to <i>USB 3.1</i> Standard-A Receptacle Adapter Assembly Signal Integrity Requirements ( <i>Normative</i> ).....	132
Table 3-36 Current Rating Test PCB.....	137
Table 3-37 Maximum DC Resistance Requirement ( <i>Normative</i> ).....	137
Table 3-38 Force and Moment Requirements .....	140
Table 3-39 Environmental Test Conditions .....	143
Table 3-40 Reference Materials .....	144
Table 4-1 USB Type-C List of Signals .....	151
Table 4-2 VBUS Source Characteristics .....	154
Table 4-3 VBUS Sink Characteristics .....	155
Table 4-4 USB Type-C Source Port's VCONN Requirements Summary.....	156
Table 4-5 VCONN Source Characteristics.....	156
Table 4-6 Cable VCONN Sink Characteristics.....	157
Table 4-7 VCONN-Powered Accessory (VPA) Sink Characteristics.....	158
Table 4-8 VCONN-Powered Device (VPD) Sink Characteristics .....	159
Table 4-9 USB Type-C Port Interoperability.....	162
Table 4-10 Source Perspective .....	164
Table 4-11 Source (Host) and Sink (Device) Behaviors by State .....	164
Table 4-12 Recommended Implementation of Try.SRC and Try.SNK for Dual-Role Ports with Preferred Roles .....	171
Table 4-13 <i>USB PD</i> Swapping Port Behavior Summary.....	171
Table 4-14 Use of Power and Data Role Swaps for Dual-Role Ports with Preferred Roles.....	172
Table 4-15 Power Role Behavioral Model Summary .....	172
Table 4-16 Source Port CC Pin State.....	181
Table 4-17 Sink Port CC Pin State.....	181
Table 4-18 Mandatory and Optional States .....	207
Table 4-19 Precedence of Power Source Usage .....	227
Table 4-20 USB Type-C Current Advertisement and PDP Equivalent.....	229
Table 4-21 Sink Maximum Current Limit When Attached to CTVPD .....	232
Table 4-22 Example Charge-Through VPD Sink Maximum Currents based on VBUS Impedance and GND Impedance.....	233
Table 4-23 Examples of 4-port Shared Capacity Group and Power Sharing Policies.....	239
Table 4-24 SOP' and SOP'' Timing.....	242
Table 4-25 Charge-Through VPD CC Impedance (RccCON) Requirements .....	244
Table 4-26 CTVPD Charge-Through Port VBUS Bypass Requirements .....	244
Table 4-27 Source CC Termination (Rp) Requirements.....	245
Table 4-28 Sink CC Termination (Rd) Requirements .....	246

Table 4-29	Powered Cable Termination Requirements .....	246
Table 4-30	CC Termination Requirements for Disabled state, ErrorRecovery state, and Unpowered Source.....	246
Table 4-31	SBU Termination Requirements.....	246
Table 4-32	VBUS and VCONN Timing Parameters.....	247
Table 4-33	DRP Timing Parameters.....	249
Table 4-34	CC Timing Parameters .....	250
Table 4-35	Sink CC Pin Voltages for Connect Detection for Rd and Clamp Voltage $\pm 20\%$ .....	254
Table 4-36	Sink CC Pin Voltages for Connect and Current Advertisement Detection for Rd $\pm 10\%$ .....	254
Table 4-37	Source CC Pin Voltages for All Current Advertisements using a Pull-Up current.....	255
Table 4-38	Source CC Pin Voltages for Pull-Up Resistance to 5 V.....	256
Table 4-39	Source CC Pin Voltages for Pull-Up Resistance to 3.3 V .....	257
Table 4-40	CC Pin Clamping Voltage.....	257
Table 5-1	Certified Cables Where <i>USB4</i> -compatible Operation is Expected.....	264
Table 5-2	Fallback Mapping <i>USB4</i> Functions to USB Device Class Types.....	276
Table 5-3	USB Billboard Device Class Availability Following <i>USB4</i> Device Entry Failure.....	277
Table 6-1	<i>USB4</i> Cable Identity Summary.....	279
Table 6-2	Active Cable Features.....	280
Table 6-3	Active Cable SBU Requirements.....	281
Table 6-4	Active Cable Power-on Requirements .....	282
Table 6-5	Maximum <i>USB 3.2</i> U0 Delay .....	283
Table 6-6	<i>USB 3.2</i> U-State Requirements .....	283
Table 6-7	Active Cable <i>USB 3.2</i> Stressed Source Swing, TP1.....	285
Table 6-8	Active Cable <i>USB 3.2</i> Stressed Source Jitter, TP1.....	285
Table 6-9	Active Cable <i>USB 3.2</i> Input Swing at TP2 ( <i>Informative</i> ).....	286
Table 6-10	Active Cable <i>USB 3.2</i> Output Swing at TP3 ( <i>Informative</i> ).....	286
Table 6-11	Compliance Points Definition.....	287
Table 6-12	<i>USB4</i> CL-State Requirements for Active Cables .....	289
Table 6-13	Re-timer-based <i>USB4</i> Active Cable Output Specifications Applied for All Speeds (at TP3') .....	290
Table 6-14	Stressed Receiver Conditions for <i>USB4</i> Gen2 and Gen3 Cable Compliance Testing (at TP2).....	292
Table 6-15	Linear Re-driver-based Active Cable Output Parameters .....	294
Table 6-16	Input Signal at TP2 for Compliance Testing.....	295
Table 6-17	<i>USB4</i> Gen4 LRD-based Active Cable ILfitMask Limits .....	299
Table 6-18	<i>USB4</i> Gen4 LRD-based Active Cable Wiring Diagram for Compliance .....	301
Table 6-19	<i>USB4</i> Gen4 Active Cable SBx Transaction Snooping.....	302
Table 6-20	<i>USB4</i> LRD Active Cable Logical Timing Parameters .....	303
Table 6-21	<i>USB4</i> LRD Tuning Register Snooping.....	312
Table 6-22	Cable Temperature Requirements.....	313
Table 6-23	OIAC <i>USB PD</i> Message Handling.....	320
Table 6-24	Recommended OIAC Sink_Capabilities PDO (SOP) on Initial Connection .....	321
Table 6-25	Recommended OIAC Sink_Capabilities PDO (SOP) on Active Connection.....	321
Table 6-26	Recommended OIAC Active Sink RDO (SOP) .....	322
Table 6-27	OIAC <i>USB PD</i> Message Timing.....	325
Table 6-28	Port and Plug Capabilities.....	330
Table 6-29	<i>USB 3.2</i> U-State Requirements.....	350
Table 6-30	<i>USB4</i> CL-State Requirements for OIAC .....	351
Table A-1	Example Measurement Test Conditions .....	355
Table B-1	DTS to TS Port Interoperability.....	362
Table B-2	Rp/Rp Charging Current Values for a DTS Source.....	369
Table B-3	Mandatory and Optional States.....	371
Table D-1	Heat Sources and Heat Dissipation Example (1.5 W cable and 5 A) .....	384

Table D-2 <i>USB 3.2</i> Active Cable Design Single Port Case Study at 35 °C Ambient and 60 °C Thermal Boundary (Single Lane).....	385
Table D-3 <i>USB 3.2</i> Active Cable Design Single Port Case Study at 35 °C Ambient and 60 °C Thermal Boundary (Dual Lane).....	388
Table E-1 USB Safe State Electrical Requirements .....	397
Table E-2 USB Billboard Device Class Availability Following Alternate Mode Entry Failure .....	397
Table E-3 Alternate Mode Signal Noise Ingression Requirements.....	397
Table F-1 <i>TBT3</i> Passive Cable Discovery Identity VDO Responses.....	405
Table F-2 <i>TBT3</i> Passive Cable VDO for <i>USB PD</i> Revision 2.0, Version 1.3.....	406
Table F-3 <i>TBT3</i> Passive Cable VDO for <i>USB PD</i> Revision 3.0, Version 1.2.....	406
Table F-4 <i>TBT3</i> Active Cable Discovery Identity VDO Responses .....	407
Table F-5 <i>TBT3</i> Active Cable VDO for <i>USB PD</i> Revision 2.0, Version 1.3 .....	408
Table F-6 <i>TBT3</i> Active Cable VDO 1 for <i>USB PD</i> Revision 3.0, Version 1.2 .....	408
Table F-7 <i>TBT3</i> Active Cable VDO 2 for <i>USB PD</i> Revision 3.0, Version 1.2 .....	409
Table F-8 <i>TBT3</i> Device Discovery Identity VDO Responses.....	410
Table F-9 <i>TBT3</i> Discover SVID VDO Responses.....	411
Table F-10 <i>TBT3</i> Device Discover Mode VDO Responses .....	412
Table F-11 <i>TBT3</i> Cable Discover Mode VDO Responses.....	413
Table F-12 <i>TBT3</i> Cable Enter Mode Command.....	414
Table F-13 <i>TBT3</i> Device Enter Mode Command .....	415
Table F-14 <i>TBT3</i> Cable Functional Difference Summary .....	417
Table G-1 Linear Fit Pulse Extraction Parameters.....	419
Table I-1 USB Type-C Product Example Clarifying Notes.....	430
Table I-2 <i>USB PD</i> Encoding Guidelines for Example Products.....	433

**Specification Editor**

SpecWerkz

Brad Saunders

**Specification Work Group Contributors**

The following is a list of contributor companies and the individuals that were members of the work group roster at the time of this release (October 2024). Note: For historical reasons, the following list also includes individuals that were members of the work group and associated with their company affiliations at the time of each release going back to Release 1.0.

Acroname Inc.	Grant Fritz	Connor Goss	Matt Krugman
Advanced-Connectek, Inc. (ACON)	Glen Chandler	Conrad Choy	Alan Tsai
	Victory Chen	Vicky Chuang	Wayne Wang
	Bobo Chen	Same Dai	Stephen Yang
	Dennis Cheung	Jessica Feng	Sunney Yang
	Jeff Chien	Aven Kao	Kevin Yao
	Lee (Dick Lee) Ching	Danny Liao	
Advanced Micro Devices	Steve Capezza	Jason Hawken	Joseph Scanlon
	Michael Comai	Juan Martinez	Peter Teng
	Walter Fry	Gerald Merits	Sujan Thomas
	Will Harris	Tim Perley	
Allion Labs, Inc.	Howard Chang	Yan Ken	Brian Shih
	Alex Chuang	Lexus Lee	Chester Tsai
	Maroco Fan	Stan Lin	Chou Tsungbo
	Jesse Jiang	Denver Mishima	Liam Wu
	Terry Kao	Minoru Ohara	
Amphenol Corporation	Louis Chan	Terry Ke	Shawn Wei
	Zhineng Fan	Martin Li	Alan Yang
	Jesse Jaramillo	Lino Liu	
Agilent Technologies, Inc.	James Choate		
Analogix Semiconductor, Inc.	Mehran Badii	Haijian Sui	Yueke Tang
	Greg Stewart		
Apple Inc. (USB Promoter company)	Colin Abraham	Brian Follis	Nathan Ng
	Mahmoud Amini	Zheng Gao	James Orr
	Sree Anantharaman	Derek Iwamoto	Keith Porthouse
	Brian Baek	Scott Jackson	Breton Saunders
	Paul Baker	Girault Jones	Reese Schreiber
	Michael Bonham	Keong Kam	Jay Sha
	Jonathan Brown	Kevin Keeler	Sascha Tietz
	Carlos Calderon	Min Kim	Jennifer Tsai
	Jason Chung	Woopoung Kim	Colin Whitby-Strevens
	David Conroy	Alan Kobayashi	Jeff Wilcox
	Bill Cornelius	Alexei Kosut	Eric Wiles
	Christophe Daniel	Christine Krause	Dan Wilson
	Raju Desai	Chris Ligtenberg	Dennis Yarak
	William Ferry	Matthew Mora	
	Aptiv Consumer Connectivity	Andrew Burchett	Moe Elghrawi
ASMedia Technology Inc.	Kuo Lung Li		
Bizlink Technology, Inc.	Alex Chou	CY Tsai	Giovanni Wang
	Morphy Hsieh	Kevin Tsai	

Cadence Design Systems, Inc.	Marcin Behrendt Huzaifa Dalal Pawel Eichler Sanjai Gandhi Sathish Kumar Ganesan	Dariusz Kaczmarczyk Tomasz Klimek Sanjeet Kumar Jie Min Asila Nahas Uyen Nguyen	Neelabh Singh Michal Staworko Fred Stivers Mark Summers Claire Ying
Canova Tech	Piergiorgio Beruto Andrea Maniero	Michael Marioli Antonio Orzelli	Paola Pilla Nicola Scantamburlo
China Telecommunications Technology Labs	Ming Wei		
Cirrus Logic Inc.	Sean Davis	Darren Holding	Brad Lambert
Corning Optical Communication LLC	Wojciech Giziewicz	Ian McKay	Jamie Silva
Cosemi Technologies Inc.	Samir Desai	Devang Parekh	
Credo Semiconductor, Inc.	Jim Bartenslager Yifei Dai Kevin Gao	Yasuo Hidaka Justin Lee Phil Sun	Ping Xiong
Cypress Semiconductor	Chia Hua Chang Mark Fu Naman Jain Savan Javia	Rushil Kadakia Benjamin Kropf Venkat Mandagulathur Anup Nayak	Jagadeesan Raj Sanjay Sancheti Subu Sankaran Anita Thimma Govarthanarajan
Dell	Mohammed Hijazi Rose Hou David Meyers Sean O'Neal	Ken Nicholas Marcin Nowak Ernesto Ramirez	Siddhartha Reddy Thomas Voor Merle Wood
Dialog Semiconductor (UK) Ltd.	Yimin Chen		
Diodes Incorporated	Kay Annamalai Justin Lee Paul Li	Bob Lo Jaya Shukla Qun Song	Jin-sheng Wang Ada Yip
DisplayLink (UK) Ltd.	Pete Burgers		
DJI Technology Co., Ltd.	Steve Huang		
eEver Technology, Inc.	Chien-Cheng Kuo		
Electronics Testing Center, Taiwan	Sophia Liu		
Elka International Ltd.	Roy Ting		
Ellisys	Abel Astley Rick Bogart	Wenhui Luo Mario Pasquali	Chuck Trefts Tim Wei
Etron Technology, Inc.	Chien-Cheng Kuo		
EverPro Technologies Company, Ltd.	Eva Chen	Hui Jiang	Silane Zhou
Feature Integration Technologies Inc.	Jacky Chan Chen Kris Yulin Lan	KungAn Lin Yuchi Tsao	Paul Yang Amanda Ying

Foxconn / Hon Hai	Patrick Casher	Fred Fons	Christine Tran
	Asroc Chen	Chris Goralka	Pei Tsao
	Brandon Chen	Bob Hall	AJ Yang
	Joe Chen	Chien-Ping Kao	Yuan Zhang
	Allen Cheng	Ji Li	Jessica Zheng
	Jason Chou	Ann Liu	Jie Zheng
	Edmond Choy	Terry Little	Andy Yao
	Shruti Deore	Steve Sedio	
Foxlink/Cheng Uei Precision Industry Co., Ltd.	Robert Chen	Armando Lee	Steve Tsai
	Sunny Chou	Dennis Lee	Wen Yang
	Carrie Chuang	Justin Lin	Wiley Yang
	Wen-Chuan Hsu	Robert Lu	Patrick Yeh
	Alex Hsue	Tse Wu Ting	Junjie Yu
Fresco Logic Inc.	Brian Collins	Bob McVay	Christopher Meyers
Google	Mehdi Abrishamchian	Mark Hayter	Vincent Palatin
	Naga Viswanadha	Eric Herrmann	Dylan Reid
	Udaya Kiran Ammu	Nithya Jagannathan	Adam Rodriguez
	Lucasz Bartosik	Nathan Kolluru	David Schneider
	Alec Berg	Lawrence Lam	Stephan Schooley
	Joshua Boilard	Adam Langley	Ketan Shringarpure
	Alec Berg	Benson Leung	Toshak Singhal
	Todd Broch	Abraham Levkoy	Bartosz Szpila
	Charlie Costakis	Ingrid Lin	Jameson Thies
	Nehemiah Dureus	Prashant Malani	Radu Vele
	Chao Fei	George-Daniel Matei	Ken Wu
	Jim Guerin	Richard Palatin	Songping Wu
	Jeffrey Hayashida		Diana Zigterman
Granite River Labs	Yung Han Ang	Mike Engbretson	Kristof Mommen
	Velmurugan Ayyakkannu	Mark Jiang	Krishna Murthy
	Rajesh B	Vishal Kakade	Amy Peng
	Pascal Berten	Jesson Li	Johnson Tan
	Hariprasad Bhat	Caspar Lin	Annie Tao
	Sandy Chang	Olivia Lu	Vasudev Uttharahalli
	Allen Chen	Bala M	Chin Hun Yaep
	Swee Guan Chua	Prasannakumar Marikunte Nagaraju	Mike Yang
	Alan Chuang	Winson Mok	Yun Yang
GuangDong OPPO Mobile Telecommunications Corp, Ltd.	Jerry Qin		
Honor Device Co., Ltd.	Wang Feng		
Hirose Electric Co., Ltd.	Jeremy Buan	Hyejun Lee	Gourgen Oganessyan
	Kohei Hida	Zhili Liang	Youngbon Park
	Kazunori Ichikawa	Sang-Muk Lim	Eungsoo Shin
	Sukkyu Jang	William MacKillop	Sid Tono
	William Kysiak		
Hosiden Corporation	Takahisa Otsuji	Fumitake Tamaki	

HP Inc. (USB Promoter company)	Lee Atkinson	Robin Castell	Jim Mann
	Srinath Balaraman	Steve Chen	Linden McClure
	Rami Bathaniah	Michael Krause	Mike Pescetto
	Roger Benson	Rahul Lakdawala	Asjad Shamim
	Alan Berkema		
Huawei Technology Co., Ltd.	Jianhong He	Gang Liang	Ruinan Sun
	Zhengbing Li	Lauri Soderbacka	Liansheng Zheng
Hynetek Semiconductor Co., Ltd.	Yingyang Ou	James Xie	
I-PEX (Dai-ichi Seiko)	Alan Kinningham	Jack Ozeki	Ro Richard
Indie Semiconductor	Ian Board	Jim Wilshire	
Infineon Technologies	Godwin Gerald Arulappan	Behzad Jamasbi	Geona Mary Pullankannappally Devasia
	Pradeep Baipai	Benjamin Kropf	Shopitham Ram
	Dominic Gutierrez	Venkat Mandagulathur	Gayathri Vasudevan
	Anton Gutsul	Aniket Shashikant Mathad	Tue Fatt David Wee
	Naman Jain		
Insight Test Labs	Caspar Lin		
Intel Corporation (USB Promoter company)	Dave Ackelson	Luke Johnson	Rajaram Regupathy
	Nirmala Bailur	Ziv Kabiry	Oren Salomon
	Mike Bell	Vijaykumar Kadgi	Brad Saunders
	Dmitriy Berchanskiy	Jerzy Kolinski	Tomer Savariego
	Brad Berlin	Venkataramana Kotakonda	Ehud Shoor
	Pierre Bossart	Rolf Kuhn	Amit Srivastava
	Huimin Chen	Rolf Kuhn	Einat Suriyan
	Kuan-Yu Chen	Henrik Leegaard	Eliahu Suued
	Hengju Cheng	Edmond Lau	Ron Swartz
	Oded David	Xiang Li	Chuen Ming Tan
	Sourabh Das	Yun Ling	David Thompson
	Jhuda Dayan	Guobin Liu	Pranav Tipnis
	Hem Doshi	Steve McGowan	Karthi Vadivelu
	Paul Durley	Sankaran Menon	Venkataramani Gopalakrishnan
	Saranya Gopal Venkataramani Gopalakrishnan	Udaya Natarajan	Tsion Vidal
	Yaniv Hayat	Aruni Nelson	Stephanie Wallick
	Howard Heck	Chee Lim Nge	Rafal Wielicki
	Hao-Han Hsu	Asutosh Pathak	Devon Worrell
	Seppo Ingalsuo	Sagar Pawar	Gal Yedidia
	Abdul (Rahman) Ismail	Duane Quiet	Li Yuan
James Jaussi	Amardeep Rai	Reza M. Zamani	
	Kannappan Rajaraman	Vitaly Zhivov	
	Sridharan Ranganathan		

Japan Aviation Electronics Industry Ltd. (JAE)	Kenji Hagiwara Hiroaki Ikeda Masaki Kimura Toshio Masumoto Kenta Minejima Toshiyuki Moritake Joe Motojima Ron Muir Norihiko Nakamura	Tadashi Okubo Kazuhiro Saito Kimiaki Saito Yuichi Saito Mark Saubert Toshio Shimoyama Tatsuya Shioda Atsuo Tago Masaaki Takaku	Jussi Takaneva Junichi Takeuchi Tomohiko Tamada Kentaro Toda Kouhei Ueda Takakazu Usami Masahide Watanabe Youhei Yokoyama
JPC/Main Super Inc.	Sam Tseng	Ray Yang	
Kandou Bus SA	Amanda Dong Majid Foodeei	Hitaish Sharma David Stauffer	Paul Wilson
Keysight Technologies Inc.	Soon Tatt Beh Fang Huey Lim	Jit Lim Pedro Merlo	Abhijeet Shinde Xiao Zhang
Kinetic Technologies, Inc.	Ramesh Dandapani Akihiro Moto	Jay Slivkoff Sireesha Vemulapalli	Kei Yasuno
Leadtrend	Yao-Wei Hsieh		
LeCroy Corporation	Mike Engbretson Daniel H. Jacobs	Tyler Joe Chetan Kopalle	Giuseppe Leccia
Lenovo	Rob Bowser Tomoki Harada	Jianye Li Wei Liu	Howard Locker Munefumi Nakata
LG Electronics Inc.	Won-Jong Choi Do Kyun Kim	Jeeyoung Kim Minji Kim	Seung Hyun Yoo
Lintes Technology Co., Ltd.	Tammy Huang Charles Kaun RD Lintes	Guobin Liu Max Lo CT Pien	JinYi Tu Jason Yang
Logitech Inc.	Niclas Granqvist		
Lotes Co., Ltd.	Ariel Delos Reyes Ernest Han Mark Ho Regina Liu-Hwang	Charles Kaun Chi-Chang Lin James Lin Max Lo	John Lynch Scott Shuey JinYi Tu Jason Yang
LSI Corporation	Dave Thompson		
Luxshare-ICT	Josue Castillo Daniel Chen Kenny Chen Lisen Chen Sally Chiu Blue Ho CY Hsu Alan Kinningham	Peter Jhou Antony Lin Gorden Lin John Lin Stone Lin Alan Liu Sean O'Neal	Scott Shuey James Stevens Carr Wang Yangli Wang Eric Wen Wayne Yeh Pat Young
Maxim Integrated Products	Forrest Christo Ken Helfrich	Sang Kim Jeff Lo	Michael Miskho Jacob Scott
MCCI Corporation	Terry Moore		
MediaTek Inc.	Henry Chen Yu-Yi Chu Yishu Hsieh Jason Hsu	Liang-Yu Hsu Jing-Hao Huang Shih Jyun-Yang Akan Lin	Alex YC Lin Tung-Sheng Lin Colin Tsai Chasel Wang

MegaChips Corporation	Alan Kobayashi	Satoru Kumashiro	
Mercedes-Benz Research & Development, North America, Inc.	Hans Wickler		
Microchip (SMSC)	Josh Averyt Mark Bohm Shannon Cash Thomas Farkas Fernando Gonzalez	Matthew Kalibat Donald Perkins Richard Petrie Mohammed Rahman Andrew Rogers	John Sisto Anthony Tarascio Kiet Tran Christopher Twigg Prasanna Vengateshan
Microsoft Corporation (USB Promoter company)	Randy Aull Jim Belesiu Michelle Bergeron Fred Bhesania Anthony Chen Philip Froese Vivek Gupta David Hargrove Robbie Harris Teemu Helenius Robert Hollyer Lily Huang Dan Iatco	Kai Inha Jayson Kastens Andrea Keating Shoaib Khan Patrick Law Eric Lee Ivan McCracken Arvind Murching Gene Obie Toby Nixon Arjun Padmanabhan Praveen Kumar Palacharla	Rahul Ramadas Srivatsan Ravindran Kiran Shastry Nathan Sherman Ugan Sivagnanenthirarajah Bala Sivakumar Timo Toivola Vahid Vassey David Voth Andrew Yang Panu Ylihaavisto
Molex LLC	Adib Al Abaji	Alan MacDougall	
Monolithic Power Systems	Junyong Gong Di Han Yuncong Jiang	Istvan Nagy Chris Sporck Ao Sun	Greg Virnig Vincent Wu
MQP Electronics Ltd.	Sten Carlsen	Pat Crowe	
Multilane Inc.	Fadi Daou	Rita Khawaja	Elias Khoury
NEC Corporation	Kenji Oguma		
Newnex Technology Corp.	Sam Liu	Nimrod Peled	
Nokia Corporation	Daniel Gratiot Pekka Leinonen	Samuli Makinen Pekka Talmola	Timo Toivola Panu Ylihaavisto
Nuvoton Technology Corp.	Nimrod Peled		
NVIDIA	Jamie Aitken	Jason Tsai	
NXP Semiconductors	Mahmoud EL Sabbagh Dennis Ha Jia Guo Ken Jaramillo	Nate Johnson Vijendra Kuroodi Roger Lo	Guru Prasad Wouter Sijm Krishnan TN
Oculus VR LLC	Amish Babu	Marty Evans	Joaquin Fierro
ON Semiconductor	Edward Berrios Rod Comer Alex Cornwall Eduardo De Reza	Alan Finkel Oscar Freitas Christian Klein Amir Lahooti	Eric Maier Rick Pierce Michael Smith
Parade Technologies, Inc.	Tom Burton Jian Chen Brian Collins	Reginald Conley Robert McVay Craig Wiley	Paul Xu Alan Yuen Jingfan Zhang
Phison Electronics Corp.	Wilson Wen		

Power Integrations	Shruti Anand	Aditya Kulkarni	Amruta Patra
	Daryll Bonavente	Akshay Nayaknur	Kaushik Raam
	Rahul Joshi		
Qualcomm, Inc.	Lior Amarilio	James Goel	Vatsal Patel
	Vara Prasad Arikatla	Amit Gupta	Jack Pham
	Aris Balatsos	Philip Hardy	Vamsi Samavedam
	Nicholas Cadieux	Will Kun	Matthew Sienko
	David Chang	Jonathan Luty	Dmitrii Vasilchenko
	Tomer Ben Chen	Adi Menachem	Joshua Warner
	Richard Burrows	Lalan Mishra	Chris Wiesner
	Amit Gil	George Paparrizos	
Realtek Semiconductor Corp.	Marco Chiu	Ray Lee	Chuting Su
	Tsung-Peng Chuang	Jay Lin	Kyle Tsai
	Charlie Hsu	Ryan Lin	Jason Wang
	Fan-Hau Hsu	Terry Lin	Changhung Wu
	Ty Kingsmore		
Renesas Electronics Corp. (USB Promoter company)	Kai Bao	Philip Leung	Yosuke Sasaki
	Yen-Mo Chen	Mengfei Liu	Toshifumi Yamaoka
	Yimin Chen	Kiichi Muto	Fengshuan Zhou
	Nobuo Furuya	Ziba Nami	Yuhuan Zhou
	Tony Lai	Hajime Nozaki	
Resillion (Belgium NV)	Bart Grispen		
Richtek Technology Corp.	Ben Chiang	Max Huang	Ken Shih
	Tzuhsien Chuang	Leo Kang	Alex Yang
	Bryan Huang	Roger Lo	
Rohde & Schwarz GmbH & Co. KG	Curtis Donahue	Kai Uwe Schmidt	Randy White
	Patrick McKenzie	Martin Stumpf	
Rohm Co., Ltd.	Mark Aaldering	Yusuke Kondo	Yoshinori Ohwaki
	Kris Bahar	Arun Kumar	Takashi Sato
	Ruben Balbuena	Chris Lin	Hiroshi Yoshimura
	Nobutaka Itakura	Kazuomi Nagai	
Samsung Electronics Co., Ltd.	Jaedeok Cha	Sangwoo Kang	Jun Bum Lee
	KangSeok Cho	Wonseok Kang	Kyunghwan Lee
	Junhwa Choi	Koyoungwon Kim	Kyungwoo Lee
	Woojin Choi	Sangju Kim	Jinyoung Oh
	Yeongbok Choi	Soondo Kim	Chahoon Park
	Cheolyoon Chung	Woonki Kim	Chulwoo Park
	Ilhyung Chung	Jagoun Koo	Youngjin Park
	JaeRyong Han	Termi Kwon	Jung Waneui
	Jaehyeok Jang	Cheolho Lee	Sunggeun Yoon
	Sung Geun Joo	Edward Lee	
SB C&S Corp.	Toshinari Nakamura	Eiji Sakai	Kenji Watanabe
	Morito Ogikubo		
Scosche Industries	Josh Aguilera	Perry DeGuzman	Kevin Trejo
Seagate	Alvin Cox	Tony Priborsky	Dan Smith
	Emmanuel Lemay	Tom Skaar	Curtis Stevens
Shenzhen Deren Electronic Co., Ltd.	Smark (Zhudong) Huo	Yang Lirong	Lucy Zhang
	Wen Fa Lei	Valerie Yang	

Silicon Line GmbH	Ian Jackson	Boleslaw Wojtowicz	Zhiying Zhang
SiliConch Systems Private Limited	Jaswanth Ammineni Pavitra Balasubramanian Kaustubh Kumar Aniket Mathad	Shubham Paliwal Jinisha Patel Vinay Patel Rakesh Polasa	Vishnu Pusuluri Ranjith S Abhishek Sardeshpande Satish Anand Verkila
Simula Technology Inc.	John Chang Voss Cheng Thomas Li	Jung Lin Jyunming Lin Doris Liu	Richard Liu CK Wang Alice Yu
Softnautics LLP	Bhavesh Desai Hetal Jariwala	Dipakkumar Modi Ishita Shah	Ujjwal Talati
Sony Corporation	Shinichi Hirata	Shigenori Tagami	
Spectra7 Microsystems Corp.	Andrew Kim	James McGrath	John Mitchell
SpecWerkz	Robert Dunstan Amanda Hosler	Diane Lenox Steve McGowan	Brad Saunders
STMicroelectronics (USB Promoter company)	Jerome Bach Nathalie Ballot Filippo Bonaccorso Guenael Cadier Dominique Chaillot Christophe Cochard Nicolas Florenchie	Cedric Force Gregory Gosciniak Chekib Hammami Joel Huloux Christophe Lorin Yohann Martiniault Patrizia Milazzo	Federico Musarra Pascal Legrand Richard O'Connor Massimo Panzica Nicolas Perrin Mathieu Rouviere
Sumitomo Electric Ind., Ltd.	Takeshi Inoue Yasuhiro Maeda	Wataru Sakurai Sainer Siagian	Masaki Suzuki Mitsuaki Tamura
Synaptics Inc.	Daniel Bogard Dan Ellis	Jeff Lukanc	Prashant Shamarao
Synopsys, Inc.	Prishkrit Abrol Subramaniam Aravindhnan	Morten Christiansen Jaspreet Gambhir Nivin George	Satya Patnala John Stonick
Taiwan Testing and Certification Center	Dennis Chang	Sophia Liu	
Tektronix, Inc.	Sourabh Das Mark Guenther	Nitin Jhanwar Abhijeet Shinde	Randy White
Texas Instruments (USB Promoter company)	Jawaid Ahmad Kasthuri Annamalai Mike Campbell Prajith Cheerakkoda Greg Collins Gary Cooper Biju Erayamkott Panayamthatta Anant Gole GP Gopalakrishnan Craig Greenberg Richard Hubbard Katherine Huckabay Nate Johnson	Michael Koltun IV Kevin Kosta Yoon Lee Grant Ley Win Maung Shafiuddin Mohammed Lauren Moore Jacob Ontiveros Brian Parten Martin Patoka Jason Peck John Perry	Louis Peryea Brian Quach Sai Karthik Rajaraman Wes Ray Dafydd Roche Anwar Sadat Cory Stewart Neeta Thawani Sue Vining Bill Waters Deric Waters Gregory Watkins Roy Wojciechowski
The Silanna Group Pty. Ltd.	Tod Wolf		
Thine Electronica, Inc.	Yuseke Fujita	Shuhei Yamamoto	

Total Phase	Chris Yokum		
Trinity Co., Ltd.	Tetsushi Hoshikawa	Kinya Kishita	
Tyco Electronics Corp. (TE Connectivity Ltd.)	Max Chao Robert E. Cid Calvin Feng Kengo Ijro Eiji Ikematsu Joan Leu Clark Li	Mike Lockyer Jeff Mason Takeshi Nakashima Luis A. Navarro Masako Saito Yoshiaki Sakuma Gavin Shih	Hiroshi Shirai Hidenori Taguchi Nathan Tracy Bernard Vetten Ryan Yu Noah Zhang Sjoerd Zwartkruis
UL LLC	Leo Chung Michael Hu Terry Kao	Dylan Su Henry Tsou Paul Vanderlaan	Eric Wall Lance Yang Chien-Wei Yeh
Unigraf OY	Steven Chen Sergey Grushin	Alexander Gushchin	Topi Lampiranta
Varjo Technologies	Kai Inha		
Ventev Mobile	Brad Cox	Colin Vose	
VIA Technologies Inc.	Rex Hsu Einsent Huang	Terrance Shih Jay Tseng	Fong-Jim Wang
Vivo Mobile Communications Co. Ltd.	Benny Dong Fangding Luo	Junchen Wei	Ziji Zhou
Weltrend Semiconductor	Hung Chiang Jeng Cheng Liu	Wayne Lo Ho Wen Tsai	Eric Wu
Western Digital	Dave Landsman Larry McMillan	Rotem Sela	Prithviraj Sengupta
Xiaomi Communications Co., Ltd.	Canfeng Chen Zhe Wang	Xiaoxing Yang Juejia Zhou	Qi Zhu
Zhuhai iSmartWare Technology Co., Ltd.	Yuanchao Liang	Liu Qiong	Long Zhang

#### Pre-Release Draft Industry Reviewing Companies That Provided Feedback

Aces	JST Mfg. Co., Ltd.	Pericom
Fairchild Semiconductor	Korea Electric Terminal	Semtech Corporation
Fujitsu Ltd.	Marvell Semiconductor	Silicon Image
Industrial Technology Research Institute (ITRI)	Motorola Mobility LLC	SMK Corporation
Joinsoon Electronics Mfg. Co. Ltd.	PalCONN/PalNova (Palpilot International Corp.)	Toshiba Corporation

## Revision History

Release	Date	Description
1.0	August 11, 2014	Initial Release
1.1	April 3, 2015	Reprint release including incorporation of all approved ECNs as of the revision date plus editorial clean-up.
1.2	March 25, 2016	Reprint release including incorporation of all approved ECNs as of the revision date plus editorial clean-up.
1.3	July 14, 2017	Reprint release including incorporation of all approved ECNs as of the revision date plus editorial clean-up.
1.4	March 29, 2019	Reprint release including incorporation of all approved ECNs as of the revision date plus editorial clean-up.
2.0	August 2019	New release primarily for enabling <b>USB4</b> over USB Type-C connectors and cables. Also includes incorporation of all approved ECNs as of the revision date plus editorial clean-up.
2.1	May 2021	New release primarily for enabling Extended Power Range (EPR) and defining EPR cables aligning with <b>USB Power Delivery</b> Specification R3.1 V1.0. Also includes incorporation of all approved ECNs as the revision date plus editorial clean-up.
2.2	October 2022	New release primarily for enabling <b>USB4</b> Version 2.0 (80 Gbps) over USB Type-C connectors and cables. Also includes incorporation of all approved ECNs as of the revision date plus editorial clean-up.
2.3	October 2023	New release primarily for <i>deprecating</i> the <b>Audio Adapter Accessory Mode</b> and <i>replacing it with</i> the <b>Liquid Corrosion Mitigation Mode</b> , and for updating the <b>Multi-port Charger Shared Capacity</b> definition and behaviors. Also includes incorporation of all other approved ECNs as of the revision date. Note: this release was created using a newly developed document template that includes some style adjustments and editorial clean-up.
2.4	October 2024	Reprint release including incorporation of all approved ECNs as of the revision date plus editorial clean-up.

## 1 Introduction

With the continued success of the USB interface, there exists a need to adapt USB technology to serve newer computing platforms and devices as they trend toward smaller, thinner, and lighter form-factors. Many of these newer platforms and devices are reaching a point where existing USB receptacles and plugs are inhibiting innovation, especially given the relatively large size and internal volume constraints of the Standard-A and Standard-B versions of USB connectors. Additionally, as platform usage models have evolved, usability and robustness requirements have advanced, and the existing set of USB connectors were not originally designed for some of these newer requirements. This specification establishes a new USB connector ecosystem that addresses the evolving needs of platforms and devices while retaining all the functional benefits of USB that form the basis for this most popular computing device interconnect.

### 1.1 Purpose

This specification defines the USB Type-C® receptacles, plug and cables.

The USB Type-C Cable and Connector Specification is guided by the following principles:

- Enable new and exciting host and device form-factors where size, industrial design and style are important parameters
- Work seamlessly with existing USB host and device silicon solutions
- Enhance ease of use for connecting USB devices with a focus on minimizing user confusion for plug and cable orientation

The USB Type-C Cable and Connector Specification defines a receptacle, plug, cable, and detection mechanisms that are compatible with existing USB interface electrical and functional specifications. This specification covers the following aspects that are needed to produce and use this new USB cable/connector solution in newer platforms and devices, and that interoperate with existing platforms and devices:

- USB Type-C receptacles, including electro-mechanical definition and performance requirements
- USB Type-C plugs and cable assemblies, including electro-mechanical definition and performance requirements
- USB Type-C to legacy cable assemblies and adapters
- USB Type-C-based device detection and interface configuration, including support for legacy connections
- **USB Power Delivery** optimized for the USB Type-C connector

The USB Type-C Cable and Connector Specification defines a standardized mechanism that supports *Alternate Modes*, such as repurposing the connector for docking-specific applications.

### 1.2 Scope

This specification is intended as a supplement to the existing **USB 2.0**, **USB 3.2**, **USB4®** and **USB Power Delivery** specifications. It addresses only the elements required to implement and support the USB Type-C receptacles, plugs and cables.

**Normative** information is provided to allow interoperability of components designed to this specification. **Informative** information, when provided, may illustrate possible design implementations.

### 1.3 Related Documents

#### **USB 2.0 Universal Serial Bus Revision 2.0 Specification**

This includes the entire document release package.

**USB 3.2 Universal Serial Bus Revision 3.2 Specification**

This includes the entire document release package.  
USB 3.1 Legacy Cable and Connector Specification, Revision 1.0

**USB4 USB4 Specification, Version 2.0, June 2023**

(including posted errata and ECNs)

**TBT3 Chapter 13 of USB4 Specification, Version 2.0, June 2023**

**USB PD USB Power Delivery Specification, Revision 2.0, Version 1.3, January 12, 2017**

**USB Power Delivery Specification, Revision 3.2, Version 1.1, October 2024**  
(including posted errata and ECNs)

**USB BB USB Billboard Device Class Specification, Revision 1.2.2, January 29, 2021**

**USB BC Battery Charging Specification, Revision 1.2, March 15, 2012**

(including posted errata and ECNs)

**DP AM DisplayPort™ Alt Mode on USB Type-C Standard, Version 2.1a, August 2024**

All USB-specific documents are available for download at <http://www.usb.org/documents>.  
The **DisplayPort Alt Mode** specification is available from VESA (<http://www.vesa.org>).