

TECHNICAL REPORT

IEC TR 61282-7

First edition
2003-01

Fibre optic communication system design guides – Part 7: Statistical calculation of chromatic dispersion

*Guide de conception des systèmes de communications
à fibres optiques –*

*Partie 7:
Calcul statistique de la dispersion chromatique*

© IEC 2003 — Copyright - all rights reserved

No part of this publication may be reproduced or utilized in any form or by any means, electronic or mechanical, including photocopying and microfilm, without permission in writing from the publisher.

International Electrotechnical Commission, 3, rue de Varembé, PO Box 131, CH-1211 Geneva 20, Switzerland
Telephone: +41 22 919 02 11 Telefax: +41 22 919 03 00 E-mail: inmail@iec.ch Web: www.iec.ch



Commission Electrotechnique Internationale
International Electrotechnical Commission
Международная Электротехническая Комиссия

PRICE CODE

M

For price, see current catalogue

CONTENTS

FOREWORD	3
1 Scope	4
2 Normative references.....	4
3 Characterisation of chromatic dispersion coefficient versus wavelength	5
4 Characterisation of chromatic dispersion coefficient statistics versus wavelength	6
5 Calculation of the concatenation statistics for a single population of optical fibres.....	9
6 Generalisation of concatenation statistics for multiple populations – including components.	10
Figure 1 – Distribution of dispersion parameters.....	6
Figure 2 – Histogram of values at 1560 nm	7
Figure 3 – Histogram of values at 1530 nm	7
Figure 4 – Average dispersion coefficient versus wavelength	8
Figure 5 – Standard deviation of dispersion coefficient versus wavelength	8
Figure 6 – Fibre average	11
Figure 7 – Fibre standard deviation	11
Figure 8 – Dispersion compensator average.....	12
Figure 9 – Dispersion compensator standard deviation.....	12
Figure 10 – Combined three sigma limits.....	13
Table 1 – Computed values at two selected wavelengths	10

INTERNATIONAL ELECTROTECHNICAL COMMISSION

FIBRE OPTIC COMMUNICATION SYSTEM DESIGN GUIDES –

Part 7: Statistical calculation of chromatic dispersion

FOREWORD

- 1) The IEC (International Electrotechnical Commission) is a worldwide organization for standardization comprising all national electrotechnical committees (IEC National Committees). The object of the IEC is to promote international co-operation on all questions concerning standardization in the electrical and electronic fields. To this end and in addition to other activities, the IEC publishes International Standards. Their preparation is entrusted to technical committees; any IEC National Committee interested in the subject dealt with may participate in this preparatory work. International, governmental and non-governmental organizations liaising with the IEC also participate in this preparation. The IEC collaborates closely with the International Organization for Standardization (ISO) in accordance with conditions determined by agreement between the two organizations.
- 2) The formal decisions or agreements of the IEC on technical matters express, as nearly as possible, an international consensus of opinion on the relevant subjects since each technical committee has representation from all interested National Committees.
- 3) The documents produced have the form of recommendations for international use and are published in the form of standards, technical specifications, technical reports or guides and they are accepted by the National Committees in that sense.
- 4) In order to promote international unification, IEC National Committees undertake to apply IEC International Standards transparently to the maximum extent possible in their national and regional standards. Any divergence between the IEC Standard and the corresponding national or regional standard shall be clearly indicated in the latter.
- 5) The IEC provides no marking procedure to indicate its approval and cannot be rendered responsible for any equipment declared to be in conformity with one of its standards.
- 6) Attention is drawn to the possibility that some of the elements of this technical report may be the subject of patent rights. The IEC shall not be held responsible for identifying any or all such patent rights.

The main task of IEC technical committees is to prepare International Standards. However, a technical committee may propose the publication of a technical report when it has collected data of a different kind from that which is normally published as an International Standard, for example "state of the art".

IEC 61282-7, which is a technical report, has been prepared by subcommittee 86C: Fibre optic systems and active devices, of IEC technical committee 86: Fibre optics.

The text of this technical report is based on the following documents:

Enquiry draft	Report on voting
86C/429/DTR	86C/468/RVC

Full information on the voting for the approval of this technical report can be found in the report on voting indicated in the above table.

This publication has been drafted in accordance with the ISO/IEC Directives, Part 2.

The committee has decided that the contents of this publication will remain unchanged until 2009-12. At this date, the publication will be

- reconfirmed;
- withdrawn;
- replaced by a revised edition, or
- amended.

FIBRE OPTIC COMMUNICATION SYSTEM DESIGN GUIDES –

Part 7: Statistical calculation of chromatic dispersion

1 Scope

This part of IEC 61282 is a guideline providing methods of representing the process statistics of the chromatic dispersion of optical fibres and related components that may be combined in a link.

Chromatic dispersion (ps/nm) is the derivative, with respect to wavelength, of the group delay (ps) induced by the spectral content of light propagating through an optical element or fibre. Chromatic dispersion is normally a function of wavelength and can be either positive (group delay increasing with wavelength) or negative (group delay decreasing with wavelength).

The presence of chromatic dispersion can induce distortions in signals leading to bit errors depending on

- source spectral width;
- source chirp;
- bit period;
- distance.

In addition, chromatic dispersion is interactive with the effects of non-linear optical effects and second order polarisation mode dispersion (PMD). The above system impairments are beyond the scope of this technical report.

When different components or fibres are combined, the chromatic dispersion of the combination is the total of the chromatic dispersion values of the individuals, on a wavelength-by-wavelength basis. A section with high chromatic dispersion will be balanced by sections with lower values. The variation in the total dispersion of links will therefore be dependent on the distributions of the products that are used in the link. This document provides methods to calculate the distribution statistics of concatenated links based on information on the distributions of different fibre or component populations.

NOTE In the clauses that follow, examples are given for particular fibre and component types. These examples are not necessarily broadly representative.

2 Normative references

The following referenced documents are indispensable for the application of this document. For dated references, only the edition cited applies. For undated references, the latest edition of the referenced document (including any amendments) applies.

IEC 60793-1-42: *Optical fibres – Part 1-42: Measurement methods and test procedures – Chromatic dispersion*

IEC 60793-2-50: *Optical fibres – Part 2-50: Product specifications – Sectional specification for class B single-mode fibres*

ITU-T Recommendation G.652: *Characteristics of a single-mode optical fibre cable*

ITU-T Recommendation G.655: *Characteristics of a non-zero dispersion shifted single-mode optical fibre cable*

ITU-T Recommendation G.671: *Transmission characteristics of optical components and subsystems*

ITU-T Recommendation G.691: *Optical interfaces for single-channel STM-64, STM-256 and other SDH systems with optical amplifiers*