

INTERNATIONAL STANDARD



**Metallic communication cable test methods –
Part 4-14: Electromagnetic compatibility (EMC) – Coupling attenuation of cable
assemblies (field conditions) absorbing clamp method**

INTERNATIONAL
ELECTROTECHNICAL
COMMISSION

PRICE CODE

P

ICS 33.040.20

ISBN 978-2-83220-086-5

Warning! Make sure that you obtained this publication from an authorized distributor.

CONTENTS

FOREWORD	3
1 Scope	5
2 Normative references	5
3 Terms and definitions	5
4 Test method	6
4.1 Equipment	6
4.1.1 General	6
4.1.2 Balun requirements	6
4.1.3 Extension cable requirements	7
4.2 Test sample	8
4.2.1 General	8
4.2.2 Tested length	8
4.2.3 Preparation of test sample	8
4.3 Calibration procedure	9
4.4 Test set-up	9
4.4.1 General	9
4.4.2 Test set-up verification	10
4.5 Measuring procedure	11
4.5.1 General	11
4.5.2 Example of link measurement	11
5 Expression of test results	12
6 Test report	12
6.1 General	12
6.2 Evaluation of test results	13
Bibliography	16
 Figure 1 – Measurement of surface wave at one end of a link or channel	6
Figure 2 – Termination of link or channel or applied extension cable	9
Figure 3 – Example of a three-connector link configuration as defined in ISO/IEC 11801	11
Figure 4 – Wall outlet end measurement	12
Figure 5 – Typical measurement of an unscreened channel – Coupling attenuation, A is 43 dB	14
Figure 6 – Typical measurement of a screened balanced channel – Coupling attenuation, A is 57 dB	14
Figure 7 – Double wall outlet, right port (without connected screen) – Coupling attenuation, A is 44,8 dB	15
Figure 8 – Double wall outlet, left port (with connected screen) – Coupling attenuation, A is 61,5 dB	15
 Table 1 – Balun performance characteristics	7

INTERNATIONAL ELECTROTECHNICAL COMMISSION

METALLIC COMMUNICATION CABLE TEST METHODS –**Part 4-14: Electromagnetic compatibility (EMC) –
Coupling attenuation of cable assemblies
(field conditions) absorbing clamp method****FOREWORD**

- 1) The International Electrotechnical Commission (IEC) is a worldwide organization for standardization comprising all national electrotechnical committees (IEC National Committees). The object of IEC is to promote international co-operation on all questions concerning standardization in the electrical and electronic fields. To this end and in addition to other activities, IEC publishes International Standards, Technical Specifications, Technical Reports, Publicly Available Specifications (PAS) and Guides (hereafter referred to as "IEC Publication(s)"). Their preparation is entrusted to technical committees; any IEC National Committee interested in the subject dealt with may participate in this preparatory work. International, governmental and non-governmental organizations liaising with the IEC also participate in this preparation. IEC collaborates closely with the International Organization for Standardization (ISO) in accordance with conditions determined by agreement between the two organizations.
- 2) The formal decisions or agreements of IEC on technical matters express, as nearly as possible, an international consensus of opinion on the relevant subjects since each technical committee has representation from all interested IEC National Committees.
- 3) IEC Publications have the form of recommendations for international use and are accepted by IEC National Committees in that sense. While all reasonable efforts are made to ensure that the technical content of IEC Publications is accurate, IEC cannot be held responsible for the way in which they are used or for any misinterpretation by any end user.
- 4) In order to promote international uniformity, IEC National Committees undertake to apply IEC Publications transparently to the maximum extent possible in their national and regional publications. Any divergence between any IEC Publication and the corresponding national or regional publication shall be clearly indicated in the latter.
- 5) IEC itself does not provide any attestation of conformity. Independent certification bodies provide conformity assessment services and, in some areas, access to IEC marks of conformity. IEC is not responsible for any services carried out by independent certification bodies.
- 6) All users should ensure that they have the latest edition of this publication.
- 7) No liability shall attach to IEC or its directors, employees, servants or agents including individual experts and members of its technical committees and IEC National Committees for any personal injury, property damage or other damage of any nature whatsoever, whether direct or indirect, or for costs (including legal fees) and expenses arising out of the publication, use of, or reliance upon, this IEC Publication or any other IEC Publications.
- 8) Attention is drawn to the Normative references cited in this publication. Use of the referenced publications is indispensable for the correct application of this publication.
- 9) Attention is drawn to the possibility that some of the elements of this IEC Publication may be the subject of patent rights. IEC shall not be held responsible for identifying any or all such patent rights.

International Standard IEC 62153-4-14 has been prepared by IEC technical committee 46: Cables, wires, waveguides, R.F. connectors, R.F. and microwave passive components and accessories.

The text of this standard is based on the following documents:

FDIS	Report on voting
46/400/FDIS	46/415/RVD

Full information on the voting for the approval of this standard can be found in the report on voting indicated in the above table.

This publication has been drafted in accordance with the ISO/IEC Directives, Part 2.

A list of all the parts in the IEC 62153 series, published under the general title: *Metallic communication cable test methods*, can be found on the IEC website.

The committee has decided that the contents of this publication will remain unchanged until the stability date indicated on the IEC web site under "<http://webstore.iec.ch>" in the data related to the specific publication. At this date, the publication will be

- reconfirmed,
- withdrawn,
- replaced by a revised edition, or
- amended.

A bilingual version of this standard may be issued at a later date.

IMPORTANT – The 'colour inside' logo on the cover page of this publication indicates that it contains colours which are considered to be useful for the correct understanding of its contents. Users should therefore print this document using a colour printer.

METALLIC COMMUNICATION CABLE TEST METHODS –

Part 4-14: Electromagnetic compatibility (EMC) – Coupling attenuation of cable assemblies (field conditions) absorbing clamp method

1 Scope

This part of IEC 62153 gives the in-field test method that is used to determine the coupling attenuation for installed links and channels used in analogue and digital communication systems.

This method is used to determine the attenuation of disturbing power to signal power in a cabling system, and vice versa. This determines the influence from cabling on the EMC performance of a system.

NOTE 1 The coupling attenuation of installed links and channels is dependent upon the performance of the cabling components (balance and screening if applicable), workmanship (especially termination of screens) and earthing and grounding. This procedure determines the overall effect of these parameters.

NOTE 2 This method cannot be used for verification of compliance with emission and immunity EMC standards for the complete system, including active components.

2 Normative references

The following documents, in whole or in part, are normatively referenced in this document and are indispensable for its application. For dated references, only the edition cited applies. For undated references, the latest edition of the referenced document (including any amendments) applies.

IEC 60050 (all parts), *International Electrotechnical Vocabulary* (available at <http://www.electropedia.org/>)

IEC 61196-1, *Coaxial communication cables – Part 1: Generic specification – General, definitions and requirements*

IEC 62153-4-5:2006, *Metallic communication cable test methods – Part 4-5: Electromagnetic Compatibility (EMC) – Coupling or screening attenuation – Absorbing clamp method*