

INTERNATIONAL STANDARD

ISO/IEC 10090

First edition
1992-10-15

Information technology — 90 mm optical disk cartridges, rewritable and read only, for data interchange

*Technologies de l'information — Cartouches pour disques optiques de
diamètre 90 mm, réinscriptibles et à lecture unique, pour échange de
données*



Reference number
ISO/IEC 10090:1992(E)

Contents

	Page
Section 1 - General	1
1 Scope	1
2 Conformance	1
3 Normative reference	1
4 Definitions	1
4.1 case	1
4.2 cyclic redundancy check (CRC)	2
4.3 embossed mark	2
4.4 entrance surface	2
4.5 error correction code (ECC)	2
4.6 field	2
4.7 format	2
4.8 groove	2
4.9 interleaving	2
4.10 Kerr rotation	2
4.11 land and groove	2
4.12 mark	2
4.13 optical disk	2
4.14 optical disk cartridge (ODC)	2
4.15 polarization	2
4.16 recording layer	2
4.17 Reed-Solomon code	2
4.18 rewritable optical disk	2
4.19 sector	2
4.20 substrate	2
4.21 track	2
4.22 zone	2
5 Conventions and notations	3
5.1 Representation of numbers	3
5.2 Names	3
6 List of acronyms	3
7 General description of the optical disk cartridge	3

© ISO/IEC 1992

All rights reserved. No part of this publication may be reproduced or utilized in any form or by any means, electronic or mechanical, including photocopying and microfilm, without permission in writing from the publisher.

ISO/IEC Copyright Office • Case Postale 56 • CH-1211 Genève 20 • Switzerland
Printed in Switzerland

8	General requirements	4
8.1	Environments	4
8.1.1	Testing environment	4
8.1.2	Operating environment	4
8.1.3	Storage environment	5
8.1.4	Transportation	5
8.2	Temperature shock	5
8.3	Safety requirements	5
8.4	Flammability	5
9	Reference Drive	5
9.1	Optical system	5
9.2	Optical beam	7
9.3	Read channels	7
9.4	Tracking	7
9.5	Rotation of the disk	7
	Section 2 - Mechanical and physical characteristics	8
10	Dimensional and physical characteristics of the case	8
10.1	General description of the case	8
10.2	Reference planes of the case	8
10.3	Dimensions of the case	8
10.3.1	Overall dimensions	8
10.3.2	Location hole	9
10.3.3	Alignment hole	9
10.3.4	Reference surfaces	9
10.3.5	Detents	10
10.3.6	Functional Areas	10
10.3.7	Spindle and head windows	11
10.3.8	Shutter	12
10.3.9	Path for shutter opener and shutter sensor notch	13
10.3.10	Mis-insert protections	13
10.3.11	Gripper slots	14
10.3.12	Label area	14
10.4	Mechanical characteristics	14
10.4.1	Material	14
10.4.2	Mass	15
10.4.3	Edge Distortion	15
10.4.4	Compliance	15
10.4.5	Shutter opening force	15
11	Dimensional, mechanical and physical characteristics of the disk	27
11.1	General description of the disk	27
11.2	Reference axis and plane of the disk	27
11.3	Dimensions of the disk	28
11.3.1	Hub dimensions	28

11.3.2	Clamping zone	28
11.4	Mechanical characteristics	29
11.4.1	Material	29
11.4.2	Mass	29
11.4.3	Moment of inertia	29
11.4.4	Imbalance	29
11.4.5	Axial deflection	29
11.4.6	Axial acceleration	29
11.4.7	Radial runout	30
11.4.8	Radial acceleration	30
11.4.9	Tilt	30
11.5	Optical characteristics	30
11.5.1	Index of refraction	30
11.5.2	Thickness of the substrate	30
11.5.3	Birefringence	31
11.5.4	Reflectance	31
12	Interface between cartridge and drive	31
12.1	Clamping method	31
12.2	Clamping force	31
12.3	Capture cylinder (see figure 14)	31
12.4	Disk position in operating condition (see figure 14)	32
Section 3 - Format of information		34
13	Track geometry	34
13.1	Track shape	34
13.2	Direction of rotation	34
13.3	Track pitch	34
13.4	Track number	34
14	Track format	34
14.1	Track layout	34
14.2	Radial alignment	35
14.3	Sector Number	35
15	Sector format	35
15.1	Sector layout	35
15.2	Sector Mark	35
15.3	VFO fields	36
15.4	Address Mark (AM)	36
15.5	ID fields	36
15.6	Postambles (PA)	37
15.7	Offset Detection Field (ODF)	37
15.8	Gap	37
15.9	Sync	37
15.10	Data field	37
15.10.1	User data bytes	38
15.10.2	CRC and ECC bytes	38
15.10.3	Resync bytes	38
15.11	Buffer field	38

16	Recording code	38
17	Format of the Information Zone	39
17.1	General description of the Information Zone	39
17.2	Division of the Information Zone	39
17.2.1	Initial Zone	40
17.2.2	Acquire Zone	40
17.2.3	Test Zones	40
17.2.4	Control Zones	41
17.2.5	Data Zone	41
17.2.6	Buffer Zone	41
18	Format of the Data Zone	41
18.1	Defect Management Areas (DMAs)	42
18.2	Disk Definition Sector (DDS)	43
18.3	Rewritable Zone	45
18.3.1	Location	45
18.3.2	Partitioning	45
18.4	Embossed Zone	45
18.4.1	Location	45
18.4.2	Partitioning	46
18.4.3	Parity Sectors	46
19	Defect management in the Rewritable Zone	46
19.1	Initialization of the disk	47
19.2	Certification	47
19.2.1	Slipping Algorithm	47
19.2.2	Linear Replacement Algorithm	47
19.3	Disks not certified	47
19.4	Write procedure	48
19.5	Primary Defect List (PDL)	48
19.6	Secondary Defect List (SDL)	48
Section 4 - Characteristics of embossed information		50
20	Method of testing	50
20.1	Environment	50
20.2	Use of the Reference Drive	51
20.2.1	Optics and mechanics	51
20.2.2	Read power	51
20.2.3	Read channels	51
20.2.4	Tracking	51
20.3	Definition of signals	51
21	Signals from grooves	53
21.1	Cross-track signal	53
21.2	Cross-track minimum signal	53
21.3	Push-pull signal	53
21.4	Divided push-pull signal	54

21.5	On-track signal	54
21.6	Phase depth	55
21.7	Track location	55
22	Signals from Headers	55
22.1	Sector Mark	55
22.2	VFO1 and VFO2	55
22.3	Address Mark, ID field and Postamble	55
23	Signals from embossed Recording fields	56
Section 5 - Characteristics of the recording layer		56
24	Method of testing	56
24.1	Environment	56
24.2	Reference Drive	56
24.2.1	Optics and mechanics	56
24.2.2	Read power	56
24.2.3	Read channel	56
24.2.4	Tracking	57
24.3	Write conditions	57
24.3.1	Write pulse	57
24.3.2	Write power and pulse width	57
24.3.3	Write magnetic field	58
24.4	Erase conditions	58
24.4.1	Erase power	58
24.4.2	Erase magnetic field	58
24.5	Definition of signals	58
25	Magneto-optical characteristics	59
25.1	Figure of merit	59
25.2	Imbalance of the magneto-optical signal	59
26	Write characteristics	59
26.1	Resolution	59
26.2	Narrow-band signal-to-noise ratio	59
26.3	Cross-talk	60
27	Erase characteristics	60
Section 6 - Characteristics of user data		61
28	Method of testing	61
28.1	Environment	61
28.2	Reference Drive	61
28.2.1	Optics and mechanics	61
28.2.2	Read power	61
28.2.3	Read amplifiers	61
28.2.4	Analog-to-binary converters	61
28.2.5	Error correction	62
28.2.6	Tracking	62
29	Minimum quality of a sector	62
29.1	Headers	62

29.1.1	Sector Mark	62
29.1.2	ID fields	62
29.2	User-written data	62
29.3	Embossed data	62
30	Data interchange requirements	62
30.1	Tracking	62
30.2	User-written data	63
30.3	Embossed data	63
30.4	Quality of disk	63
Annexes		
A	Edge distortion test	64
B	Compliance test	65
C	Track deviation measurement	67
D	CRC for ID fields	71
E	Format of the Data field of a sector	72
F	Contents of the Control Zones	76
G	Guidelines for sector replacement	84
H	Measurement of the figure of merit	84
J	Read power, write power and erase power	85
K	Test method for measuring the adsorbent force of the hub	86
L	Derivation of the operating climatic environment	88
M	Air cleanliness class 100 000	92
N	Position of the cartridge relative to the reference planes	93
P	Transportation	94
Q	Office environment	94
R	Relaxation by zones of the requirements for signals	95

Foreword

ISO (the International Organization for Standardization) and IEC (the International Electrotechnical Commission) form the specialized system for worldwide standardization. National bodies that are members of ISO or IEC participate in the development of International Standards through technical committees established by the respective organization to deal with particular fields of technical activity. ISO and IEC technical committees collaborate in fields of mutual interest. Other international organizations, governmental and non-governmental, in liaison with ISO and IEC, also take part in the work.

In the field of information technology, ISO and IEC have established a joint technical committee, ISO/IEC JTC1. Draft International Standards adopted by the joint technical committee are circulated to national bodies for voting. Publication as an International Standard requires approval by at least 75% of the national bodies casting a vote.

International Standard ISO/IEC 10090 was prepared by the European Computer Manufacturers Association (as Standard ECMA-154) and was adopted, under a special "fast-track procedure", by Joint Technical Committee ISO/IEC JTC1, *Information technology* in parallel with its approval by national bodies of ISO and IEC.

Annexes A, B, D, E, F, H, K, M, N and R form an integral part of this International Standard. Annexes C, G, J, L, P and Q are for information only.

Introduction

This International Standard specifies the characteristics of 90 mm optical disk cartridges (ODCs) of the type providing for data to be written, read and erased many times using the thermo-magnetic and magneto-optical effects.

A part or all of the optical disk may be pre-recorded and be reproduced by stamping or other means. This information is read without recourse to the magneto-optical effect.

This International Standard together with a standard for volume and file structure provides for full data interchange between data processing systems. Interchange involves the ability to write, read and erase data without introducing any error.

Information technology - 90 mm optical disk cartridges, rewritable and read only, for data interchange

Section 1 - General

1 Scope

This International Standard specifies

- the conditions for conformance testing and the Reference Drive;
- the mechanical and physical characteristics of the cartridge, so as to provide mechanical interchangeability between data processing systems;
- the format of the information on the disk, both embossed and user-written;
- the characteristics of the embossed information on the disk;
- the magneto-optical characteristics of the disk, enabling processing systems to write data onto the disk;
- the minimum quality of user-written data on the disk, enabling data processing systems to read data from the disk.

2 Conformance

A 90 mm optical disk cartridge is in conformance with this International Standard if it meets all mandatory requirements specified herein.

Annex R specifies the zones of the disk in which the requirements for the signal characteristics given in the body of this International Standard shall be met, and the zones in which a relaxation of these requirements is permitted.

A drive claiming conformance with this International Standard shall be able, in the operating environment, to write on any optical disk cartridge which is in conformance with this International Standard, and to read from any optical disk cartridge which is in conformance with this International Standard.

A drive shall not claim conformance if it cannot accept the full range of media conforming to this International Standard but only a specific sub-set of it.

3 Normative reference

The following standard contains provisions which, through reference in this text, constitute provisions of this International Standard. At the time of publication, the edition indicated was valid. All standards are subject to revision, and parties to agreements based on this International Standard are encouraged to investigate the possibility of applying the most recent edition of the standard listed below. Members of IEC and ISO maintain registers of currently valid International Standards.

IEC 950:1991, *Safety of information technology equipment, including electrical business equipment*.