

INTERNATIONAL  
STANDARD

**ISO/IEC  
10885**

First edition  
1993-11-01

---

---

---

**Information technology — 356 mm optical  
disk cartridge for information  
interchange — Write once**

*Technologies de l'information — Cartouches de disques optiques de  
356 mm pour l'échange d'informations — Cartouches non réinscriptibles*



Reference number  
ISO/IEC 10885:1993(E)

**Contents**

		<b>Page</b>
<b>1</b>	<b>Scope</b>	<b>1</b>
<b>2</b>	<b>Conformance</b>	<b>1</b>
<b>3</b>	<b>Normative reference</b>	<b>1</b>
<b>4</b>	<b>Definitions</b>	<b>1</b>
<b>4.1</b>	<b>General</b>	<b>2</b>
<b>4.1.1</b>	caddy.	2
<b>4.1.2</b>	case	2
<b>4.1.3</b>	optical disk	2
<b>4.1.4</b>	optical disk carrier	2
<b>4.1.5</b>	optical disk cartridge	2
<b>4.1.6</b>	perimeter ring	2
<b>4.2</b>	<b>Disk</b>	<b>2</b>
<b>4.2.1</b>	air-sandwich disk	2
<b>4.2.2</b>	clamping zone	2
<b>4.2.3</b>	coversheet	2
<b>4.2.4</b>	disk reference plane	2
<b>4.2.5</b>	entrance surface	2
<b>4.2.6</b>	hub	2
<b>4.2.7</b>	protective layer	2
<b>4.2.8</b>	recording layer	2
<b>4.2.9</b>	spindle	2
<b>4.2.10</b>	tilt	2
<b>4.3</b>	<b>Optics</b>	<b>2</b>
<b>4.3.1</b>	actual write power	2
<b>4.3.2</b>	baseline reflectance	2
<b>4.3.3</b>	birefringence	2
<b>4.3.4</b>	cross-talk level	3
<b>4.3.5</b>	mark	3
<b>4.3.6</b>	narrow band signal-to-noise ratio	3
<b>4.3.7</b>	noise floor	3
<b>4.3.8</b>	optical retardation	3
<b>4.3.9</b>	read power	3
<b>4.3.10</b>	write power	3

<b>4.4</b>	<b>Format</b>	<b>3</b>
<b>4.4.1</b>	band	3
<b>4.4.2</b>	format	3
<b>4.4.3</b>	track	3
<b>4.4.4</b>	track pitch	3
<b>4.5</b>	<b>Errors</b>	<b>3</b>
<b>4.5.1</b>	cyclic redundancy check (CRC)	3
<b>4.5.2</b>	defect management	3
<b>4.5.3</b>	error correction code (ECC)	3
<b>4.5.4</b>	error detection and correction (EDAC)	3
<b>4.5.5</b>	interleaving	3
<b>4.5.6</b>	Reed-Solomon code	3
<b>5</b>	<b>Abbreviations and acronyms</b>	<b>3</b>
<b>6</b>	<b>Conventions</b>	<b>4</b>
<b>7</b>	<b>General description</b>	<b>4</b>
<b>8</b>	<b>Environment</b>	<b>4</b>
<b>8.1</b>	Testing environment	4
<b>8.2</b>	Operating environment	4
<b>8.3</b>	Storage environment	5
<b>8.3.1</b>	Short-term storage	5
<b>8.3.2</b>	Long-term storage	5
<b>8.3.3</b>	Transportation	5
<b>9</b>	<b>Safety requirements</b>	<b>5</b>
<b>9.1</b>	Safety	5
<b>9.2</b>	Flammability	5
<b>10</b>	<b>Dimensional and mechanical characteristics of the caddy</b>	<b>6</b>
<b>10.1</b>	General	6
<b>10.2</b>	Caddy drawings	6
<b>10.3</b>	Relationship of sides and interface with carrier	6
<b>10.3.1</b>	Relationship of sides	6
<b>10.3.2</b>	Interface with carrier	6
<b>10.3.3</b>	Write protect features (see figure 4)	6
<b>10.4</b>	Materials	7
<b>10.5</b>	Mass	7
<b>10.6</b>	Caddy dimensions	7
<b>10.6.1</b>	Overall dimensions of the caddy	7
<b>10.6.2</b>	Opening force of the caddy door	7
<b>10.6.3</b>	Location of the caddy window	7
<b>10.6.4</b>	Caddy write protect tabs	7

<b>10.6.5</b>	<b>Caddy autoload drive surfaces</b>	<b>7</b>
<b>11</b>	<b>Dimensional and mechanical characteristics of the carrier</b>	<b>17</b>
<b>11.1</b>	<b>General</b>	<b>17</b>
<b>11.2</b>	<b>Carrier drawings</b>	<b>17</b>
<b>11.3</b>	<b>Sides, reference axes and reference planes</b>	<b>18</b>
	<b>11.3.1 Relationship between Side A and Side B</b>	<b>18</b>
	<b>11.3.2 Reference axes and reference features</b>	<b>18</b>
<b>11.4</b>	<b>Materials</b>	<b>18</b>
<b>11.5</b>	<b>Mass</b>	<b>18</b>
<b>11.6</b>	<b>Location of the optical disk centre in the carrier</b>	<b>18</b>
<b>11.7</b>	<b>Overall dimensions of the carrier</b>	<b>18</b>
<b>11.8</b>	<b>Cutouts</b>	<b>19</b>
<b>11.9</b>	<b>Carrier latch points and latch actuation force</b>	<b>19</b>
<b>11.10</b>	<b>Carrier guide rails and carrier thickness</b>	<b>19</b>
<b>11.11</b>	<b>Carrier write protect hole</b>	<b>20</b>
<b>11.12</b>	<b>Carrier Side A or Side B sensor hole</b>	<b>20</b>
<b>11.13</b>	<b>Carrier disk type sensor notches</b>	<b>20</b>
<b>11.14</b>	<b>Carrier location within the caddy</b>	<b>21</b>
<b>11.15</b>	<b>Carrier locator pin slot characteristics and location within the caddy</b>	<b>21</b>
<b>11.16</b>	<b>Carrier latch point location when the carrier is inside the caddy</b>	<b>21</b>
<b>11.17</b>	<b>Carrier latch release hole locations</b>	<b>22</b>
<b>11.18</b>	<b>Carrier latch release hole locations for unlatched carrier</b>	<b>22</b>
<b>11.19</b>	<b>Location of carrier locator pin slots</b>	<b>22</b>
<b>11.20</b>	<b>Carrier label location</b>	<b>22</b>
<b>11.21</b>	<b>Carrier label</b>	<b>23</b>
<b>11.22</b>	<b>Carrier label characteristics</b>	<b>23</b>
<b>12</b>	<b>Dimensional and physical characteristics of the disk</b>	<b>37</b>
<b>12.1</b>	<b>General</b>	<b>37</b>
	<b>12.1.1 Protective layer</b>	<b>37</b>
	<b>12.1.2 Unobstructed access</b>	<b>37</b>
<b>12.2</b>	<b>Disk drawings</b>	<b>38</b>
<b>12.3</b>	<b>Sides, reference axes, reference plane</b>	<b>38</b>
	<b>12.3.1 Relationship of Sides A and B</b>	<b>38</b>
	<b>12.3.2 Reference axes and reference planes</b>	<b>38</b>
<b>12.4</b>	<b>Dimensions of the disk</b>	<b>38</b>
	<b>12.4.1 Outside diameter</b>	<b>38</b>
	<b>12.4.2 Outside diameter of the recording zone</b>	<b>38</b>
	<b>12.4.3 Inside diameter of the recording zone</b>	<b>38</b>
	<b>12.4.4 Outside diameter of the clamping zone</b>	<b>38</b>
	<b>12.4.5 Inside diameter of the clamping zone</b>	<b>39</b>
	<b>12.4.6 Inner diameter of the optical disk</b>	<b>39</b>
	<b>12.4.7 Optical disk inner diameter roundness</b>	<b>39</b>

<b>12.4.8</b>	<b>Location of the recording surface</b>	<b>39</b>
<b>12.4.9</b>	<b>Thickness of the clamping zone)</b>	<b>39</b>
<b>12.4.10</b>	<b>Inner diameter of the chamfer</b>	<b>39</b>
<b>12.4.11</b>	<b>Inner diameter chamfer angle</b>	<b>39</b>
<b>12.4.12</b>	<b>Outer diameter of the chamfer</b>	<b>40</b>
<b>12.4.13</b>	<b>Chamfer angle of the outer diameter</b>	<b>40</b>
<b>12.4.14</b>	<b>Dimensional characteristics of the protective layers</b>	<b>40</b>
<b>12.5</b>	<b>Mass</b>	<b>40</b>
<b>12.6</b>	<b>Moment of inertia</b>	<b>40</b>
<b>12.7</b>	<b>Imbalance</b>	<b>41</b>
<b>12.8</b>	<b>Apparent axial runout</b>	<b>41</b>
<b>12.9</b>	<b>Residual focus error</b>	<b>41</b>
<b>13</b>	<b>Handling requirements</b>	<b>41</b>
<b>13.1</b>	<b>Drop test</b>	<b>41</b>
<b>13.2</b>	<b>Dead weight strength</b>	<b>41</b>
<b>13.3</b>	<b>Exposure to ambient light</b>	<b>41</b>
<b>14</b>	<b>Interface between disk and drive</b>	<b>41</b>
<b>14.1</b>	<b>Clamping technique</b>	<b>41</b>
<b>14.2</b>	<b>Radial positioning</b>	<b>41</b>
<b>14.3</b>	<b>Reference surface</b>	<b>41</b>
<b>14.4</b>	<b>Clamping force</b>	<b>42</b>
<b>15</b>	<b>Characteristics of the protective layer</b>	<b>49</b>
<b>15.1</b>	<b>General</b>	<b>49</b>
<b>15.2</b>	<b>Characteristics of a 90 µm thick protective layer</b>	<b>49</b>
<b>15.2.1</b>	<b>Index of refraction</b>	<b>49</b>
<b>15.2.2</b>	<b>Thickness</b>	<b>49</b>
<b>15.2.3</b>	<b>Optical characteristics</b>	<b>49</b>
<b>15.2.4</b>	<b>Tilt</b>	<b>49</b>
<b>15.3</b>	<b>Characteristics of a 1,2 mm thick protective layer</b>	<b>49</b>
<b>15.3.1</b>	<b>Index of refraction</b>	<b>49</b>
<b>15.3.2</b>	<b>Thickness</b>	<b>49</b>
<b>15.3.3</b>	<b>Optical characteristics</b>	<b>49</b>
<b>15.3.4</b>	<b>Tilt</b>	<b>49</b>
<b>16</b>	<b>Characteristics of the recording layer</b>	<b>49</b>
<b>16.1</b>	<b>Test conditions</b>	<b>50</b>
<b>16.1.1</b>	<b>General</b>	<b>50</b>
<b>16.1.2</b>	<b>Read conditions</b>	<b>50</b>
<b>16.1.3</b>	<b>Write conditions</b>	<b>50</b>
<b>16.2</b>	<b>Baseline reflectance</b>	<b>51</b>
<b>16.2.1</b>	<b>General</b>	<b>51</b>

<b>16.2.2</b>	Actual value	<b>51</b>
<b>16.2.3</b>	Requirement	<b>51</b>
<b>16.3</b>	Write power requirement	<b>51</b>
<b>16.4</b>	Read power requirement	<b>51</b>
<b>16.5</b>	Prerecorded marks	<b>51</b>
<b>16.6</b>	Data written in user area	<b>51</b>
<b>16.6.1</b>	Reflectivity characteristics of written marks	<b>51</b>
<b>16.6.2</b>	Signals	<b>51</b>
<b>16.6.3</b>	Narrow-band signal-to-noise ratio	<b>52</b>
<b>16.6.4</b>	Cross-talk	<b>52</b>
<b>17</b>	Characteristics of the data organization on the disk	<b>52</b>
<b>17.1</b>	General description	<b>52</b>
<b>17.2</b>	Band organization	<b>53</b>
<b>17.2.1</b>	Recordable area in each band	<b>53</b>
<b>17.2.2</b>	Track shape in each band	<b>53</b>
<b>17.2.3</b>	Direction of rotation for each side	<b>53</b>
<b>17.2.4</b>	Track pitch	<b>53</b>
<b>17.2.5</b>	Radial eccentricity of pre-formatted information	<b>53</b>
<b>17.2.6</b>	Band numbers	<b>54</b>
<b>17.2.7</b>	Pre-formatted information in-track bit spacing	<b>54</b>
<b>17.2.8</b>	Rotational velocity	<b>54</b>
<b>17.2.9</b>	Number of sectors in each band	<b>54</b>
<b>17.3</b>	Formatted zones	<b>55</b>
<b>17.3.1</b>	Organization of the sectors in each band	<b>55</b>
<b>17.3.2</b>	Organization of the usable sectors	<b>56</b>
<b>17.3.3</b>	User sector organization	<b>58</b>
<b>17.4</b>	Requirements for interchange	<b>59</b>
<b>17.4.1</b>	Requirements for reading	<b>59</b>
<b>17.4.2</b>	Requirements for writing	<b>59</b>
<b>18</b>	Format	<b>59</b>
<b>18.1</b>	Track layout	<b>59</b>
<b>18.1.1</b>	Tracking	<b>59</b>
<b>18.1.2</b>	Tracking pads	<b>59</b>
<b>18.1.3</b>	Tracking pad tolerances	<b>60</b>
<b>18.1.4</b>	Tracking push-pull ratio	<b>60</b>
<b>18.1.5</b>	Focus	<b>60</b>
<b>18.1.6</b>	Recorded characteristics	<b>60</b>
<b>18.2</b>	Leader and manufacturing test sectors	<b>60</b>
<b>18.3</b>	Disk Identification Sector	<b>60</b>
<b>18.4</b>	Sectors of the bad sector map	<b>61</b>
<b>18.5</b>	Disk drive supplemental data	<b>61</b>
<b>18.6</b>	User supplemental data	<b>61</b>

<b>18.7</b>	Write power calibration and auto-rewrite sectors	<b>61</b>
<b>18.8</b>	User sector format	<b>61</b>
<b>18.8.1</b>	User sector header	<b>61</b>
<b>18.8.2</b>	User data field preamble and pre-formatted tracking pad	<b>62</b>
<b>18.8.3</b>	Pre-formatted tracking pads	<b>62</b>
<b>18.8.4</b>	User data field	<b>62</b>
<b>18.8.5</b>	Error detection and correction (EDAC)	<b>63</b>
<b>18.8.6</b>	Interface sector gap	<b>63</b>
<b>18.9</b>	Sectors following the user sectors in each band	<b>64</b>
<b>18.10</b>	Coding method	<b>64</b>

## Annexes

<b>A</b> - Definition of air cleanliness of class 100 000	<b>79</b>
<b>B</b> - Recommendation for transportation	<b>80</b>
<b>C</b> - Mechanical test method	<b>81</b>
<b>D</b> - Imbalance test method	<b>83</b>
<b>E</b> - Apparent axial runout test method	<b>84</b>
<b>F</b> - Residual focus error test method	<b>86</b>
<b>G</b> - Drop test method	<b>89</b>
<b>H</b> - Dead weight strength test method	<b>90</b>
<b>J</b> - Double-pass retardation test method	<b>91</b>
<b>K</b> - Signal characteristics test method	<b>94</b>
<b>L</b> - Optical disk write power test method	<b>96</b>
<b>M</b> - Read power test method	<b>98</b>
<b>N</b> - Narrow-band signal-to-noise ratio test method	<b>99</b>
<b>P</b> - Cross-talk test method	<b>100</b>
<b>Q</b> - Radial runout test method	<b>101</b>
<b>R</b> - Residual tracking error signal test method	<b>103</b>

## Foreword

ISO (the International Organization for Standardization) and IEC (the International Electrotechnical Commission) form the specialized system for worldwide standardization. National bodies that are members of ISO or IEC participate in the development of International Standards through technical committees established by the respective organization to deal with particular fields of technical activity. ISO and IEC technical committees collaborate in fields of mutual interest. Other international organizations, governmental and non-governmental, in liaison with ISO and IEC, also take part in the work.

In the field of information technology, ISO and IEC have established a joint technical committee, ISO/IEC JTC 1. Draft International Standards adopted by the joint technical committee are circulated to national bodies for voting. Publication as an International Standard requires approval by at least 75 % of the national bodies casting a vote.

International Standard ISO/IEC 10885 was prepared by Joint Technical Committee ISO/IEC JTC 1, *Information technology*, Sub-Committee SC 23, *Optical disk cartridges for information interchange*.

Annexes A, C, D, E, F, G, H, J, K, L, M, N, P, Q and R form an integral part of this International Standard. Annex B is for information only.

# Information technology — 356 mm optical disk cartridge for information interchange — Write once

## 1 Scope

This International Standard specifies the characteristics of 356 mm optical disk cartridges of the type providing for information to be written once and read many times.

ISO 10885 specifies

- definitions of essential concepts,
- the environment in which the characteristics shall be tested,
- the environments in which the cartridge shall be operated and stored,
- the mechanical, physical and dimensional characteristics of the case and of the optical disk,
- the optical characteristics and the recording characteristics for recording the information once and for reading it many times, so as to provide physical interchangeability between data processing systems.
- the format for the physical disposition of the tracks and sectors, the error correction codes, the modulation methods used for recording and the quality of the recorded signals.

Together with a standard for volume and file structure, ISO/IEC 10885 provides for full data interchange between data processing systems.

## 2 Conformance

A 356 mm optical disk cartridge is in conformance with this International Standard if it meets all the mandatory requirements herein.

## 3 Normative reference

The following standard contains provisions which, through reference in this text, constitute provisions of this International Standard. At the time of publication, the edition indicated was valid. All standards are subject to revision, and parties to agreements based on this International Standard are encouraged to investigate the possibility of applying the most recent edition of the standard listed below. Members of IEC and ISO maintain registers of currently valid international standards.

ISO/IEC 646:1991 *Information Technology - ISO 7-bit coded character set for information interchange.*