

INTERNATIONAL
STANDARD

ISO/IEC
11559

First edition
1993-08-15

**Information technology — Data
interchange on 12,7 mm wide 18-track
magnetic tape cartridges — Extended
format**

*Technologies de l'information — Échange de données sur cartouche de
bande magnétique de 12,7 mm de large à 18 pistes — Format étendu*



Reference number
ISO/IEC 11559:1993(E)

Contents	Page
Section 1 - General	1
1 Scope	1
2 Conformance	1
2.1 Magnetic tape cartridge	1
2.2 Generating system	1
2.3 Receiving system	1
3 Normative references	2
4 Definitions	2
4.1 algorithm	2
4.2 Average Signal Amplitude	2
4.3 back surface	2
4.4 Beginning of Tape (BOT)	2
4.5 byte	2
4.6 cartridge	2
4.7 Cyclic Redundancy Check Character	2
4.8 Data Block	2
4.9 Data Records	2
4.9.1 Processed Data Record (PDR)	2
4.9.2 Host Data Record	2
4.9.3 Logical Data Record (LDR)	3
4.9.4 User Data Record (UDR)	3
4.10 Error Correcting Code	3
4.11 flux transition position	3
4.12 flux transition spacing	3
4.13 magnetic tape	3
4.14 Master Standard Reference Tape	3
4.15 Packet	3
4.16 Packet Identifier	3
4.17 Packet Trailer	3

4.18	pad byte	3
4.19	physical recording density	3
4.20	Postamble	3
4.21	Preamble	3
4.22	Processed Data	3
4.23	processing	3
4.24	Reference Field	3
4.25	Secondary Standard Reference Tape	3
4.26	Standard Reference Amplitude (SRA)	4
4.27	Standard Reference Current	4
4.28	Test Recording Current	4
4.29	track	4
4.30	Typical Field	4
4.31	transformation	4
5	Conventions and notations	4
5.1	Representation of numbers	4
5.2	Names	4
5.3	Acronyms	4
6	Environment and safety	5
6.1	Cartridge/Tape testing environment	5
6.2	Cartridge operating environment	5
6.3	Cartridge storage environment	5
6.4	Safety requirements	5
6.4.1	Safeness	5
6.4.2	Flammability	5
6.5	Transportation	5
Section 2 - Characteristics of the tape		6
7	Characteristics of the tape	6
7.1	Material	6
7.2	Tape length	6
7.3	Tape width	6
7.4	Tape discontinuity	6
7.5	Total thickness of tape	6
7.6	Base material thickness	6
7.7	Longitudinal curvature	6
7.8	Out-of-plane distortions	6
7.9	Cupping	6
7.10	Dynamic frictional characteristics	7
7.10.1	Frictional drag between the recording surface and the tape back surface	7
7.10.2	Frictional drag between the tape recording surface and ferrite after environmental cycling	7
7.11	Coating adhesion	7
7.12	Flexural rigidity	8
7.13	Electrical resistance of coated surfaces	8
7.14	Tape durability	9
7.15	Inhibitor tape	9

7.16	Tape abrasivity	9
7.17	Pre-recording condition	10
7.18	Magnetic recording characteristics	10
7.18.1	Typical Field	10
7.18.2	Signal amplitude	10
7.18.3	Resolution	10
7.18.4	Overwrite	10
7.18.5	Narrow-band signal-to-noise ratio (NB-SNR)	11
7.19	Tape quality	11
7.19.1	Missing pulses	12
7.19.2	Missing pulse zones	12
7.19.3	Coincident missing pulse zones	12
Section 3 - Cartridge		12
8	Dimensional and mechanical characteristics of the cartridge	12
8.1	Overall dimensions	13
8.2	Write-inhibit mechanism	13
8.3	Label area of the rear side	14
8.4	Label area of the top side	14
8.5	Case opening	14
8.6	Locating notches	15
8.7	Locating areas	15
8.8	Inside configuration of the case around the case opening	15
8.9	Other external dimensions of the case	15
8.10	Central window	16
8.11	Stacking ribs	16
8.12	Flexibility of the case	16
8.12.1	Requirements	16
8.12.2	Procedure	16
8.13	Tape reel	17
8.13.1	Locking mechanism	17
8.13.2	Axis of rotation of the reel	17
8.13.3	Metallic insert	17
8.13.4	Toothed rim	17
8.13.5	Hub of the reel	17
8.13.6	Relative positions	18
8.13.7	Characteristics of the toothed rim	19
8.14	Leader block	19
8.15	Attachment of the tape to the header block	20
8.16	Latching mechanism	20
8.17	Tape wind	20
8.18	Wind tension	20
8.19	Circumference of the tape reel	21
8.20	Moment of inertia	21
Section 4 - Recording method and formats		28
9	Method of recording	28

9.1	Physical recording density	28
9.2	Bit cell length	28
9.3	Average bit cell length	28
9.4	Long-term average bit cell length	28
9.5	Short-term average bit cell length (STA)	28
9.6	Rate of change	28
9.7	Bit shift	28
9.8	Total character skew	29
9.9	Read signal amplitude	29
9.10	Coincident missing pulse zones	29
10	Track format	29
10.1	Number of tracks	29
10.2	Reference edge	29
10.3	Track positions	29
10.4	Track width	29
10.5	Azimuth	30
11	Packet format	30
11.1	Packet elements	30
11.2	Packet ID	30
11.3	UDR	31
11.4	Packet Trailer	31
11.4.1	Packet Trailer when data has been processed	31
11.4.2	Packet Trailer when data has not been processed	31
12	Data Block format	32
12.1	Data Part	32
12.1.1	Packet Bytes	32
12.1.2	Count Field Bytes	32
12.1.3	Block-ID Bytes	32
12.2	Allocation of Data Bytes to frames	33
12.2.1	Prefix Frames	34
12.2.2	Data Frames	34
12.2.3	Residual Frame 1	35
12.2.4	Residual Frame 2	35
12.2.5	Suffix Frames	37
12.3	Error Correcting Code (ECC)	37
12.3.1	Diagonal Redundancy Check (DRC)	38
12.3.2	Vertical Redundancy Check (VRC)	38
12.3.3	ECC Format	38
12.3.4	Summary of ECC2)	39
12.4	Recording of 8-bit bytes on the tape	40
12.5	Recorded Data Block	40
12.5.1	Preamble	40
12.5.2	Beginning of Data Mark (BDM)	41

12.5.3	Resync Control Frame	41
12.5.4	End of Data Mark (EDM)	41
12.5.5	Postamble	41
12.6	Data Density	41
13	Tape format	41
13.1	Density Identification Burst	42
13.2	ID Separator Burst	42
13.3	Interblock Gaps	42
13.4	Erase Gaps	43
13.4.1	Normal Erase Gaps	43
13.4.2	Elongated Erase Gaps	43
13.5	Tape Marks	43
13.6	Relationship between Interblock Gaps, Erase Gaps and Tape Marks	44
13.6.1	Interblock Gap followed by a Tape Mark	44
13.6.2	Tape Mark followed by an Interblock Gap	44
13.6.3	Interblock Gap followed by an Erase Gap	44
13.6.4	Erase Gap followed by an Interblock Gap	44
13.6.5	Summary of the relationship between Interblock Gaps, Erase Gaps and Tape Marks	45
13.7	First and last recording on the tape	45
13.8	Summary of the tape format	46
13.9	Transform Change Records (TCRs)	47
Annexes		
A	- Recommendations for transportation	49
B	- Inhibitor tape	50
C	- Tape abrasivity measurement procedure	51
D	- Recommendations on tape durability	53
E	- Pre-recording condition	54
F	- Representation of 8-bit bytes by 9-bit patterns	55
G	- Measurement of bit shift	58
H	- Summary of data flow	60
J	- Implementation of a CRC	61
K	- Calculation of a Physical Position Indicator	62

Foreword

ISO (the International Organization for Standardization) and IEC (the International Electrotechnical Commission) form the specialized system for worldwide standardization. National bodies that are members of ISO or IEC participate in the development of International Standards through technical committees established by the respective organization to deal with particular fields of technical activity. ISO and IEC technical committees collaborate in fields of mutual interest. Other international organizations, governmental and non-governmental, in liaison with ISO and IEC, also take part in the work.

In the field of information technology, ISO and IEC have established a joint technical committee, ISO/IEC JTC 1. Draft International Standards adopted by the joint technical committee are circulated to national bodies for voting. Publication as an International Standard requires approval by at least 75 % of the national bodies casting a vote.

International Standard ISO/IEC 11559 was prepared by European Computer Manufacturers Associations (as ECMA-152) and was adopted, under a special "fast-track procedure", by Joint Technical Committee ISO/IEC JTC 1, *Information technology*, in parallel with its approval by national bodies of ISO and IEC.

Annexes C, E, F, G and K form an integral part of this International Standard. Annexes A, B, D, H and J are for information only.

Introduction

ISO/IEC 11559 incorporates all the specifications of ISO 9661, together with extensions and modifications which specify the additional features of an extended format that also allows higher capacities to be achieved. The specifications of the tape, cartridge, recorded signal, recording method and most of the recorded format are identical with those in ISO 9661.

It is not intended that this International Standard replaces ISO 9661. Existing drives and cartridges which conform to ISO 9661 will continue to do so and will not conform to all requirements of this International Standard. Drives conforming to this International Standard will be able to write on, and read from, cartridges conforming to ISO 9661.

Information technology — Data interchange on 12,7 mm wide 18-track magnetic tape cartridges — Extended format**Section 1 - General****1 Scope**

This International Standard specifies the physical and magnetic characteristics of a 12,7 mm wide, 18-track magnetic tape cartridge, to enable interchangeability of such cartridges. It also specifies the quality of the recorded signals, the format and the recording method, thus allowing, together with ISO 1001, full data interchange by means of such magnetic tape cartridges.

The cartridge and recording method are identical with those described in ISO 9661. This International Standard specifies extensions to the transformation of data before it is formatted as in ISO 9661.

These extensions

- specify a method for increasing the utilization of the tape by combining smaller blocks of data into extended blocks;
- specify a method for identifying whether the recorded data has been processed and, if it has been processed, the algorithm used for processing;
- specify a method for including recorded data blocks conforming to this International Standard and recorded data blocks conforming to ISO 9661 on the same tape.

The permissible routes for the flow of data are shown in annex H.

2 Conformance**2.1 Magnetic tape cartridge**

A magnetic tape cartridge shall be in conformance with this International Standard if

- the cartridge meets all the requirements of clauses 4 and 6 to 8;
- the recording on the tape meets the requirements of clauses 9 to 13;
- for each recorded packet the algorithm used for processing the data therein, if processed data has been recorded, has (have) been registered and the registered identification is included in Byte 13 of the Packet ID Block of this packet (see 11.2).
- Note 1 - If the algorithm has not been registered Byte 13 shall be set to (FF).

2.2 Generating system

A system generating a magnetic tape cartridge for interchange shall be entitled to claim conformance with this International Standard if all the recordings that it makes on a tape meet the mandatory requirements of this International Standard. A claim of conformance shall state whether or not one, or more, registered algorithms are implemented and, if so, the registered number(s) of all implemented algorithm(s).

2.3 Receiving system

A system receiving a magnetic tape cartridge for interchange shall be entitled to claim conformance with this International Standard if it is able to handle any recording made on the tape according to this International Standard. In particular it shall

- be able to recognize the occurrence of extended blocks and to identify and retrieve data from individual packets within the extended blocks;
- be able to recognize that the data has been processed, to identify the algorithm(s) used, and to indicate to the host if it cannot restore the data to its original form;

- be capable of restoring to its original form data which has been processed according to zero or more registered algorithms.

A claim of conformance shall state whether or not one, or more, registered algorithm(s) is (are) implemented and, if so, the registered number(s) of all implemented algorithms.

3 Normative references

The following standards contain provisions which, through reference in this text, constitute provisions of this International Standard. At the time of publication, the editions indicated were valid. All standards are subject to revision, and parties to agreements based on this International Standard are encouraged to investigate the possibility of applying the most recent edition of the standards listed below. Members of IEC and ISO maintain registers of currently valid International Standards.

ISO 683-13:1986, *Heat-treatable steels, alloy steels and free-cutting steels - Part 13: Wrought stainless steels.*

ISO 1001:1986, *Information processing - File structure and labelling of magnetic tapes for information interchange.*

ISO 1302:1992, *Technical drawings - Method of indicating surface texture on drawings.*

ISO 9661:1986, *Information processing - Data interchange on 12,7 mm (0,5 in) wide magnetic tape cartridges - 18-tracks, 1 491 data bytes per millimetre (37 871 data bytes per inch).*

ISO/IEC 11576:1993, *Information technology - Procedure for the registration of algorithms for the lossless compression of data.*