

INTERNATIONAL  
STANDARD

ISO/IEC  
12246

First edition  
1993-12-15

---

---

---

**Information technology — 8 mm wide  
magnetic tape cartridge dual azimuth  
format for information interchange —  
Helical scan recording**

*Technologies de l'information — Cartouche de bande magnétique de  
8 mm de large de format double azimut pour l'échange  
d'information — Enregistrement par balayage en spirale*



**Contents**

	<b>Page</b>
<b>Section 1 - General</b>	<b>1</b>
<b>1 Scope</b>	<b>1</b>
<b>2 Conformance</b>	<b>1</b>
<b>3 Normative references</b>	<b>1</b>
<b>4 Definitions</b>	<b>1</b>
<b>4.1 a.c. erase</b>	<b>1</b>
<b>4.2 algorithm</b>	<b>1</b>
<b>4.3 Average Signal Amplitude</b>	<b>1</b>
<b>4.4 azimuth</b>	<b>2</b>
<b>4.5 back surface</b>	<b>2</b>
<b>4.6 bit cell</b>	<b>2</b>
<b>4.7 byte</b>	<b>2</b>
<b>4.8 cartridge</b>	<b>2</b>
<b>4.9 compressed data</b>	<b>2</b>
<b>4.10 Cyclic Redundancy Check (CRC) Character</b>	<b>2</b>
<b>4.11 Error Correcting Code (ECC)</b>	<b>2</b>
<b>4.12 flux transition position</b>	<b>2</b>
<b>4.13 flux transition spacing</b>	<b>2</b>
<b>4.14 logical record</b>	<b>2</b>
<b>4.15 magnetic tape</b>	<b>2</b>
<b>4.16 Master Standard Reference Tape</b>	<b>2</b>
<b>4.17 Physical Beginning of Tape (PBOT)</b>	<b>2</b>
<b>4.18 Physical End of Tape (PEOT)</b>	<b>2</b>
<b>4.19 physical recording density</b>	<b>2</b>
<b>4.20 Secondary Reference Amplitude</b>	<b>2</b>
<b>4.21 Secondary Reference Field</b>	<b>2</b>
<b>4.22 Secondary Standard Reference Tape</b>	<b>2</b>

<b>4.23</b>	<b>Standard Reference Current</b>	<b>2</b>
<b>4.24</b>	<b>Tape Reference Edge</b>	<b>2</b>
<b>4.25</b>	<b>Test Recording Current</b>	<b>2</b>
<b>4.26</b>	<b>track</b>	<b>2</b>
<b>4.27</b>	<b>Typical Field</b>	<b>2</b>
<b>4.28</b>	<b>uncompressed data</b>	<b>2</b>
<b>5</b>	<b>Environment and safety</b>	<b>3</b>
<b>5.1</b>	<b>Testing environment</b>	<b>3</b>
<b>5.2</b>	<b>Operating environment</b>	<b>3</b>
<b>5.3</b>	<b>Storage environment</b>	<b>3</b>
<b>5.4</b>	<b>Transportation</b>	<b>3</b>
<b>5.5</b>	<b>Safety</b>	<b>3</b>
<b>5.6</b>	<b>Flammability</b>	<b>3</b>
<b>Section 2 - Cartridge</b>		<b>4</b>
<b>6</b>	<b>Dimensional and mechanical characteristics of the cartridge</b>	<b>4</b>
<b>6.1</b>	<b>General</b>	<b>4</b>
<b>6.2</b>	<b>Overall dimensions</b>	<b>4</b>
<b>6.3</b>	<b>Holding areas</b>	<b>4</b>
<b>6.4</b>	<b>Cartridge insertion</b>	<b>5</b>
<b>6.5</b>	<b>Window</b>	<b>5</b>
<b>6.6</b>	<b>Loading grips</b>	<b>5</b>
<b>6.7</b>	<b>Label areas</b>	<b>6</b>
<b>6.8</b>	<b>Datum areas and datum holes</b>	<b>6</b>
<b>6.9</b>	<b>Support areas</b>	<b>7</b>
<b>6.10</b>	<b>Recognition holes</b>	<b>7</b>
<b>6.11</b>	<b>Write-inhibit hole</b>	<b>8</b>
<b>6.12</b>	<b>Pre-positioning surfaces</b>	<b>8</b>
<b>6.13</b>	<b>Cartridge lid</b>	<b>9</b>
<b>6.14</b>	<b>Cartridge reel lock</b>	<b>10</b>
<b>6.15</b>	<b>Reel access holes</b>	<b>11</b>
<b>6.16</b>	<b>Interface between the reels and the drive spindles</b>	<b>11</b>
<b>6.17</b>	<b>Light path</b>	<b>12</b>
<b>6.18</b>	<b>Position of the tape in the case</b>	<b>12</b>
<b>6.19</b>	<b>Tape path zone</b>	<b>12</b>
<b>6.20</b>	<b>Tape access cavity</b>	<b>13</b>
<b>6.21</b>	<b>Tape access cavity clearance requirements</b>	<b>13</b>
<b>Section 3 - Requirements for the unrecorded tape</b>		<b>30</b>
<b>7</b>	<b>Mechanical, physical and dimensional characteristics of the tape</b>	<b>30</b>
<b>7.1</b>	<b>Materials</b>	<b>30</b>
<b>7.2</b>	<b>Tape length</b>	<b>30</b>
<b>7.2.1</b>	<b>Magnetic tape</b>	<b>30</b>
<b>7.2.2</b>	<b>Leader and trailer tapes</b>	<b>30</b>
<b>7.2.3</b>	<b>Splicing tape</b>	<b>30</b>

<b>7.3</b>	<b>Width</b>	<b>30</b>
<b>7.4</b>	<b>Discontinuities</b>	<b>30</b>
<b>7.5</b>	<b>Thickness</b>	<b>30</b>
<b>7.5.1</b>	<b>Thickness of magnetic tape</b>	<b>30</b>
<b>7.5.2</b>	<b>Thickness of leader and trailer tape</b>	<b>30</b>
<b>7.6</b>	<b>Longitudinal curvature</b>	<b>30</b>
<b>7.7</b>	<b>Cupping</b>	<b>31</b>
<b>7.8</b>	<b>Coating adhesion</b>	<b>31</b>
<b>7.9</b>	<b>Layer-to-layer adhesion</b>	<b>31</b>
<b>7.10</b>	<b>Tensile strength</b>	<b>32</b>
<b>7.10.1</b>	<b>Breaking strength</b>	<b>32</b>
<b>7.10.2</b>	<b>Yield strength</b>	<b>32</b>
<b>7.11</b>	<b>Residual elongation</b>	<b>32</b>
<b>7.12</b>	<b>Electrical resistance of the surface</b>	<b>32</b>
<b>7.13</b>	<b>Tape winding</b>	<b>33</b>
<b>7.14</b>	<b>Light transmittance of tape</b>	<b>33</b>
<b>8</b>	<b>Magnetic recording performance</b>	<b>33</b>
<b>8.1</b>	<b>Test conditions</b>	<b>33</b>
<b>8.2</b>	<b>Typical Field</b>	<b>33</b>
<b>8.3</b>	<b>Signal amplitude</b>	<b>34</b>
<b>8.4</b>	<b>Resolution</b>	<b>34</b>
<b>8.5</b>	<b>Narrow-band signal-to-noise ratio</b>	<b>34</b>
<b>8.5.1</b>	<b>Requirement</b>	<b>34</b>
<b>8.5.2</b>	<b>Procedure</b>	<b>34</b>
<b>8.6</b>	<b>Ease of erasure</b>	<b>34</b>
<b>8.7</b>	<b>Tape quality</b>	<b>34</b>
<b>8.7.1</b>	<b>Missing pulses</b>	<b>34</b>
<b>8.7.2</b>	<b>Missing pulse zone</b>	<b>34</b>
<b>8.8</b>	<b>Inhibitor tape</b>	<b>34</b>
<b>Section 4 - Requirements for an interchanged tape</b>		<b>35</b>
<b>9</b>	<b>Format</b>	<b>35</b>
<b>9.1</b>	<b>General</b>	<b>35</b>
<b>9.2</b>	<b>Information Matrix</b>	<b>35</b>
<b>9.2.1</b>	<b>Loading of the Information Matrix</b>	<b>36</b>
<b>10</b>	<b>Method of recording</b>	<b>41</b>
<b>10.1</b>	<b>Physical recording density</b>	<b>41</b>

<b>10.1.1</b>	Long-term average bit cell length	<b>41</b>
<b>10.1.2</b>	Short-term average bit cell length	<b>41</b>
<b>10.1.3</b>	Rate of change	<b>41</b>
<b>10.2</b>	Bit shift	<b>41</b>
<b>10.3</b>	Read signal amplitudes	<b>41</b>
<b>10.3.1</b>	Amplitude of data signals	<b>41</b>
<b>10.3.2</b>	Amplitude of servo signals	<b>41</b>
<b>10.4</b>	Erasure	<b>41</b>
<b>11</b>	Track geometry	<b>42</b>
<b>11.1</b>	Track positions	<b>42</b>
<b>11.2</b>	Track pitch	<b>43</b>
<b>11.2.1</b>	Adjacent track pitch	<b>43</b>
<b>11.2.2</b>	Average track pitch	<b>43</b>
<b>11.3</b>	Track width	<b>43</b>
<b>11.4</b>	Track angle	<b>43</b>
<b>11.5</b>	Straightness of track edge	<b>43</b>
<b>11.6</b>	Azimuth	<b>43</b>
<b>12</b>	Format of a track	<b>43</b>
<b>12.1</b>	Channel Bit	<b>43</b>
<b>12.2</b>	Information Segment	<b>43</b>
<b>12.2.1</b>	Bit Synchronization Field	<b>44</b>
<b>12.2.2</b>	Information Segment Number	<b>44</b>
<b>12.2.3</b>	Information Segment field	<b>44</b>
<b>12.3</b>	Information Block	<b>45</b>
<b>12.4</b>	Physical track types	<b>45</b>
<b>12.4.1</b>	T1 and T2 track layouts	<b>46</b>
<b>12.5</b>	Search Field Zones	<b>46</b>
<b>12.5.1</b>	Search Field Data Zones	<b>46</b>
<b>12.5.2</b>	Search Field Zone Sequence of recording	<b>48</b>
<b>12.6</b>	Servo Zone	<b>49</b>
<b>12.6.1</b>	Servo Zone 1	<b>49</b>
<b>12.6.2</b>	Servo Zone 2	<b>49</b>
<b>12.6.3</b>	Servo Zone 3	<b>49</b>
<b>12.7</b>	Information Tracks	<b>49</b>

<b>12.7.1</b>	<b>Format Track</b>	<b>49</b>
<b>12.7.2</b>	<b>Data Track</b>	<b>49</b>
<b>12.7.3</b>	<b>Long Tape Mark Track</b>	<b>49</b>
<b>12.7.4</b>	<b>Gap Track</b>	<b>49</b>
<b>12.7.5</b>	<b>End of Data Track</b>	<b>49</b>
<b>13</b>	<b>Tape Mark</b>	<b>50</b>
<b>13.1</b>	<b>Long Tape Mark</b>	<b>50</b>
<b>13.2</b>	<b>Short Tape Mark</b>	<b>50</b>
<b>14</b>	<b>End of Data</b>	<b>50</b>
<b>15</b>	<b>ID Information</b>	<b>50</b>
<b>15.1</b>	<b>Physical Block ID</b>	<b>50</b>
<b>15.2</b>	<b>Logical Block ID</b>	<b>50</b>
<b>15.3</b>	<b>Logical Record ID</b>	<b>50</b>
<b>15.4</b>	<b>Block type</b>	<b>50</b>
<b>15.4.1</b>	<b>Data Block</b>	<b>51</b>
<b>15.4.2</b>	<b>Gap Block</b>	<b>52</b>
<b>15.4.3</b>	<b>Format Block</b>	<b>52</b>
<b>15.4.4</b>	<b>Long/Short Tape Mark Block</b>	<b>53</b>
<b>15.4.5</b>	<b>End of Data Block</b>	<b>53</b>
<b>16</b>	<b>Rewritten Information Blocks</b>	<b>53</b>
<b>17</b>	<b>Physical Tape Format</b>	<b>54</b>
<b>17.1</b>	<b>Initial Erased Area</b>	<b>54</b>
<b>17.2</b>	<b>Logical Beginning of Tape Area (LBOT Area)</b>	<b>54</b>
<b>17.3</b>	<b>Usable area of the tape</b>	<b>54</b>
<b>Annexes</b>		
<b>A -</b>	<b>Measurement of light transmittance of tape and leaders</b>	<b>55</b>
<b>B -</b>	<b>Measurement of bit shift</b>	<b>58</b>
<b>C -</b>	<b>Representation of 8-bit bytes by 10-bit patterns</b>	<b>61</b>
<b>D -</b>	<b>Recommendations for transportation</b>	<b>64</b>
<b>E -</b>	<b>Inhibitor tape</b>	<b>65</b>

## Foreword

ISO (the International Organization for Standardization) and IEC (the International Electrotechnical Commission) form the specialized system for worldwide standardization. National bodies that are members of ISO or IEC participate in the development of International Standards through technical committees established by the respective organization to deal with particular fields of technical activity. ISO and IEC technical committees collaborate in fields of mutual interest. Other international organizations, governmental and non-governmental, in liaison with ISO and IEC, also take part in the work.

In the field of information technology, ISO and IEC have established a joint technical committee, ISO/IEC JTC 1. Draft International Standards adopted by the joint technical committee are circulated to national bodies for voting. Publication as an International Standard requires approval by at least 75 % of the national bodies casting a vote.

International Standard ISO/IEC 12246 was prepared by the European Computer Manufacturers Association (ECMA) (as Standard ECMA-169) and was adopted, under a special "fast-track procedure", by Joint Technical Committee ISO/IEC JTC 1, *Information technology*, in parallel with its approval by national bodies of ISO and IEC.

Annexes A, B and C form an integral part of this International Standard. Annexes D, E and F are for information only.

## Introduction

ISO/IEC have produced a series of International Standards for cassettes and cartridges containing magnetic tapes of different width and characteristics.

The first International Standards (e.g. ISO 3407, ISO 4057, ISO 8063, ISO 8462, ISO/IEC 9661, ISO/IEC 11559) dealt with media designed for the digital recording of data for storage and processing in data processing systems. Later, other magnetic media, originally developed for audio and video applications, have been considered for use in data processing applications for storage as well as for information interchange. The recording method known as helical scan recording, together with new types of magnetic tapes, allows to achieve capacities of more than 1 gigabyte of user data. International Standards ISO/IEC 10777, ISO/IEC 11319, ISO/IEC 11321, ISO/IEC 11557, ISO/IEC 12247 and ISO/IEC 12248 deal with such magnetic tape cartridges.

This International Standard is based on ISO/IEC 11319 with extensions and modifications which specify the additional features of the Dual Azimuth format. The specifications of the tape, cartridge, recorded signal, recording method and much of the recorded format are identical with those in ISO/IEC 11319.

It is not intended that this International Standard replace ISO/IEC 11319. Existing drives and cartridges which conform to ISO/IEC 11319 will continue to do so and will not conform to this International Standard. Future drives and tapes which conform to ISO/IEC 11319 may, in addition, conform to this International Standard, but only if they support those features herein which are not in ISO/IEC 11319.

**Information technology - 8 mm wide magnetic tape cartridge dual azimuth format for information interchange - Helical scan recording****Section 1 - General****1 Scope**

This International Standard specifies the physical and magnetic characteristics of an 8 mm wide magnetic tape cartridge to enable interchangeability of such cartridges. It also specifies the quality of the recorded signals, the format and the recording method, thus allowing, together with ISO 1001 for Magnetic Tape Labelling, full data interchange by means of such magnetic tape cartridges. It is based on ISO/IEC 11319, but uses Dual Azimuth Recording to allow the raw capacity to be doubled. The format supports variable length Logical Records, high speed search, and the use of a registered data compression algorithm.

**2 Conformance**

A magnetic tape cartridge conforms to this International Standard if it satisfies all mandatory requirements specified herein. The tape requirements shall be satisfied throughout the extent of the tape.

**3 Normative references**

The following standards contain provisions which, through reference in this text, constitute provisions of this International Standard. At the time of publication, the editions indicated were valid. All standards are subject to revision, and parties to agreements based on this International Standard are encouraged to investigate the possibility of applying the most recent editions of the standards listed below. Members of IEC and ISO maintain registers of currently valid International Standards.

ISO/R 527:1966, *Plastics - Determination of tensile properties*.

ISO 1001:1986, *Information processing - File structure and labelling of magnetic tapes for information interchange*.

ISO 1302:1992, *Technical drawings - Method of indicating surface texture*.

ISO/IEC 11319: 1993, *Information technology - 8 mm wide magnetic tape cartridge for information interchange - Helical scan recording*.

ISO/IEC 11576:1993, *Information technology - Procedure for the registration of algorithms for the lossless compression of data*.

IEC 950:1991, *Safety of information technology equipment, including electrical business equipment*.