
**Information technology — 120 mm
(8,54 Gbytes per side) and 80 mm
(2,66 Gbytes per side) DVD recordable
disk for dual layer (DVD-R for DL)**

*Technologies de l'information — Disques DVD enregistrables de
120 mm (8,54 Go par face) et 80 mm (2,66 Go par face) pour double
couche (DVD-R pour DL)*



COPYRIGHT PROTECTED DOCUMENT

© ISO/IEC 2011

All rights reserved. Unless otherwise specified, no part of this publication may be reproduced or utilized in any form or by any means, electronic or mechanical, including photocopying and microfilm, without permission in writing from either ISO at the address below or ISO's member body in the country of the requester.

ISO copyright office
Case postale 56 • CH-1211 Geneva 20
Tel. + 41 22 749 01 11
Fax + 41 22 749 09 47
E-mail copyright@iso.org
Web www.iso.org

Published in Switzerland

Contents

Page

Foreword	vii
Introduction.....	viii
1 Scope	1
2 Conformance	1
2.1 Optical Disk	1
2.2 Generating system	2
2.3 Receiving system	2
3 Normative references	2
4 Terms and definitions	2
5 Conventions and notations	6
5.1 Representation of numbers	6
5.2 Names	6
6 Abbreviated terms	6
7 General description of a disk	8
8 General requirement	9
8.1 Environments	9
8.1.1 Test environment.....	9
8.1.2 Operating environment.....	9
8.1.3 Storage environment.....	10
8.1.4 Transportation	10
8.2 Safety requirements	10
8.3 Flammability.....	10
9 Reference measurement devices	10
9.1 Pick-Up Head (PUH)	10
9.1.1 PUH for measuring recorded disks	10
9.1.2 PUH for measuring unrecorded disks.....	12
9.2 Measurement conditions	13
9.2.1 Recorded and unrecorded disk	13
9.2.2 Recorded disk.....	13
9.2.3 Unrecorded disk	13
9.3 Normalized servo transfer function.....	14
9.4 Reference servo for axial tracking.....	14
9.4.1 Recorded disk.....	14
9.4.2 Unrecorded disk	15
9.5 Reference servo for radial tracking	16
9.5.1 Recorded disk.....	16
9.5.2 Unrecorded disk	17
10 Dimensional characteristics.....	18
10.1 Overall dimensions	20
10.2 First transition area	20
10.3 Second transition area.....	21
10.4 Clamping Zone.....	21
10.5 Third transition area	21
10.6 R-Information Zone	22
10.6.1 Sub-divisions of the R-Information Zone.....	22
10.7 Information Zone	22
10.7.1 Sub-divisions of the Information zone	22

10.8	Track geometry	23
10.8.1	Track Path.....	23
10.9	Channel bit length.....	24
10.10	Rim area.....	24
10.11	Remark on tolerances	25
10.12	Label.....	25
11	Mechanical parameters	25
11.1	Mass.....	25
11.2	Moment of inertia.....	25
11.3	Dynamic imbalance	25
11.4	Sense of rotation.....	25
11.5	Runout	25
11.5.1	Axial runout.....	25
11.5.2	Radial runout.....	26
12	Optical parameters	26
12.1	Recorded and unrecorded disk parameters	26
12.1.1	Index of refraction.....	26
12.1.2	Thickness of the transparent substrate	26
12.1.3	Angular deviation.....	27
12.1.4	Birefringence of the transparent substrate.....	27
12.2	Recorded disk reflectivity	27
12.3	Unrecorded disk parameters	28
12.3.1	Polarity of reflectivity modulation.....	28
12.3.2	Recording power sensitivity variation.....	28
13	Operational signals for recorded disk	28
13.1	Measurement conditions	28
13.2	Read conditions	28
13.3	Recorded disk high frequency (HF) signals	28
13.3.1	Modulated amplitude.....	28
13.3.2	Signal asymmetry	29
13.3.3	Cross-track signal.....	29
13.4	Quality of signals	29
13.4.1	Jitter	29
13.4.2	Random errors	29
13.4.3	Defects	30
13.5	Servo signals.....	30
13.5.1	Differential phase tracking error signal.....	30
13.5.2	Tangential push-pull signal	30
13.6	Groove wobble signal	32
14	Operational signals for the unrecorded disk	33
14.1	Measurement conditions	33
14.2	Recording conditions.....	33
14.3	Write strategy for media testing.....	33
14.3.1	Definition of the write pulse.....	34
14.4	Servo signals.....	35
14.4.1	Radial push-pull tracking error signal.....	35
14.4.2	Defects	36
14.5	Addressing signals.....	36
14.5.1	Land Pre-Pit signal	36
14.5.2	Groove wobble signal	38
14.5.3	Relation in phase between wobble and Land Pre-Pit	38
15	Data Format	39
15.1	General.....	39
16	Data Frames	39
16.1	Identification Data (ID).....	40
16.2	ID Error Detection Code	41
16.3	RSV.....	41

16.4	Error Detection Code	41
17	Scrambled Frames	42
18	ECC Block configuration	43
19	Recording Frames	44
20	Modulation.....	45
21	Physical Sectors	46
22	Suppress control of the d.c. component	47
23	Linking scheme	48
23.1	Structure of linking.....	48
23.2	2K-Link and 32K-Link	49
23.3	Lossless-Link.....	49
24	General description of the Information Zone	51
24.1	Layout of the Information Zone	51
24.2	Physical Sector numbering	52
25	Lead-in Zone, Middle Zone and Lead-out Zone.....	53
25.1	Lead-in Zone	53
25.1.1	Initial Zone.....	54
25.1.2	Buffer Zone 0	54
25.1.3	R-Physical Format Information Zone	54
25.1.4	Reference Code Zone.....	58
25.1.5	Buffer Zone 1	58
25.1.6	Control Data Zone	59
25.1.7	Extra Border Zone	72
25.2	Middle Zone.....	72
25.3	Lead-out Zone.....	73
25.3.1	Structure of Lead-out Zone with Format4 RMD.....	73
25.3.2	Superficial Extra Border Zone.....	73
26	General description of the Unrecorded Zone	74
26.1	Layout of the Unrecorded Zone	74
26.2	ECC Block address	75
26.3	ECC Block numbering.....	75
27	Pre-pit Data format	76
27.1	General description.....	76
27.2	Pre-pit block structure	78
27.3	Pre-pit data block configuration	80
27.3.1	Relative address	82
27.3.2	ECC Block address data configuration.....	82
27.3.3	Parity A and Parity B	82
27.3.4	Field ID0.....	84
27.3.5	Field ID1.....	85
27.3.6	Field ID2.....	87
27.3.7	Field ID3 and Field ID4	88
27.3.8	Field ID5.....	90
28	Data structure of R-Information Zone and ODTA.....	90
28.1	Layout of Disk Testing Area and Recording Management Area	90
28.2	Structure of the Disk Testing Area	91
28.3	Data configuration of the Recording Management Area (RMA)	93
28.3.1	Sector format of the Recording Management Area	93
28.3.2	Recording Management Data (Format1 RMD and Format4 RMD).....	95
Annex A (normative) Measurement of the angular deviation α		124
Annex B (normative) Measurement of birefringence		126
Annex C (normative) Measurement of the differential phase tracking error		129

Annex D (normative) Measurement of light reflectance.....	133
Annex E (normative) Tapered cone for disk clamping.....	135
Annex F (normative) Measurement of jitter	136
Annex G (normative) 8-to-16 Modulation with RLL (2,10) requirements	139
Annex H (normative) Optimum Power Control	149
Annex I (normative) Measurement of the groove wobble amplitude	151
Annex J (normative) Measurement methods for the operational signals for an unrecorded disk.....	153
Annex K (normative) NBCA Code.....	154
Annex L (normative) Border Zone	160
Annex M (normative) Measurement method of the Land Pre-Pit signal.....	173
Annex N (normative) Construction of Information Zone.....	174
Annex O (normative) Recording order	176
Annex P (normative) Clearance in the number of sectors	177
Annex Q (normative) Anchor Point Re-mapping	179
Annex R (informative) Measurement method of the Space layer thickness in a disk.....	181
Annex S (informative) Transportation	182

Foreword

ISO (the International Organization for Standardization) and IEC (the International Electrotechnical Commission) form the specialized system for worldwide standardization. National bodies that are members of ISO or IEC participate in the development of International Standards through technical committees established by the respective organization to deal with particular fields of technical activity. ISO and IEC technical committees collaborate in fields of mutual interest. Other international organizations, governmental and non-governmental, in liaison with ISO and IEC, also take part in the work. In the field of information technology, ISO and IEC have established a joint technical committee, ISO/IEC JTC 1.

International Standards are drafted in accordance with the rules given in the ISO/IEC Directives, Part 2.

The main task of the joint technical committee is to prepare International Standards. Draft International Standards adopted by the joint technical committee are circulated to national bodies for voting. Publication as an International Standard requires approval by at least 75 % of the national bodies casting a vote.

Attention is drawn to the possibility that some of the elements of this document may be the subject of patent rights. ISO and IEC shall not be held responsible for identifying any or all such patent rights.

ISO/IEC 12862 was prepared by Ecma International (as ECMA-382) and was adopted, under a special “fast-track procedure”, by Joint Technical Committee ISO/IEC JTC 1, *Information technology*, in parallel with its approval by national bodies of ISO and IEC.

This second edition cancels and replaces the first edition (ISO/IEC 12862:2009), which has been technically revised.

Introduction

Ecma Technical Committee TC31 was established in 1984 for the standardization of optical disks and optical disk cartridges (ODC). Since its establishment, TC31 has made major contributions to ISO/IEC JTC 1/SC 23 toward the development of International Standards for optical disks. Numerous standards have been developed by TC31 and published by Ecma, almost all of which have also been adopted by ISO/IEC under the fast-track procedure as International Standards. The following Ecma standards for DVD 120 mm and 80 mm have been published by Ecma and adopted by ISO/IEC JTC 1. These standards are based on original specifications from the DVD Forum.

ECMA-267 (2001) 120 mm DVD-Read-Only Disk, 3rd edition
ISO/IEC 16448

ECMA-268 (2001) 80 mm DVD-Read-Only Disk, 3rd edition
ISO/IEC 16449

ECMA-272 (1999) 120 mm DVD Rewritable Disk (DVD-RAM), 2nd edition
ISO/IEC 16824

ECMA-273 (1998) Case for 120 mm DVD-RAM Disks, 1st edition
ISO/IEC 16825

ECMA-279 (1998) 80 mm (1,23 Gbytes per side) and 120 mm (3,95 Gbytes per side) DVD-Recordable Disk (DVD-R), 1st edition
ISO/IEC 20563

ECMA-330 (2005) 120 mm (4,7 Gbytes per side) and 80 mm (1,46 Gbytes per side) DVD Rewritable Disk (DVD-RAM), 3rd edition
ISO/IEC 17592

ECMA-331 (2004) Cases for 120 mm and 80 mm DVD-RAM Disks, 2nd edition
ISO/IEC 17594

ECMA-338 (2002) 80 mm (1,46 Gbytes per side) and 120 mm (4,70 Gbytes per side) DVD Re-recordable Disk (DVD-RW), 1st edition
ISO/IEC 17342

ECMA-359 (2004) 80 mm (1,46 Gbytes per side) and 120 mm (4,70 Gbytes per side) DVD Recordable Disk (DVD-R), 1st edition
ISO/IEC 23912

ECMA-382 (2008) 120 mm (8,54 Gbytes per side) and 80 mm (2,66 Gbytes per side) DVD Recordable Disk for Dual Layer (DVD-R for DL), 1st edition
ISO/IEC 12862

ECMA-384 (2008) 120 mm (8,54 Gbytes per side) and 80 mm (2,66 Gbytes per side) DVD Re-recordable Disk for Dual Layer (DVD-RW for DL), 1st edition
ISO/IEC 13170

In April 2007, nine members proposed that TC31 develop a standard for 120 mm and 80 mm dual layer DVD recordable optical disks using organic dye recording technology. TC31 adopted this project, which resulted in ECMA-382 (2008).

In December 2009, a proposal was made that TC31 update this Ecma Standard for editorial corrections and clarifications. TC31 approved this proposal, which resulted in the second edition of ECMA-382.

This International Standard specifies two types of dual layer recordable optical disks, one (Type 1S) making use of recording on only a single side of the disk and yielding a nominal capacity of 8,54 Gbytes for a 120 mm disk and 2,66 Gbytes for an 80 mm disk, the other (Type 2S) making use of recording on both sides of the disk and yielding a nominal capacity of 17,08 Gbytes for a 120 mm disk and 5,32 Gbytes for an 80 mm disk.

Information technology — 120 mm (8,54 Gbytes per side) and 80 mm (2,66 Gbytes per side) DVD recordable disk for dual layer (DVD-R for DL)

1 Scope

This International Standard specifies the mechanical, physical and optical characteristics of a 120 mm and an 80 mm dual layer DVD recordable disk to enable the interchange of such disks. It specifies the quality of the pre-recorded, unrecorded and recorded signals, the format of the data, the format of the information zone, the format of the unrecorded zone, and the recording method, thereby allowing for information interchange by means of such disks. This disk is identified as a DVD recordable disk for dual layer (DVD-R for DL).

This International Standard specifies the following:

- 120 mm and 80 mm nominal diameter disks that can be either single- or double-sided;
- the conditions for conformance;
- the environments in which the disk is to be operated and stored;
- the mechanical and physical characteristics of the disk, so as to provide mechanical interchange between data processing systems;
- the format of the pre-recorded information on an unrecorded disk, including the physical disposition of the tracks and sectors, the error correcting codes and the coding method used;
- the format of the data and the recorded information on the disk, including the physical disposition of the tracks and sectors, the error correcting codes and the coding method used;
- the characteristics of the signals from pre-recorded and unrecorded areas on the disk, enabling data processing systems to read the pre-recorded information and to write to the disks;
- the characteristics of the signals recorded on the disk, enabling data processing systems to read the data from the disk.

This International Standard provides for interchange of disks between disk drives. Together with a standard for volume and file structure, it provides for full data interchange between data processing systems.

2 Conformance

2.1 Optical Disk

A claim of conformance shall specify the type of the disk, i.e. its size and whether it is single-sided or double-sided. An optical disk is in conformance with this International Standard if it meets the mandatory requirements specified for this type.

2.2 Generating system

A generating system is in conformance with this International Standard if the optical disk it generates is in accordance with 2.1.

2.3 Receiving system

A receiving system is in conformance with this International Standard if it is able to handle an optical disk in accordance with 2.1.

3 Normative references

The following referenced documents are indispensable for the application of this document. For dated references, only the edition cited applies. For undated references, the latest edition of the referenced document (including any amendments) applies.

ECMA-287, *Safety of electronic equipment*