

INTERNATIONAL  
STANDARD

ISO/IEC  
15780

First edition  
1998-08-01

---

---

---

**Information technology — 8 mm wide  
magnetic tape cartridge — Helical scan  
recording — AIT-1 format**

*Technologies de l'information — Cartouche de bande magnétique de 8 mm  
de large — Enregistrement par balayage en spirale — Format AIT-1*



Reference number  
ISO/IEC 15780:1998(E)

## Contents

<b>Section 1 - General</b>	<b>1</b>
<b>1 Scope</b>	<b>1</b>
<b>2 Conformance</b>	<b>1</b>
<b>2.1 Magnetic tape cartridge</b>	<b>1</b>
<b>2.2 Generating drive</b>	<b>1</b>
<b>2.3 Receiving drive</b>	<b>1</b>
<b>3 Normative references</b>	<b>2</b>
<b>4 Definitions</b>	<b>2</b>
<b>4.1 Absolute Frame Number (AFN)</b>	<b>2</b>
<b>4.2 a.c. erase</b>	<b>2</b>
<b>4.3 Access</b>	<b>2</b>
<b>4.4 algorithm</b>	<b>2</b>
<b>4.5 Area ID</b>	<b>2</b>
<b>4.6 Automatic Track Finding (ATF)</b>	<b>2</b>
<b>4.7 Average Signal Amplitude</b>	<b>2</b>
<b>4.8 azimuth</b>	<b>2</b>
<b>4.9 back surface</b>	<b>2</b>
<b>4.10 byte</b>	<b>2</b>
<b>4.11 cartridge</b>	<b>2</b>
<b>4.12 Channel bit</b>	<b>2</b>
<b>4.13 Codeword</b>	<b>2</b>
<b>4.14 Early Warning Point (EWP)</b>	<b>2</b>
<b>4.15 End of Data (EOD)</b>	<b>2</b>
<b>4.16 Entity</b>	<b>2</b>
<b>4.17 Error Correcting Code (ECC)</b>	<b>2</b>
<b>4.18 flux transition position</b>	<b>2</b>
<b>4.19 flux transition spacing</b>	<b>2</b>
<b>4.20 Frame</b>	<b>2</b>
<b>4.21 Housekeeping Frame</b>	<b>3</b>
<b>4.22 Logical Beginning of Tape (LBOT)</b>	<b>3</b>
<b>4.23 magnetic tape</b>	<b>3</b>
<b>4.24 Master Standard Amplitude Calibration Tape</b>	<b>3</b>
<b>4.25 Master Standard Reference Tape</b>	<b>3</b>
<b>4.26 Memory In Cartridge (MIC)</b>	<b>3</b>
<b>4.27 Partition Boundary</b>	<b>3</b>
<b>4.28 Physical Beginning of Tape (PBOT)</b>	<b>3</b>
<b>4.29 Physical End of Tape (PEOT)</b>	<b>3</b>
<b>4.30 physical recording density</b>	<b>3</b>

<b>4.31</b> pre-recording condition	<b>3</b>
<b>4.32</b> processing	<b>3</b>
<b>4.33</b> processed data	<b>3</b>
<b>4.34</b> Processed Record	<b>3</b>
<b>4.35</b> record	<b>3</b>
<b>4.36</b> Reference Field	<b>3</b>
<b>4.37</b> reprocessing	<b>3</b>
<b>4.38</b> Secondary Standard Amplitude Calibration Tape	<b>3</b>
<b>4.39</b> Secondary Standard Reference Tape	<b>3</b>
<b>4.40</b> Separator Mark	<b>3</b>
<b>4.41</b> Standard Reference Amplitude (SRA)	<b>3</b>
<b>4.42</b> Tape Reference Edge	<b>4</b>
<b>4.43</b> Typical Field	<b>4</b>
<b>4.44</b> Standard Reference Current	<b>4</b>
<b>4.45</b> Test Recording Current	<b>4</b>
<b>4.46</b> track	<b>4</b>
<b>4.47</b> unprocessed data	<b>4</b>
<b>4.48</b> Unprocessed Record	<b>4</b>
<b>5</b> Conventions and Notations	<b>4</b>
<b>5.1</b> Representation of numbers	<b>4</b>
<b>5.2</b> Names	<b>4</b>
<b>6</b> Acronyms	<b>4</b>
<b>7</b> Environment and safety	<b>5</b>
<b>7.1</b> Test environment	<b>5</b>
<b>7.2</b> Operating environment	<b>5</b>
<b>7.3</b> Storage environment	<b>5</b>
<b>7.4</b> Transportation	<b>5</b>
<b>7.5</b> Safety	<b>5</b>
<b>7.6</b> Flammability	<b>5</b>
<b>8</b> Dimensional and mechanical characteristics of the case	<b>6</b>
<b>8.1</b> General	<b>6</b>
<b>8.2</b> Overall dimension	<b>6</b>
<b>8.3</b> Holding areas	<b>7</b>
<b>8.4</b> Cartridge insertion	<b>7</b>
<b>8.5</b> Window	<b>8</b>
<b>8.6</b> Loading grips	<b>8</b>
<b>8.7</b> Label areas	<b>8</b>
<b>8.8</b> Datum areas and Datum holes	<b>8</b>
<b>8.9</b> Support areas	<b>9</b>
<b>8.10</b> Recognition holes	<b>10</b>
<b>8.11</b> Write-inhibit hole	<b>10</b>
<b>8.12</b> Pre-positioning surfaces	<b>11</b>
<b>8.13</b> Cartridge lid	<b>11</b>
<b>8.14</b> Cartridge reel lock	<b>12</b>
<b>8.15</b> Reel access holes	<b>13</b>
<b>8.16</b> Interface between the reels and the drive spindles	<b>13</b>
<b>8.17</b> Light path	<b>14</b>
<b>8.18</b> Position of the tape in the case	<b>15</b>
<b>8.19</b> Tape path zone	<b>15</b>
<b>8.20</b> Tape access cavity	<b>15</b>
<b>8.21</b> Tape access cavity clearance requirements	<b>16</b>
<b>8.22</b> Requirements for the MIC	<b>16</b>
<b>8.22.1</b> Access holes	<b>16</b>

<b>8.22.2</b> Recognition recesses	<b>17</b>
<b>Section 3 - Requirements for the unrecorded tape</b>	<b>37</b>
<b>9</b> Mechanical, physical and dimensional characteristics of the tape	<b>37</b>
<b>9.1</b> Materials	<b>37</b>
<b>9.2</b> Tape length	<b>37</b>
<b>9.2.1</b> Length of magnetic tape	<b>37</b>
<b>9.2.2</b> Length of leader and trailer tapes	<b>37</b>
<b>9.2.3</b> Length of the splicing tapes	<b>37</b>
<b>9.3</b> Tape width	<b>37</b>
<b>9.3.1</b> Width of magnetic, leader and trailer tapes	<b>37</b>
<b>9.3.2</b> Width and position of the splicing tape	<b>37</b>
<b>9.4</b> Discontinuities	<b>37</b>
<b>9.5</b> Tape thickness	<b>38</b>
<b>9.5.1</b> Thickness of the magnetic tape	<b>38</b>
<b>9.5.2</b> Thickness of leader and trailer tape	<b>38</b>
<b>9.5.3</b> Thickness of splicing tape	<b>38</b>
<b>9.6</b> Longitudinal curvature	<b>38</b>
<b>9.7</b> Cupping	<b>38</b>
<b>9.8</b> Coating adhesion	<b>38</b>
<b>9.9</b> Layer-to-layer adhesion	<b>39</b>
<b>9.10</b> Tensile strength	<b>39</b>
<b>9.10.1</b> Breaking strength	<b>39</b>
<b>9.10.2</b> Yield strength	<b>39</b>
<b>9.11</b> Residual elongation	<b>39</b>
<b>9.12</b> Electrical resistance of the recording surface	<b>40</b>
<b>9.13</b> Tape winding	<b>40</b>
<b>9.14</b> Light transmittance of the tape	<b>40</b>
<b>10</b> Magnetic recording characteristics	<b>40</b>
<b>10.1</b> Typical Field	<b>41</b>
<b>10.2</b> Signal Amplitude	<b>41</b>
<b>10.3</b> Resolution	<b>41</b>
<b>10.4</b> Overwrite	<b>41</b>
<b>10.5</b> Ease of erasure	<b>42</b>
<b>10.6</b> Tape quality	<b>42</b>
<b>10.6.1</b> Missing pulses	<b>42</b>
<b>10.6.2</b> Missing pulse zone	<b>42</b>
<b>10.7</b> Signal-to-Noise Ratio (SNR) characteristic	<b>42</b>
<b>Section 4 - Requirements for an interchanged tape</b>	<b>42</b>
<b>11</b> Format	<b>42</b>
<b>11.1</b> General	<b>42</b>
<b>11.2</b> Basic Groups	<b>43</b>
<b>11.2.1</b> Entity	<b>43</b>
<b>11.2.2</b> Group Information Table	<b>44</b>
<b>11.2.3</b> Block Access Table (BAT)	<b>46</b>
<b>11.3</b> Sub-Groups	<b>49</b>
<b>11.3.1</b> G1 Sub-Group	<b>49</b>
<b>11.3.2</b> G2 Sub-Group - Randomizing	<b>50</b>
<b>11.3.3</b> G3 Sub-Group	<b>51</b>
<b>11.4</b> Data Block	<b>52</b>
<b>11.4.1</b> ID information	<b>53</b>
<b>11.4.2</b> Recording of the ID Information in the Data Block Headers	<b>55</b>
<b>12</b> Method of recording	<b>58</b>
<b>12.1</b> Physical recording density	<b>58</b>

<b>12.2</b> Long-term average bit cell length	<b>58</b>
<b>12.3</b> Short-term average bit cell length	<b>58</b>
<b>12.4</b> Rate of change	<b>58</b>
<b>12.5</b> Bit shift	<b>58</b>
<b>12.6</b> Read signal amplitude	<b>58</b>
<b>12.7</b> Maximum recorded levels	<b>58</b>
<b>13</b> Track geometry	<b>59</b>
<b>13.1</b> Track configuration	<b>59</b>
<b>13.2</b> Average track pitch	<b>59</b>
<b>13.3</b> Variations of the track pitch	<b>59</b>
<b>13.4</b> Track width	<b>59</b>
<b>13.5</b> Track angle	<b>60</b>
<b>13.6</b> Track edge straightness	<b>60</b>
<b>13.7</b> Track length	<b>60</b>
<b>13.8</b> Azimuth angles	<b>60</b>
<b>14</b> Recorded patterns	<b>60</b>
<b>14.1</b> Recorded Data Block	<b>60</b>
<b>14.2</b> Margin blocks	<b>60</b>
<b>15</b> Format of a track	<b>60</b>
<b>15.1</b> Track capacity	<b>60</b>
<b>15.2</b> Positioning accuracy	<b>61</b>
<b>15.3</b> Tracking scheme	<b>62</b>
<b>16</b> Layout of a Single Data Space tape	<b>62</b>
<b>16.1</b> Device Area	<b>63</b>
<b>16.2</b> Reference Area	<b>63</b>
<b>16.3</b> Position Tolerance Band No. 1	<b>63</b>
<b>16.4</b> System Area	<b>63</b>
<b>16.4.1</b> System Preamble	<b>64</b>
<b>16.4.2</b> System Log	<b>64</b>
<b>16.4.3</b> System Postamble	<b>67</b>
<b>16.4.4</b> Position Tolerance Band No. 2	<b>67</b>
<b>16.4.5</b> Vendor Group Preamble	<b>67</b>
<b>16.5</b> Data Area	<b>67</b>
<b>16.5.1</b> Vendor Group	<b>67</b>
<b>16.5.2</b> Recorded Data Group	<b>67</b>
<b>16.5.3</b> ECC3	<b>67</b>
<b>16.5.4</b> Multiple Recorded Instances	<b>68</b>
<b>16.5.5</b> Repeated Frames	<b>68</b>
<b>16.5.6</b> Appending and overwriting	<b>69</b>
<b>16.6</b> EOD Area	<b>70</b>
<b>16.7</b> Optional Device Area	<b>70</b>
<b>16.8</b> Early Warning Point - EWP	<b>71</b>
<b>16.9</b> Initialization	<b>71</b>
<b>17</b> Layout of partitioned tape	<b>72</b>
<b>17.1</b> Overall magnetic tape layout	<b>72</b>
<b>17.1.1</b> Partition	<b>72</b>
<b>17.2</b> LBOT	<b>73</b>
<b>17.3</b> Empty Partition	<b>73</b>
<b>17.4</b> Initialization of partitioned tapes	<b>73</b>
<b>18</b> Housekeeping Frames	<b>73</b>
<b>18.1</b> Amble Frames	<b>73</b>
<b>18.2</b> System Amble Frames	<b>74</b>

**Annexes**

<b>A</b> - Measurement of light transmittance	<b>75</b>
<b>B</b> - Measurement of Signal-to-Noise Ratio	<b>78</b>
<b>C</b> - Method for determining the nominal and the maximum allowable recorded levels	<b>79</b>
<b>D</b> - Representation of 8-bit bytes by 10-bit patterns	<b>80</b>
<b>E</b> - Measurement of bit shift	<b>92</b>
<b>F</b> - Method of measuring the straightness of track edges	<b>94</b>
<b>G</b> - ECC calculation	<b>95</b>
<b>H</b> - Recommendations for transportation	<b>98</b>
<b>J</b> - Read-After-Write	<b>99</b>
<b>K</b> - Example of the content of a Basic Group No. 0	<b>100</b>

## Foreword

ISO (the International Organization for Standardization) and IEC (the International Electrotechnical Commission) form the specialized system for worldwide standardization. National bodies that are members of ISO or IEC participate in the development of International Standards through technical committees established by the respective organization to deal with particular fields of technical activity. ISO and IEC technical committees collaborate in fields of mutual interest. Other international organizations, governmental and non-governmental, in liaison with ISO and IEC, also take part in the work.

In the field of information technology, ISO and IEC have established a joint technical committee, ISO/IEC JTC 1. Draft International Standards adopted by the joint technical committee are circulated to national bodies for voting. Publication as an International Standard requires approval by at least 75 % of the national bodies casting a vote.

This International Standard was prepared by ECMA (as ECMA-246) and was adopted, under a special “fast-track procedure”, by Joint Technical Committee ISO/IEC JTC 1, *Information technology*, in parallel with its approval of national bodies of ISO and IEC.

Annexes A to G form an integral part of this International Standard. Annexes H to K are for information only.

# Information technology — 8 mm wide magnetic tape cartridge — Helical scan recording — AIT-1 format

## Section 1 - General

### 1 Scope

This International Standard specifies the physical and magnetic characteristics of an 8 mm wide magnetic tape cartridge to enable physical interchange of such cartridges between drives. It also specifies the quality of the recorded signals, the recording method and the recorded format - called Advanced Intelligent Tape No. 1 (AIT-1) - thereby allowing data interchange between drives by means of such magnetic tape cartridges.

Information interchange between systems also requires, at a minimum, agreement between the interchange parties upon the interchange code(s) and the specifications of the structure and labelling of the information on the interchanged cartridge.

### 2 Conformance

#### 2.1 Magnetic tape cartridge

A tape cartridge shall be in conformance with this International Standard if it meets all the mandatory requirements specified herein. The tape requirements shall be satisfied throughout the extent of the tape.

#### 2.2 Generating drive

A drive generating a magnetic tape cartridge for interchange shall be in conformance with this International Standard if all recordings on the tape meet the mandatory requirements of this International Standard, and if either or both methods of appending and overwriting are implemented.

A claim of conformance shall state which of the following optional features are implemented and which are not

- the performing of a Read-After-Write check and the recording of any necessary repeated frames;
- the generation of ECC3 Frames.

In addition a claim of conformance shall state

- whether or not one, or more, registered algorithm(s) are implemented within the system and are able to compress data received from the host prior to collecting the data into Basic Groups, and
- the registered identification number(s) of the implemented compression algorithm(s).

#### 2.3 Receiving drive

A drive receiving a magnetic tape cartridge for interchange shall be in conformance with this International Standard if it is able to handle any recording made on the tape according to this International Standard. In particular it shall

- be able to recognise repeated frames, and to make available to the host, data and Separator Marks from only one of these frames;
- be able to recognise multiple representations of the same Basic Group, and to make available to the host, data and Separator Marks from only one of these representations;
- be able to recognise an ECC3 frame, and ignore it if the system is not capable of using ECC3 check bytes in a process of error correction;
- be able to recognise processed data within an Entity, identify the algorithm used, and make its registered identification number available to the host;
- be able to make processed data available to the host.

In addition a claim of conformance shall state

- whether or not the system is capable of using ECC3 check bytes in a process of error correction;

- whether or not one or more de-compression algorithm(s) are implemented within the system, and are able to be applied to compressed data prior to making such data available to the host;
- the registered identification number(s) of the compression algorithm(s) for which a complementary de-compression algorithm is implemented.

### 3 Normative references

The following standards contain provisions which, through reference in this text, constitute provisions of this International Standard. At the time of publication, the editions indicated were valid. All standards are subject to revision, and parties to agreements based on this International Standard are encouraged to investigate the possibility of applying the most recent editions of the standards indicated below. Members of IEC and ISO maintain registers of currently valid International Standards.

ISO/R 527 (all parts), *Plastics - Determination of tensile properties.*

ISO 1302:1992, *Technical drawings - Method of indicating surface texture.*

ISO/IEC 11576:1994, *Information technology - Procedure for the registration of algorithms for the lossless compression of data.*