

INTERNATIONAL
STANDARD

ISO/IEC
20061

First edition
2001-12-01

**Information technology — 12,65 mm wide
magnetic tape cassette for information
interchange — Helical scan recording —
DTF-2**

*Technologies de l'information — Cassette de bande magnétique de
12,65 mm de large pour l'échange d'information — Enregistrement par
balayage en spirale — DTF-2*



Reference number
ISO/IEC 20061:2001(E)

© ISO/IEC 2001

PDF disclaimer

This PDF file may contain embedded typefaces. In accordance with Adobe's licensing policy, this file may be printed or viewed but shall not be edited unless the typefaces which are embedded are licensed to and installed on the computer performing the editing. In downloading this file, parties accept therein the responsibility of not infringing Adobe's licensing policy. The ISO Central Secretariat accepts no liability in this area.

Adobe is a trademark of Adobe Systems Incorporated.

Details of the software products used to create this PDF file can be found in the General Info relative to the file; the PDF-creation parameters were optimized for printing. Every care has been taken to ensure that the file is suitable for use by ISO member bodies. In the unlikely event that a problem relating to it is found, please inform the Central Secretariat at the address given below.

© ISO/IEC 2001

All rights reserved. Unless otherwise specified, no part of this publication may be reproduced or utilized in any form or by any means, electronic or mechanical, including photocopying and microfilm, without permission in writing from either ISO at the address below or ISO's member body in the country of the requester.

ISO copyright office
Case postale 56 • CH-1211 Geneva 20
Tel. + 41 22 749 01 11
Fax + 41 22 749 09 47
E-mail copyright@iso.ch
Web www.iso.ch

Printed in Switzerland

Contents

	Page
Section 1 - General	1
1 Scope	1
2 Conformance	1
2.1 Magnetic tape cassette	1
2.2 Generating system	1
2.3 Receiving system	1
3 Normative references	1
4 Terms and definitions	2
4.1 Absolute block number	2
4.2 a.c. erase	2
4.3 algorithm	2
4.4 Append file	2
4.5 Append volume	2
4.6 Average Signal Amplitude (ASA)	2
4.7 azimuth	2
4.8 back surface	2
4.9 bit cell	2
4.10 block	2
4.11 Block Management Table (BMT)	2
4.12 byte	2
4.13 cassette	2
4.14 compressed data	2
4.15 Control Track	2
4.16 flux transition position	2
4.17 flux transition spacing	2
4.18 Logical track set ID	2
4.19 Logical volume	2
4.20 magnetic tape	2
4.21 Master Standard Reference Tape (MSRT)	2
4.22 physical recording density	2
4.23 Reference Field (RF)	2
4.24 Secondary Standard Reference Tape (SSRT)	2
4.25 Standard Reference Amplitude (SRA)	3
4.26 Standard Reference Current (Ir)	3
4.27 Tape Reference Edge	3
4.28 Test Recording Current (TRC)	3
4.29 track	3
4.30 track angle	3
4.31 Track Set	3
4.32 Typical Field (TF)	3
4.33 word	3
5 Conventions and notations	3
5.1 Representation of numbers	3
5.2 Names	3
6 Acronyms	4
7 Environment and safety	4

7.1	Testing environment	4
7.2	Operating environment	4
7.3	Storage environment	5
7.4	Transportation	5
7.5	Safety	5
7.6	Flammability	5
Section 2 - Requirements for the case		5
8	Dimensional and mechanical characteristics of the case	5
8.1	General	5
8.2	Type S cassette	5
8.2.1	Overall dimensions (Figure 3)	6
8.2.2	Holding areas (Figure 4)	6
8.2.3	Window	6
8.2.4	Label areas (Figure 4)	7
8.2.5	Datum areas and datum holes (Figures 5 and 6)	7
8.2.6	Support areas (Figure 5)	7
8.2.7	Guiding grooves (Figures 3 and 6)	8
8.2.8	Recognition holes (Figures 6 and 7)	9
8.2.9	Write-inhibit plug (Figure 8)	10
8.2.10	Pre-positioning surface (Figures 3 and 5)	11
8.2.11	Cassette lid (Figures 9, 10, 11, 12 and 13)	11
8.2.12	Cassette reel lock (Figure 13)	12
8.2.13	Reel access holes (Figure 6)	13
8.2.14	Reels (Figure 14)	13
8.2.15	Position of the tape in the case (Figure 16)	14
8.2.16	Tape path zone (Figures 16 to 18)	14
8.2.17	Tape access cavity (Figure 19)	15
8.3	Type L cassette	30
8.3.1	Overall dimensions (Figure 22)	30
8.3.2	Holding areas (Figure 23)	30
8.3.3	Window	31
8.3.4	Label areas (Figure 23)	31
8.3.5	Datum areas and datum holes (Figures 24 and 25)	31
8.3.6	Support areas (Figure 24)	32
8.3.7	Guiding grooves (Figure 25)	32
8.3.8	Recognition holes (Figure 26)	33
8.3.9	Write-inhibit plug (Figure 27)	34
8.3.10	Pre-positioning surface (Figures 24 and 25)	35
8.3.11	Cassette lid (Figures 28, 29, 30, 31 and 32)	35
8.3.12	Cassette reel lock (Figure 32)	36
8.3.13	Reel access holes (Figure 25)	36
8.3.14	Reels (Figure 33)	37
8.3.15	Position of the tape in the case (Figure 35)	38
8.3.16	Tape path zone (Figures 35 to 37)	38
8.3.17	Tape access cavity (Figure 38)	39
8.3.18	Cavity for compatibility with Type S cassette (Figure 39)	40
Section 3 - Requirements for the unrecorded tape		55
9	Mechanical, physical and dimensional characteristics of the tape	55
9.1	Materials	55
9.2	Tape length	55
9.3	Tape width	55
9.4	Width and position of splicing tape	55
9.5	Discontinuity	55
9.6	Tape thickness	55
9.7	Longitudinal curvature	55
9.8	Out-of-plane distortions	56

9.9	Coating adhesion	56
9.10	Layer-to-layer adhesion	57
9.11	Tensile strength	57
9.11.1	Breaking strength	57
9.11.2	Yield strength	57
9.11.3	Strength of splice	57
9.12	Residual elongation	57
9.13	Electrical resistance of the coated surfaces	57
9.14	Tape wind	58
10	Magnetic recording characteristics	58
10.1	Typical Field (TF1)	58
10.2	Average Signal Amplitude(ASA)	59
10.3	Resolution	59
10.4	Signal-to-noise ratio (S/N)	59
10.5	Ease of erasure	59
10.6	Tape quality	59
10.6.1	Missing pulses	59
10.6.2	Missing pulse zone	59
10.7	Inhibitor tape	59
11	Format for helical tracks	60
11.1	General description of the write data path (see Figure 42)	60
11.2	Formation of a Logical Track Set	60
11.2.1	Types of information track sets	60
11.2.2	Generation of a Logical Track Set	62
11.2.3	Subcode data field	62
11.2.4	Block Management Table (BMT)	66
11.2.5	Data and information field definitions	66
11.3	Track Set information	70
11.3.1	Loading the Product Code Arrays	70
11.4	Product code array processing	72
11.4.1	Error correction method	72
11.4.2	Error correction coding for C1 Parity	72
11.5	Track assignments	73
11.5.1	Segments/Sectors (Figure 46)	73
11.5.2	Sync Blocks (Figure 47)	74
11.5.3	Track interleave (Figure 48)	74
11.5.4	Byte interleave across Sync Blocks (Figure 49)	77
11.5.5	Randomization	77
11.6	Formation of the contents of a helical track (Figure 50)	78
11.6.1	Segment/Sector details (Figure 47)	78
11.6.2	Channel bit coding	79
11.6.3	Interleaved-NRZ1 (Figure 51)	79
11.6.4	Tracking Pilot Signals (TPS)	79
12	Track geometry	79
12.1	General	79
12.2	Helically recorded tracks	80
12.2.1	Location of the tracks	80
12.2.2	Track width	81
12.2.3	Track angle	81
12.2.4	Track pitch	81
12.2.5	Location of elements in the helical track	82

12.2.6	Location of the Data Area Reference Point	82
12.2.7	Straightness of tracks	82
12.2.8	Azimuth angles	82
12.2.9	Tracking Pilot Signals (TPS)	82
12.2.10	Amplitude of servo signals	82
12.3	Longitudinal tracks geometry	82
12.3.1	Control Track	82
12.3.2	Time Code Track signals recording position	83
13	Method of recording helical tracks	83
13.1	Physical recording density	83
13.2	Record current optimization	83
13.3	Efficiency of erasure	83
14	Method of recording longitudinal tracks	83
14.1	Overview	83
14.2	Control Track	83
14.2.1	Signal	83
14.2.2	Polarity of magnetisation (Figure 54)	83
14.2.3	Alignment	83
14.2.4	Read signal amplitude	84
14.2.5	Quality of the Control Track	84
14.3	Time Code Track	84
14.3.1	Method of recording the Time Code Track	84
14.3.2	Physical recording density	84
14.3.3	Bit shift	84
14.3.4	Read signal amplitude	84
14.3.5	Quality of the Time Code Track	85
14.4	Format for the Time Code Track	85
14.4.1	Count bits	85
14.4.2	Phase bit	85
14.4.3	Synchronizing pattern	85
14.4.4	Supplemental Data	85
14.4.5	Extent of Time Code	85
Section 5 - Requirements for recorded information		85
15	Recorded information	85
15.1	Recording area (Figure 55)	85
15.2	Magnetic tape layout (Figure 56)	85
15.2.1	Valid data areas	85
15.2.2	Invalid data areas	86
15.3	Physical TSID	86
15.3.1	Structure surrounding the VSIT area	88
15.3.2	Structure of the DIT area	88
15.3.3	Structure of the User Data Area	89
Section 6 - Write operations		89
16	Write retry sequence (Figure 58)	89
17	Append file operation (Figure 59)	90
17.1	Append volume	90
17.2	Append write (Figure 60)	90
17.3	Overwrite (Figure 61)	91

17.4	File extension (Figure 62)	92
Annexes		
A	- Measurement of Signal-to-Noise Ratio	94
B	- Representation 8/9 coding patterns	95
C	- Recommendations for transportation	99
D	- Inhibitor tape	100

Foreword

ISO (the International Organization for Standardization) and IEC (the International Electrotechnical Commission) form the specialized system for worldwide standardization. National bodies that are members of ISO or IEC participate in the development of International Standards through technical committees established by the respective organization to deal with particular fields of technical activity. ISO and IEC technical committees collaborate in fields of mutual interest. Other international organizations, governmental and non-governmental, in liaison with ISO and IEC, also take part in the work. In the field of information technology, ISO and IEC have established a joint technical committee, ISO/IEC JTC 1.

International Standards are drafted in accordance with the rules given in the ISO/IEC Directives, Part 3.

The main task of the joint technical committee is to prepare International Standards. Draft International Standards adopted by the joint technical committee are circulated to national bodies for voting. Publication as an International Standard requires approval by at least 75 % of the national bodies casting a vote.

Attention is drawn to the possibility that some of the elements of this International Standard may be the subject of patent rights. ISO and IEC shall not be held responsible for identifying any or all such patent rights.

ISO/IEC 20061 was prepared by ECMA (as Standard ECMA-315) and was adopted, under a special “fast-track procedure”, by Joint Technical Committee ISO/IEC JTC 1, *Information technology*, in parallel with its approval of national bodies of ISO and IEC.

Annexes A and B form a normative part of this International Standard. Annexes C and D are for information only.

Information technology — 12,65 mm wide magnetic tape cassette for information interchange — Helical scan recording — DTF-2

Section 1 - General

1 Scope

This International Standard specifies the physical and magnetic characteristics of magnetic tape cassettes, using magnetic tape 12,65 mm wide so as to provide physical interchange of such cassettes between drives. It also specifies the quality of the recorded signals, the recording method and the recorded format, called Digital Tape Format-2 (DTF-2), thereby allowing data interchange between drives by means of such cassettes. The format supports variable length Logical Records, high-speed search, and the use of a registered algorithm for data compression.

This International Standard specifies two sizes of cassette. For the purposes of this International Standard the larger cassette is referred to as Type L, and the smaller as Type S.

Together with a standard for volume and file structure, e.g. International Standard ISO 1001, this International Standard provides for full data interchange between data processing systems.

2 Conformance

2.1 Magnetic tape cassette

A claim of conformance with this International Standard shall specify the Type of cassette. It shall be in conformance with this International Standard if:

- the case and unrecorded tape meet all the requirements of clause 8 to 10 for that Type
- the recording on the tape meets the requirements of clauses 11 to 17

2.2 Generating system

A claim of conformance with this International Standard shall specify which Type(s) of cassette is (are) supported. A system generating a magnetic tape cassette for interchange shall be in conformance with this International Standard if all the recordings that it makes, meet the mandatory requirements of this International Standard. A claim of conformance with this International Standard shall state whether or not one, or more, registered algorithm(s) is (are) implemented and, if so, the registered number(s) of (all) the implemented algorithm(s).

2.3 Receiving system

A claim of conformance with this International Standard shall specify which Type(s) of cassette is (are) supported. A system receiving a magnetic tape cassette for interchange shall be in conformance with this International Standard if it is able to handle any recording made on the tape according to this International Standard, and a claim of conformance shall state whether or not one, or more, registered algorithm(s) is (are) implemented and, if so, the registered number(s) of (all) the implemented algorithm(s).

3 Normative references

The following normative documents contain provisions which, through reference in this text, constitute provisions of this International Standard. For dated references, subsequent amendments to, or revisions of, any of these publications do not apply. However, parties to agreements based on this International Standard are encouraged to investigate the possibility of applying the most recent editions of the normative documents indicated below. For undated references, the latest edition of the normative document referred to applies. Members of ISO and IEC maintain registers of currently valid International Standards.

ISO 527-3:1995, *Plastics — Determination of tensile properties — Part 3: Test conditions for films and sheets*

ISO 1001:1986, *Information processing — File structure and labelling of magnetic tapes for information interchange*

ISO/IEC 11576:1994, *Information technology — Procedure for the registration of algorithms for the lossless compression of data*

SMPTE timecode: C98.12 : time and control code for video and audio tape for 525/60 television system

JIS-B-7502 Characteristics of plastic goods