



ISO/IEC 29341-10-1

Edition 1.0 2008-11

INTERNATIONAL STANDARD

**Information technology – UPnP Device Architecture –
Part 10-1: Quality of Service Device Control Protocol – Quality of Service
Architecture**

INTERNATIONAL
ELECTROTECHNICAL
COMMISSION

PRICE CODE

L

ICS 35.200

ISBN 978-2-88910-898-5

CONTENTS

FOREWORD	4
ORIGINAL UPNP DOCUMENTS (informative)	6
1. Glossary.....	8
2. Introduction.....	11
2.1. Referenced Specifications	11
3. Architecture Overview.....	12
3.1. Motivation	13
3.1.1. Policy Management.....	13
3.2. Key Concepts	13
3.2.1. Admission Control.....	13
3.2.2. Admission Policy.....	14
3.2.3. Traffic Descriptor	14
4. UPnP QoS Components.....	15
4.1. QosPolicyHolder Service.....	15
4.1.1. Role.....	15
4.1.2. Traffic Stream QoS Policy Description	15
4.2. QoS Manager	16
4.2.1. Role.....	16
4.2.2. Behavior.....	16
4.2.3. Dealing with Policy	16
4.2.4. QoS Update	17
4.3. QosDevice Service.....	17
4.3.1. Role.....	17
4.3.2. Behavior.....	17
4.3.3. Setup Traffic QoS	17
4.3.4. Traffic Admission Control.....	17
4.3.5. Path Information.....	18
5. System Operation	19
5.1. Initiation of QoS Setup	19
5.1.1. Generic Control Point.....	19
5.1.2. Independent AV Control Point.....	20
5.1.3. Determination of TrafficId	20
5.1.4. Creation of Optional Traffic Specification (Tspec)	21
5.2. Determination of Policy for the Traffic Stream	21
5.2.1. QosPolicyHolder Service	21
5.2.2. Default Policy	21
5.3. Determination of QosDevice Services that should be configured	22
5.3.1. Path Determination (Optional)	22
5.3.2. Setup Capabilities Determination.....	22
5.4. Configuration of QoS Devices	22
5.4.1. Priority Setup Strategy	23
5.4.2. Admission Control Strategy	23
5.5. Run time Operation	23
5.5.1. Lease Management	23
5.5.2. Traffic revocation	23
5.5.3. Violation of TSPEC	23
5.5.4. The Use of Traffic Descriptor.....	23
5.6. Relationship to other UPnP Services and non UPnP Traffic Streams	23

5.6.1. UPnP IGD	23
5.6.2. Legacy Devices.....	24
6. Prioritized QoS.....	25
6.1. Management of Packet Priorities	25
7. Parameterized QoS.....	27
Annex A (normative) Layer 2 Implementation Guidelines	28
A.1 802.1p and 802.1d, Annex G	28
A.2 HomePlug	28
A.3 HPNA 2.0	29

INFORMATION TECHNOLOGY – UPNP DEVICE ARCHITECTURE –

Part 10-1: Quality of Service Device Control Protocol Quality of Service Architecture

FOREWORD

- 1) ISO (International Organization for Standardization) and IEC (International Electrotechnical Commission) form the specialized system for worldwide standardization. National bodies that are members of ISO or IEC participate in the development of International Standards. Their preparation is entrusted to technical committees; any ISO and IEC member body interested in the subject dealt with may participate in this preparatory work. International governmental and non-governmental organizations liaising with ISO and IEC also participate in this preparation.
- 2) In the field of information technology, ISO and IEC have established a joint technical committee, ISO/IEC JTC 1. Draft International Standards adopted by the joint technical committee are circulated to national bodies for voting. Publication as an International Standard requires approval by at least 75 % of the national bodies casting a vote.
- 3) The formal decisions or agreements of IEC and ISO on technical matters express, as nearly as possible, an international consensus of opinion on the relevant subjects since each technical committee has representation from all interested IEC and ISO member bodies.
- 4) IEC, ISO and ISO/IEC publications have the form of recommendations for international use and are accepted by IEC and ISO member bodies in that sense. While all reasonable efforts are made to ensure that the technical content of IEC, ISO and ISO/IEC publications is accurate, IEC or ISO cannot be held responsible for the way in which they are used or for any misinterpretation by any end user.
- 5) In order to promote international uniformity, IEC and ISO member bodies undertake to apply IEC, ISO and ISO/IEC publications transparently to the maximum extent possible in their national and regional publications. Any divergence between any ISO/IEC publication and the corresponding national or regional publication should be clearly indicated in the latter.
- 6) ISO and IEC provide no marking procedure to indicate their approval and cannot be rendered responsible for any equipment declared to be in conformity with an ISO/IEC publication.
- 7) All users should ensure that they have the latest edition of this publication.
- 8) No liability shall attach to IEC or ISO or its directors, employees, servants or agents including individual experts and members of their technical committees and IEC or ISO member bodies for any personal injury, property damage or other damage of any nature whatsoever, whether direct or indirect, or for costs (including legal fees) and expenses arising out of the publication of, use of, or reliance upon, this ISO/IEC publication or any other IEC, ISO or ISO/IEC publications.
- 9) Attention is drawn to the normative references cited in this publication. Use of the referenced publications is indispensable for the correct application of this publication.

IEC and ISO draw attention to the fact that it is claimed that compliance with this document may involve the use of patents as indicated below.

ISO and IEC take no position concerning the evidence, validity and scope of the putative patent rights. The holders of the putative patent rights have assured IEC and ISO that they are willing to negotiate free licences or licences under reasonable and non-discriminatory terms and conditions with applicants throughout the world. In this respect, the statements of the holders of the putative patent rights are registered with IEC and ISO.

Intel Corporation has informed IEC and ISO that it has patent applications or granted patents.

Information may be obtained from:

Intel Corporation
Standards Licensing Department
5200 NE Elam Young Parkway
MS: JFS-98
USA – Hillsboro, Oregon 97124

Microsoft Corporation has informed IEC and ISO that it has patent applications or granted patents as listed below:

6101499 / US; 6687755 / US; 6910068 / US; 7130895 / US; 6725281 / US; 7089307 / US; 7069312 / US;
10/783 524 /US

Information may be obtained from:

Microsoft Corporation
One Microsoft Way
USA – Redmond WA 98052

Philips International B.V. has informed IEC and ISO that it has patent applications or granted patents.

Information may be obtained from:

Philips International B.V. – IP&S
High Tech campus, building 44 3A21
NL – 5656 Eindhoven

NXP B.V. (NL) has informed IEC and ISO that it has patent applications or granted patents.

Information may be obtained from:

NXP B.V. (NL)
High Tech campus 60
NL – 5656 AG Eindhoven

Matsushita Electric Industrial Co. Ltd. has informed IEC and ISO that it has patent applications or granted patents.

Information may be obtained from:

Matsushita Electric Industrial Co. Ltd.
1-3-7 Shiromi, Chuoh-ku
JP – Osaka 540-6139

Hewlett Packard Company has informed IEC and ISO that it has patent applications or granted patents as listed below:

5 956 487 / US; 6 170 007 / US; 6 139 177 / US; 6 529 936 / US; 6 470 339 / US; 6 571 388 / US; 6 205
466 / US

Information may be obtained from:

Hewlett Packard Company
1501 Page Mill Road
USA – Palo Alto, CA 94304

Samsung Electronics Co. Ltd. has informed IEC and ISO that it has patent applications or granted patents.

Information may be obtained from:

Digital Media Business, Samsung Electronics Co. Ltd.
416 Maetan-3 Dong, Yeongtang-Gu,
KR – Suwon City 443-742

Attention is drawn to the possibility that some of the elements of this document may be the subject of patent rights other than those identified above. IEC and ISO shall not be held responsible for identifying any or all such patent rights.

ISO/IEC 29341-10-1 was prepared by UPnP Implementers Corporation and adopted, under the PAS procedure, by joint technical committee ISO/IEC JTC 1, *Information technology*, in parallel with its approval by national bodies of ISO and IEC.

The list of all currently available parts of the ISO/IEC 29341 series, under the general title *Universal plug and play (UPnP) architecture*, can be found on the IEC web site.

This International Standard has been approved by vote of the member bodies, and the voting results may be obtained from the address given on the second title page.

ORIGINAL UPNP DOCUMENTS (informative)

Reference may be made in this document to original UPnP documents. These references are retained in order to maintain consistency between the specifications as published by ISO/IEC and by UPnP Implementers Corporation. The following table indicates the original UPnP document titles and the corresponding part of ISO/IEC 29341:

UPnP Document Title	ISO/IEC 29341 Part
UPnP Device Architecture 1.0	ISO/IEC 29341-1
UPnP Basic:1 Device	ISO/IEC 29341-2
UPnP AV Architecture:1	ISO/IEC 29341-3-1
UPnP MediaRenderer:1 Device	ISO/IEC 29341-3-2
UPnP MediaServer:1 Device	ISO/IEC 29341-3-3
UPnP AVTransport:1 Service	ISO/IEC 29341-3-10
UPnP ConnectionManager:1 Service	ISO/IEC 29341-3-11
UPnP ContentDirectory:1 Service	ISO/IEC 29341-3-12
UPnP RenderingControl:1 Service	ISO/IEC 29341-3-13
UPnP MediaRenderer:2 Device	ISO/IEC 29341-4-2
UPnP MediaServer:2 Device	ISO/IEC 29341-4-3
UPnP AV Datastructure Template:1	ISO/IEC 29341-4-4
UPnP AVTransport:2 Service	ISO/IEC 29341-4-10
UPnP ConnectionManager:2 Service	ISO/IEC 29341-4-11
UPnP ContentDirectory:2 Service	ISO/IEC 29341-4-12
UPnP RenderingControl:2 Service	ISO/IEC 29341-4-13
UPnP ScheduledRecording:1	ISO/IEC 29341-4-14
UPnP DigitalSecurityCamera:1 Device	ISO/IEC 29341-5-1
UPnP DigitalSecurityCameraMotionImage:1 Service	ISO/IEC 29341-5-10
UPnP DigitalSecurityCameraSettings:1 Service	ISO/IEC 29341-5-11
UPnP DigitalSecurityCameraStillImage:1 Service	ISO/IEC 29341-5-12
UPnP HVAC_System:1 Device	ISO/IEC 29341-6-1
UPnP HVAC_ZoneThermostat:1 Device	ISO/IEC 29341-6-2
UPnP ControlValve:1 Service	ISO/IEC 29341-6-10
UPnP HVAC_FanOperatingMode:1 Service	ISO/IEC 29341-6-11
UPnP FanSpeed:1 Service	ISO/IEC 29341-6-12
UPnP HouseStatus:1 Service	ISO/IEC 29341-6-13
UPnP HVAC_SetpointSchedule:1 Service	ISO/IEC 29341-6-14
UPnP TemperatureSensor:1 Service	ISO/IEC 29341-6-15
UPnP TemperatureSetpoint:1 Service	ISO/IEC 29341-6-16
UPnP HVAC_UserOperatingMode:1 Service	ISO/IEC 29341-6-17
UPnP BinaryLight:1 Device	ISO/IEC 29341-7-1
UPnP DimmableLight:1 Device	ISO/IEC 29341-7-2
UPnP Dimming:1 Service	ISO/IEC 29341-7-10
UPnP SwitchPower:1 Service	ISO/IEC 29341-7-11
UPnP InternetGatewayDevice:1 Device	ISO/IEC 29341-8-1
UPnP LANDevice:1 Device	ISO/IEC 29341-8-2
UPnP WANDevice:1 Device	ISO/IEC 29341-8-3
UPnP WANConnectionDevice:1 Device	ISO/IEC 29341-8-4
UPnP WLANAccessPointDevice:1 Device	ISO/IEC 29341-8-5
UPnP LANHostConfigManagement:1 Service	ISO/IEC 29341-8-10
UPnP Layer3Forwarding:1 Service	ISO/IEC 29341-8-11
UPnP LinkAuthentication:1 Service	ISO/IEC 29341-8-12
UPnP RadiusClient:1 Service	ISO/IEC 29341-8-13
UPnP WANCableLinkConfig:1 Service	ISO/IEC 29341-8-14
UPnP WANCommonInterfaceConfig:1 Service	ISO/IEC 29341-8-15
UPnP WANDSLLinkConfig:1 Service	ISO/IEC 29341-8-16
UPnP WANEthernetLinkConfig:1 Service	ISO/IEC 29341-8-17
UPnP WANIPConnection:1 Service	ISO/IEC 29341-8-18
UPnP WANPOTSLinkConfig:1 Service	ISO/IEC 29341-8-19
UPnP WANPPConnection:1 Service	ISO/IEC 29341-8-20
UPnP WLANConfiguration:1 Service	ISO/IEC 29341-8-21
UPnP Printer:1 Device	ISO/IEC 29341-9-1
UPnP Scanner:1.0 Device	ISO/IEC 29341-9-2
UPnP ExternalActivity:1 Service	ISO/IEC 29341-9-10
UPnP Feeder:1.0 Service	ISO/IEC 29341-9-11
UPnP PrintBasic:1 Service	ISO/IEC 29341-9-12
UPnP Scan:1 Service	ISO/IEC 29341-9-13
UPnP QoS Architecture:1.0	ISO/IEC 29341-10-1
UPnP QosDevice:1 Service	ISO/IEC 29341-10-10
UPnP QosManager:1 Service	ISO/IEC 29341-10-11
UPnP QosPolicyHolder:1 Service	ISO/IEC 29341-10-12
UPnP QoS Architecture:2	ISO/IEC 29341-11-1
UPnP QOS v2 Schema Files	ISO/IEC 29341-11-2

UPnP Document Title	ISO/IEC 29341 Part
UPnP QoSDevice:2 Service	ISO/IEC 29341-11-10
UPnP QoSManager:2 Service	ISO/IEC 29341-11-11
UPnP QoSPolicyHolder:2 Service	ISO/IEC 29341-11-12
UPnP RemoteUIClientDevice:1 Device	ISO/IEC 29341-12-1
UPnP RemoteUIServerDevice:1 Device	ISO/IEC 29341-12-2
UPnP RemoteUIClient:1 Service	ISO/IEC 29341-12-10
UPnP RemoteUIServer:1 Service	ISO/IEC 29341-12-11
UPnP DeviceSecurity:1 Service	ISO/IEC 29341-13-10
UPnP SecurityConsole:1 Service	ISO/IEC 29341-13-11

1. Glossary

Access Domain

A set of LAN or MAN stations together with interconnecting data transmission media and related equipment (e.g., connectors, repeaters), in which the LAN or MAN stations use the same MAC protocol to establish the sequence of stations that are in temporary control of the shared transmission media.

Access Priority

The Access Priority is a parameter that indicates the priority handling when accessing the communication resource. The range of access priorities is defined by the layer 2 networking technology.

Best Effort

A general method of accessing a network communications medium to deliver a message. Best effort access is not guaranteed, and therefore the message may not get delivered. Many communication protocols mediums use this approach. Higher layers of protocol are needed to provide reliability or QoS. Best Effort is typically the default grade of service provided in a network when no specific QoS is requested.

Bridge

A functional unit that interconnects two or more LANs that use the same Data Link layer protocols above the MAC sublayer, but can use different MAC protocols

Hub

A device, with two or more physical ports, that forwards all traffic received on any individual port to all other ports. This device is also referred to as a “repeater”. In a home network, a hub connects networks segments of the same physical medium.

IGD

Internet Gateway Device: a border device physically connects the Home LAN with a WAN. This device performs routing. QoS mechanisms associated with routing are not addressed by this architecture, the IGD may present a QosDevice interface on the Home LAN.

Intermediate Device

An intermediate device is physically connected between the Source and Sink device data flow. There may be more than one intermediate device in the Source to Sink connection.

Path

The physical course that traffic will flow on from source to sink. For UPnP QoS, a path must reside within a single IP subnet, but a path may comprise multiple segments.

Packet Priority

The Packet Priority is a layer 2 parameter that indicates the priority handling requested by the originating service. Typically this parameter is part of a packet header and indicates the relative importance of the packet compared to other packets. It is used to differentiate packets to determine which are given preferential access to the communication medium. This parameter is typically mapped to an Access Priority value supported by the network device.

Parameterized Services

Parameterized services refer to a general methodology for obtaining QoS. A contract is made with the network using a set of parameters that define the application's traffic requirements. The parameters typically include bandwidth and delay.

Policy Management

A function that makes decisions on the traffic streams allowed to use network resources.

Prioritized Services

Prioritized services refer to a general methodology for providing QoS by differentiating traffic. Message types are grouped by order of importance and assigned a priority. Message types assigned a higher priority are given preferential access to the communications medium. There are no limits to the number of messages using a given priority, and the bandwidth of the network may be less than the bandwidth of the messages.

Quality of Service (QoS)

The term QoS refers to a broad collection of networking capabilities and techniques. The goal of QoS is to improve the user experience of a network's ability to deliver predictable results for sensitive applications such as audio, video, and voice applications. Elements of network performance within the scope of QoS often include bandwidth (throughput), latency (delay), and error rate. There are two broad classes of QoS: data reliability and temporal reliability. Each makes different demands on network technologies. This architecture is primarily concerned with delivering temporal reliability.

Router

A device, with two or more physical ports, that makes port to port traffic forwarding decisions based on layer 3 information (source and destination IP addresses).

Segment

A segment refers to a section of a network that shares a common physical medium. The boundaries of a network segment are established by devices capable of regulating the flow of traffic into and out of the segment. This includes routers, bridges, hubs, switches, adapters (e.g., PCI, PCCard, or USB NICs). With particular relevance to UPnP QoS, a segment is typically a physically distinct portion of a larger network that is in turn defined logically by devices residing on a common IP subnet.

Sink Device

A Sink device provides media data receiving, playback, storage, or rendering capabilities. Some examples include TV monitors, Stereo and Home Theaters, PDAs, Wireless Monitors, recordable DVDs, and Printers.

Source Device

A Source device provides media transmission and data sourcing capabilities. Examples include STBs, PVRs, PCs, Music Servers, Broadcast Tuners and Video Imaging Capture Devices. It acts as the source of a traffic stream, regardless of other functions on the device.

Subnet

Subnet as defined in IETF Zeroconf in RFC 3927:

<ftp://ftp.isi.edu/internet-drafts/draft-ietf-zeroconf-ipv4-linklocal-18.txt> .

Traffic Class

The Traffic Class indicates the kind of traffic in the traffic stream. The Traffic Class is used to distinguish, for example, audio from video. The distinction is at the application layer and the Traffic Class is mapped into the applicable layer 2 representations for the technology bearing the stream. An example is the mapping in 802.1D, Annex G.

Traffic Identifier (TID)

A Traffic Identifier is a set of information that uniquely identifies a set of data packets as belonging to a traffic stream. This information is typically used by a packet classifier function to associate a Traffic Specification's QoS contract to the service provided to the Traffic stream. Other technologies may refer to this as a Filter Spec (RFC2205) or Traffic Classifier (802.11e).

Traffic Specification (TSPEC)

A Traffic Specification contains a set of parameters that define the characteristics of the traffic stream. The TSPEC may be used to define the operating requirement for carrying the traffic stream and may define the operation of the packet scheduling function.

Traffic Stream (TS)

Traffic Stream is a unidirectional flow of data that originates at a source device and terminates at one or more sink device(s).

2. Introduction

This architecture document describes the motivation, use and interaction of the three services that comprise the UPnP QoS Framework:

- QoSDeviceService
- QosPolicyHolder Service
- QosManager Service

It should be noted that while UPnP QoS defines three new services (listed above), it does not define a new device type.

Since Quality of Service issues need to be solved for multiple usage scenarios, it is expected that vendors may use any UPnP device as a container for the services defined in UPnP QoS. The Control Points and QoS Management Entities must look for UPnP QoS Services embedded in all UPnP device types.

The UPnP QoS Framework is compliant with the UPnP Device Architecture version 1.0.

2.1. Referenced Specifications

Unless explicitly stated otherwise herein, implementation of the mandatory provisions of any standard referenced by this specification shall be mandatory for compliance with this specification.

[Annex_G] – IEEE 802.1D-2004, Annex G, *IEEE Standard for Information technology - Telecommunications and information exchange between systems - IEEE standard for local and metropolitan area networks - Common specifications - Media access control (MAC) Bridges*, 2004.

[XML] – *Extensible Markup Language (XML) 1.0 (Second Edition)*, T. Bray, J. Paoli, C. M. Sperberg-McQueen, E. Maler, eds. W3C Recommendations, 6 October 2000.

[QM] – UPnP™ QosManager:1 Service Document:

[QD] – UPnP™ QosDevice:1 Service Document:

[QPH] – UPnP™ QosPolicyHolder:1 Service Document:

[AV] – UPnP™ AV Architecture Document V0.83

[DEVICE] - *UPnP Device Architecture, version 1.0*.