



ISO/IEC 29341-17-13

Edition 1.0 2011-08

INTERNATIONAL STANDARD



**Information technology – UPnP device architecture –
Part 17-13: Quality of Service Device Control Protocol – Level 3 – Quality of
Service Device Service – Underlying Technology Interfaces**

INTERNATIONAL
ELECTROTECHNICAL
COMMISSION

PRICE CODE

H

ICS 35.200

ISBN 978-2-88912-647-7

CONTENTS

| | | |
|-------|--|----|
| 1 | Overview and Scope..... | 2 |
| 1.1 | Referenced Specifications | 3 |
| 1.1.1 | Normative References | 3 |
| 1.1.2 | Informative References | 3 |
| 2 | (Normative) Requirements on the QosDevice Service and interactions that are specific for the Underlying Network Technologies | 3 |
| 2.1 | DSCP | 4 |
| 2.1.1 | References | 4 |
| 2.1.2 | Priority Mapping..... | 4 |
| 2.2 | <i>HomePlug AV</i> | 4 |
| 2.2.1 | References | 4 |
| 2.2.2 | Priority Mapping..... | 4 |
| 2.2.3 | <i>QosSegmentId</i> formation..... | 4 |
| 2.2.4 | <i>Layer2StreamId</i> representation | 5 |
| 2.2.5 | Mapping of UPnP QoS Parameters to HomePlug CSPEC Parameters..... | 5 |
| 2.2.6 | Blocking traffic stream identification | 6 |
| 2.2.7 | Responsibility for Stream Setup | 6 |
| 2.2.8 | Mapping of <i>HomePlug AV</i> Returned Parameters to <i>ProtoTspec</i> Parameters | 6 |
| 2.2.9 | Mapping of <i>HomePlug AV</i> Returned Parameters to <i>AdmitTrafficQosExtendedResult</i> and <i>AllocatedResources</i> Parameters | 6 |
| 2.3 | HPNA..... | 6 |
| 2.3.1 | References | 6 |
| 2.3.2 | Priority Mapping..... | 7 |
| 2.4 | IEEE 802.1Q, Annex G | 7 |
| 2.4.1 | References | 7 |
| 2.4.2 | Priority Mapping..... | 7 |
| 2.5 | <i>MoCA</i> | 7 |
| 2.5.1 | References | 7 |
| 2.5.2 | Priority Mapping..... | 8 |
| 2.5.3 | <i>QosSegmentId</i> formation..... | 8 |
| 2.5.4 | <i>Layer2StreamId</i> representation | 8 |
| 2.5.5 | Mapping of UPnP QoS Parameters to <i>MoCA</i> Parameters..... | 8 |
| 2.5.6 | Blocking traffic stream identification | 9 |
| 2.5.7 | Responsibility for QoS Setup | 9 |
| 2.5.8 | Mapping of <i>MoCA</i> Returned Parameters to <i>ProtoTspec</i> Parameters..... | 9 |
| 2.5.9 | Mapping of <i>MoCA</i> Returned Parameters to <i>AdmitTrafficQosExtendedResult</i> and <i>AllocatedResources</i> Parameters | 10 |
| 2.6 | Wi-Fi WMM-AC..... | 10 |
| 2.6.1 | References | 10 |
| 2.6.2 | Priority Mapping..... | 10 |
| 2.6.3 | <i>QosSegmentId</i> formation..... | 11 |
| 2.6.4 | <i>Layer2StreamId</i> representation | 11 |
| 2.6.5 | Mapping of UPnP QoS Parameters to <i>WMM</i> Parameters | 11 |

| | | |
|---|--|----|
| 2.6.6 | Blocking traffic stream identification | 11 |
| 2.6.7 | Responsibility for QoS Setup | 12 |
| 2.6.8 | Mapping of <i>WMM</i> Returned Parameters to <i>ProtoTspec</i> Parameters | 12 |
| 2.6.9 | Mapping of <i>WMM</i> Returned Parameters to <i>AdmitTrafficQosExtendedResult</i> and <i>AllocatedResources</i> Parameters | 13 |
| 2.7 | UPA | 13 |
| 2.7.1 | References | 13 |
| 2.7.2 | Priority Mapping..... | 13 |
| 2.7.3 | <i>QosSegmentId</i> formation..... | 14 |
| 2.7.4 | <i>Layer2StreamId</i> representation | 14 |
| 2.7.5 | Mapping of UPnP QoS Parameters to UPA Parameters | 14 |
| 2.7.6 | Blocking traffic stream identification | 15 |
| 2.7.7 | Responsibility for QoS Setup | 15 |
| 2.7.8 | Mapping of <i>UPA</i> Returned Parameters to <i>ProtoTspec</i> Parameters | 15 |
| 2.7.9 | Mapping of <i>UPA</i> Returned Parameters to <i>AdmitTrafficQosExtendedResult</i> and <i>AllocatedResources</i> Parameters | 16 |
| Table 2.1-1 — Priority Mapping..... | | 4 |
| Table 2.2-1 — Priority Mapping..... | | 4 |
| Table 2.2-2 — Traffic Specification Parameters..... | | 5 |
| Table 2.2-3 — <i>ProtoTspec</i> Parameters | | 6 |
| Table 2.3-1 — Priority Mapping..... | | 7 |
| Table 2.4-1 — Priority Mapping..... | | 7 |
| Table 2.5-1 — Priority Mapping..... | | 8 |
| Table 2.5-2 — Traffic Specification Parameters..... | | 9 |
| Table 2.5-3 — <i>ProtoTspec</i> Parameters | | 9 |
| Table 2.5-4 — <i>AllocatedResource</i> Parameters | | 10 |
| Table 2.6-1 — Priority Mapping..... | | 11 |
| Table 2.6-2 — Traffic Specification Parameters..... | | 11 |
| Table 2.6-3 — <i>ProtoTspec</i> Parameters | | 13 |
| Table 2.6-4 — <i>AllocatedResource</i> Parameters | | 13 |
| Table 2.7-1 — Priority Mapping..... | | 14 |
| Table 2.7-2 — Traffic Specification Parameters..... | | 15 |
| Table 2.7-3 — <i>ProtoTspec</i> Parameters | | 16 |
| Table 2.7-4 — <i>AllocatedResource</i> Parameters | | 16 |

INFORMATION TECHNOLOGY – UPNP DEVICE ARCHITECTURE –

Part 17-13: Quality of Service Device Control Protocol – Level 3 – Quality of Service Device Service – Underlying Technology Interfaces

FOREWORD

- 1) ISO (International Organization for Standardization) and IEC (International Electrotechnical Commission) form the specialized system for worldwide standardization. National bodies that are members of ISO or IEC participate in the development of International Standards. Their preparation is entrusted to technical committees; any ISO and IEC member body interested in the subject dealt with may participate in this preparatory work. International governmental and non-governmental organizations liaising with ISO and IEC also participate in this preparation.
- 2) In the field of information technology, ISO and IEC have established a joint technical committee, ISO/IEC JTC 1. Draft International Standards adopted by the joint technical committee are circulated to national bodies for voting. Publication as an International Standard requires approval by at least 75 % of the national bodies casting a vote.
- 3) The formal decisions or agreements of IEC and ISO on technical matters express, as nearly as possible, an international consensus of opinion on the relevant subjects since each technical committee has representation from all interested IEC and ISO member bodies.
- 4) IEC, ISO and ISO/IEC publications have the form of recommendations for international use and are accepted by IEC and ISO member bodies in that sense. While all reasonable efforts are made to ensure that the technical content of IEC, ISO and ISO/IEC publications is accurate, IEC or ISO cannot be held responsible for the way in which they are used or for any misinterpretation by any end user.
- 5) In order to promote international uniformity, IEC and ISO member bodies undertake to apply IEC, ISO and ISO/IEC publications transparently to the maximum extent possible in their national and regional publications. Any divergence between any ISO/IEC publication and the corresponding national or regional publication should be clearly indicated in the latter.
- 6) ISO and IEC provide no marking procedure to indicate their approval and cannot be rendered responsible for any equipment declared to be in conformity with an ISO/IEC publication.
- 7) All users should ensure that they have the latest edition of this publication.
- 8) No liability shall attach to IEC or ISO or its directors, employees, servants or agents including individual experts and members of their technical committees and IEC or ISO member bodies for any personal injury, property damage or other damage of any nature whatsoever, whether direct or indirect, or for costs (including legal fees) and expenses arising out of the publication of, use of, or reliance upon, this ISO/IEC publication or any other IEC, ISO or ISO/IEC publications.
- 9) Attention is drawn to the normative references cited in this publication. Use of the referenced publications is indispensable for the correct application of this publication.
- 10) Attention is drawn to the possibility that some of the elements of this International Standard may be the subject of patent rights. ISO and IEC shall not be held responsible for identifying any or all such patent rights.

International Standard ISO/IEC 29341-17-13 was prepared by UPnP Forum Steering committee¹, was adopted, under the fast track procedure, by subcommittee 25: Interconnection of information technology equipment, of ISO/IEC joint technical committee 1: Information technology.

The list of all currently available parts of the ISO/IEC 29341 series, under the general title *Information technology – UPnP device architecture*, can be found on the IEC web site.

This International Standard has been approved by vote of the member bodies, and the voting results may be obtained from the address given on the second title page.

¹ UPnP Forum Steering committee, UPnP Forum, 3855 SW 153rd Drive, Beaverton, Oregon 97006 USA. See also "Introduction".

IMPORTANT – The “colour inside” logo on the cover page of this publication indicates that it contains colours which are considered to be useful for the correct understanding of its contents. Users should therefore print this publication using a colour printer.

1 Overview and Scope

This service definition addendum contains recommendations for implementing interfaces between the UPnP QoSDevice Service and various lower transport layers. Its purpose is to ensure that implementers of these interfaces use consistent mapping of methods and parameters from UPnP to the lower layers.

1.1 Referenced Specifications

Unless explicitly stated otherwise herein, implementation of the mandatory provisions of any standard referenced by this specification shall be mandatory for compliance with this specification.

1.1.1 Normative References

This clause lists the normative references used in this document and includes the tag inside square brackets that is used for each sub reference:

[QD 3] *UPnP QosDevice:3 Service Document*. Available at:
<http://www.upnp.org/specs/qos/UPnP-qos-QosDevice-v3-Service-20081130.pdf> Latest version available at: <http://www.upnp.org/specs/qos/UPnP-qos-QosDevice-v3-Service.pdf>

[DEVICE] - *UPnP Device Architecture, version 1.0*.

[IANA] - IANA Interface Type (IANAifType)-MIB <http://www.iana.org/assignments/ianaiftype-mib>

1.1.2 Informative References

This clause lists the informative references used in this document and includes the tag inside square brackets that is used for each sub reference:

[Qos Architecture] – UPnP Qos Architecture:3 Document Available at:
<http://www.upnp.org/specs/qos/UPnP-qos-Architecture-v3-20081130.pdf> Latest version available at: <http://www.upnp.org/specs/qos/UPnP-qos-Architecture-v3.pdf>

[Annex_G] – IEEE 802.1Q-2005, Annex G, IEEE Standard for Information technology - Telecommunications and information exchange between systems – IEEE Standard for Local and metropolitan area networks - Virtual Bridged Local Area Networks, 2005.