

IPC J-STD-001D

February 2005

Supersedes Revision C March 2000

JOINT INDUSTRY STANDARD

Requirements for
Soldered Electrical
and Electronic
Assemblies



Table of Contents

1 GENERAL	1	3 MATERIALS, COMPONENTS AND EQUIPMENT REQUIREMENTS	5
1.1 Scope	1	3.1 Materials	5
1.2 Purpose	1	3.2 Solder	5
1.3 Classification	1	3.2.1 Solder - Lead Free	5
1.4 Measurement Units and Applications	1	3.2.2 Solder Purity Maintenance	5
1.4.1 Verification of Dimensions	1	3.3 Flux	6
1.5 Definition of Requirements	1	3.3.1 Flux Application	6
1.5.1 Hardware Defects and Process Indicators	2	3.4 Solder Paste	6
1.5.2 Material and Process Nonconformance	2	3.5 Solder Preforms	6
1.6 General Requirements	2	3.6 Adhesives	6
1.7 Order of Precedence	2	3.7 Chemical Strippers	6
1.7.1 Conflict	2	3.8 Heat Shrinkable Soldering Devices	6
1.7.2 Clause References	2	3.9 Components	6
1.7.3 Appendices	2	3.9.1 Solderability	6
1.8 Terms and Definitions	2	3.9.2 Solderability Maintenance	6
1.8.1 Defect	2	3.9.3 Gold Removal	6
1.8.2 Disposition	2	3.9.4 Rework of Nonsolderable Parts	7
1.8.3 Electrical Clearance	2	3.9.5 Component and Seal Damage	7
1.8.4 High Voltage	3	3.9.6 Component Damage	7
1.8.5 Manufacturer (Assembler)	3	3.9.7 Coating Meniscus	7
1.8.6 Objective Evidence	3	3.10 Presoldering Cleanliness Requirements	7
1.8.7 Process Control	3	3.11 Soldering Tools and Equipment	7
1.8.8 Process Indicator	3		
1.8.9 Proficiency	3	4 GENERAL SOLDERING AND ASSEMBLY REQUIREMENTS	7
1.8.10 Solder Destination Side	3	4.1 Electrostatic Discharge (ESD)	7
1.8.11 Solder Source Side	3	4.2 Facilities	7
1.8.12 Supplier	3	4.2.1 Environmental Controls	7
1.8.13 User	3	4.2.2 Temperature and Humidity	7
1.9 Requirements Flowdown	3	4.2.3 Lighting	7
1.10 Personnel Proficiency	3	4.2.4 Field Assembly Operations	7
1.11 Acceptance Requirements	3	4.3 General Part Mounting Requirements	7
1.12 General Assembly Requirements	3	4.4 Hole Obstruction	8
1.13 Miscellaneous Requirements	3	4.5 Metal-Cased Component Isolation	8
1.13.1 Health and Safety	3	4.6 Adhesive Coverage Limits	8
1.13.2 Procedures for Specialized Technologies	3	4.7 Mounting of Parts on Parts (Stacking of Components)	8
2 APPLICABLE DOCUMENTS	4	4.8 Connectors and Contact Areas	8
2.1 EIA	4	4.9 Handling of Parts	8
2.2 IPC	4	4.9.1 Preheating	8
2.3 Joint Industry Standards	5	4.9.2 Controlled Cooling	8
2.4 ASTM	5	4.9.3 Drying/Degassing	8
2.5 Electrostatic Discharge Association	5	4.9.4 Holding Devices and Materials	8

4.10	Heat Sinks	9	6.3	Supported Holes	17
4.11	Machine (Nonreflow) Soldering	9	6.3.1	Solder Application	17
4.11.1	Machine Controls	9	6.3.2	Through-Hole Component Lead Soldering	17
4.11.2	Solder Bath	9	7	SURFACE MOUNTING OF COMPONENTS	18
4.12	Reflow Soldering	9	7.1	Surface Mount Device Lead Forming	18
4.13	Intrusive Soldering (Paste-in-Hole)	9	7.1.1	Lead Deformation Limits	19
4.14	Solder Connection	9	7.1.2	Flat Pack Parallelism	19
4.14.1	Exposed Basis Metal	10	7.1.3	Surface Mount Device Lead Bends	19
4.14.2	Exposed Surface Finishes	10	7.1.4	Flattened Leads	19
4.14.3	Solder Connection Defects	10	7.1.5	Dual-in-Line Packages (DIPs)	19
4.14.4	Partially Visible or Hidden Solder Connections	10	7.1.6	Parts Not Configured for Surface Mounting ...	19
5	WIRES AND TERMINAL CONNECTIONS	10	7.2	Devices with Externally Deposited Elements .	19
5.1	Wire and Cable Preparation	10	7.3	Leaded Component Body Clearing	19
5.1.1	Tinning of Stranded Wire	10	7.3.1	Axial-Leaded Components	19
5.2	Solder Terminals	11	7.4	Parts Configured for Butt Lead Mounting	19
5.3	Bifurcated, Turret and Slotted Terminal Installation	11	7.5	Hold Down of Surface Mount Leads	19
5.3.1	Shank Damage	11	7.6	Soldering Requirements	20
5.3.2	Flange Damage	11	7.6.1	Misaligned Components	20
5.3.3	Flared Flange Angles	11	7.6.2	Unspecified and Special Requirements	20
5.3.4	Terminal Mounting - Mechanical	11	7.6.3	Bottom Only Terminations	21
5.3.5	Terminal Mounting - Electrical	12	7.6.4	Chip Components - Rectangular or Square End Components - 1, 3 or 5 Side Termination	22
5.3.6	Terminal Soldering	12	7.6.5	Cylindrical End Cap (MELF) Terminations ...	23
5.4	Mounting to Terminals	12	7.6.6	Castellated Terminations	24
5.4.1	General Requirements	12	7.6.7	Flat, Ribbon, "L," and Gull Wing Leads	25
5.4.2	Bifurcated and Turret Terminals	14	7.6.8	Round or Flattened (Coined) Leads	26
5.4.3	Slotted Terminals	15	7.6.9	"J" Leads	27
5.4.4	Hook Terminals	15	7.6.10	Butt Connections (Not Permitted for Class 3 Products)	28
5.4.5	Pierced or Perforated Terminals	15	7.6.11	Flat Lug Leads	29
5.4.6	Cup and Hollow Cylindrical Terminals	15	7.6.12	Tall Profile Components Having Bottom Only Terminations	30
5.5	Soldering to Terminals	15	7.6.13	Inward Formed L-Shaped Ribbon Leads	31
5.5.1	Turret and Straight Pin Terminals	15	7.6.14	Surface Mount Area Array Packages	32
5.5.2	Cup and Hollow Cylindrical Terminals	16	7.6.15	Quad Flat Pack (No Leads) (QFNL)	33
6	THROUGH-HOLE MOUNTING AND TERMINATIONS	16	7.6.16	Components with Bottom Thermal Plane Terminations	34
6.1	Through-Hole Terminations - General	16	8	CLEANING PROCESS REQUIREMENTS	35
6.1.1	Lead Forming	16	8.1	Cleanliness Exemptions	35
6.1.2	Lead Deformation Limits	16	8.2	Ultrasonic Cleaning	35
6.1.3	Lead Termination Requirements	16	8.3	Post-Solder Cleanliness	35
6.1.4	Lead Trimming	17	8.3.1	Particulate Matter	35
6.1.5	Interfacial Connections	17	8.3.2	Flux Residues and Other Ionic or Organic Contaminants	35
6.1.6	Coating Meniscus In Solder	17	8.3.3	Post-Soldering Cleanliness Designator	35
6.2	Unsupported Holes	17	8.3.4	Cleaning Option	35
6.2.1	Lead Termination Requirements for Unsupported Holes	17			

8.3.5	Test for Cleanliness	35
8.3.6	Testing	35
9	PCB REQUIREMENTS	36
9.1	Printed Circuit Board Damage	36
9.1.1	Blistering/Delamination	36
9.1.2	Weave Exposure	36
9.1.3	Haloing	36
9.1.4	Land Separation	36
9.1.5	Land/Conductor Reduction in Size	37
9.1.6	Flexible Circuitry Delamination	37
9.1.7	Flexible Circuitry Damage	37
9.1.8	Burns	37
9.1.9	Solder on Gold Contacts	37
9.1.10	Measles	37
9.2	Marking	37
9.3	Bow and Twist (Warpage)	37
10	COATING AND ENCAPSULATION	37
10.1	Conformal Coating	37
10.1.1	Application	37
10.1.2	Performance Requirements	38
10.1.3	Conformal Coating Inspection	38
10.2	Encapsulation	38
10.2.1	Application	38
10.2.2	Performance Requirements	38
10.2.3	Rework of Encapsulant Material	38
10.2.4	Encapsulant Inspection	38
11	PRODUCT ASSURANCE	39
11.1	Hardware Defects Requiring Disposition	39
11.2	Inspection Methodology	39
11.2.1	Process Verification Inspection	39
11.2.2	Visual Inspection	39
11.2.3	Sampling Inspection	39
11.3	Process Control Requirements	39
11.3.1	Opportunities Determination	40
11.4	Statistical Process Control	40
12	REWORK AND REPAIR	40
12.1	Rework of Unsatisfactory Solder Connections	40
12.2	Repair	40
12.3	Post Rework/Repair Cleaning	40
12.4	Rework of Conformal Coating/Encapsulant	40
APPENDIX A	Summary of Criteria Requiring Disposition to Nonconforming Conditions	41

APPENDIX B	Guidelines for Soldering Tools and Equipment	43
APPENDIX C	Material and Process Compatibility Testing	45
APPENDIX D	Minimum Electrical Clearance - Electrical Conductor Spacing	47
APPENDIX E	Visual Comparisons of SnPb and Lead Free Solder Connections	49

Figures

Figure 4-1	Hole Obstruction	8
Figure 4-2	Acceptable Wetting Angles	10
Figure 5-1	Flange Damage	11
Figure 5-2	Flare Angles	11
Figure 5-3	Terminal Mounting - Mechanical	11
Figure 5-4	Terminal Mounting - Electrical	12
Figure 5-5	Insulation Clearance Measurement	12
Figure 5-6	Service Loop for Lead Wiring	13
Figure 5-7	Stress Relief Examples	13
Figure 5-8	Continuous Runs	13
Figure 5-9	Wire and Lead Wrap Around	14
Figure 5-10	Side Route Connections and Wrap on Bifurcated Terminal	14
Figure 5-11	Top and Bottom Route Terminal Connection .	15
Figure 5-12	Hook Terminal Connections	15
Figure 5-13	Pierced or Perforated Terminal Wire Wrap	15
Figure 6-1	Lead Bends	16
Figure 6-2	Vertical Fill Example	18
Figure 7-1	Surface Mount Device Lead Forming	18
Figure 7-2	Surface Mount Device Lead Forming	18
Figure 7-3	Bottom Only Terminations	21
Figure 7-4	Rectangular or Square End Components	22
Figure 7-5	MELF Terminations	23
Figure 7-6	Castellated Terminations	24
Figure 7-7	Flat, Ribbon, "L," and Gull Wing Leads	25
Figure 7-8	Round or Flattened (Coined) Leads	26
Figure 7-9	"J" Leads	27
Figure 7-10	Butt Joint	28
Figure 7-11	Flat Lug Leads	29
Figure 7-12	Tall Profile Components Having Bottom Only Terminations	30
Figure 7-13	Inward Formed L-Shaped Ribbon Lead	31
Figure 7-14	BGA Solder Ball Spacing	32
Figure 7-15	PQFN	33
Figure 7-16	Component with Bottom Thermal Plane Terminations	34
Figure E-1	SnPb Solder; No Clean Process	49
Figure E-2	SnAgCu Solder; No Clean Process	49

Figure E-3	SnPb Solder; Water Soluble Flux	49
Figure E-4	SnAgCu Solder; Water Soluble Flux	49
Figure E-5	SnPb Solder; Water Soluble Flux	49
Figure E-6	SnAgCu Solder; Water Soluble Flux	49
Figure E-7	SnAgCu Solder; No Clean Process, N2 Reflow	50
Figure E-8	SnAgCu Solder; No Clean Process; Air Reflow	50
Figure E-9	SnPb Solder; No Clean Process	50
Figure E-10	SnAgCu Solder; No Clean Process	50
Figure E-11	SnPb Solder; No Clean Process	50
Figure E-12	SnAgCu Solder; No Clean Process	50
Figure E-13	SnPb Solder	51
Figure E-14	SnAgCu Solder	51
Figure E-15	SnPb Solder	51
Figure E-16	SnAgCu Solder	51
Figure E-17	SnPb Solder; OSP Finish	51
Figure E-18	SnAgCu Solder; OSP Finish	51
Figure E-19	SnAgCu Solder	52
Figure E-20	SnAgCu Solder	52
Figure E-21	SnAgCu Solder	52
Figure E-22	SnAgCu Solder	52

Tables

Table 1-1	Design and Fabrication Specification	2	Table 6-3	Protrusion of Leads in Supported Holes	17
Table 3-1	Solder Limits for Tin/Lead Alloys	5	Table 6-4	Unsupported Holes with Component Leads, Minimum Acceptable Conditions	17
Table 4-1	Solder Acceptability, Intrusive Soldering, Supported Holes	9	Table 6-5	Supported Holes with Component Leads, Minimum Acceptable Conditions	18
Table 5-1	Damaged Strand Limits	11	Table 7-1	SMT Lead Forming Minimum Lead Length	19
Table 5-2	Terminal Soldering Requirements	12	Table 7-2	Surface Mount Components	20
Table 5-3	Staking Requirements of Side Route Straight Through Connections - Bifurcated Terminals	14	Table 7-3	Dimensional Criteria - Bottom Only Terminations	21
Table 5-4	Solder Height Requirements Wire to Post	15	Table 7-4	Dimensional Criteria - Chip Components - Rectangular or Square End Components - 1, 3 or 5 Side Termination	22
Table 6-1	Lead Bend Radius	16	Table 7-5	Dimensional Criteria - Cylindrical End Cap (MELF) Terminations	23
Table 6-2	Protrusion of Leads in Unsupported Holes	17	Table 7-6	Dimensional Criteria - Castellated Terminations	24
			Table 7-7	Dimensional Criteria - Flat, Ribbon, "L," and Gull Wing Leads	25
			Table 7-8	Dimensional Criteria - Round or Flattened (Coined) Leads	26
			Table 7-9	Dimensional Criteria - "J" Leads	27
			Table 7-10	Dimensional Criteria - Butt/I Connections (Not Applicable to Class 3)	28
			Table 7-11	Dimensional Criteria - Flat Lug Leads	29
			Table 7-12	Dimensional Criteria - Tall Profile Components Having Bottom Only Terminations	30
			Table 7-13	Dimensional Criteria - Inward Formed L-Shaped Ribbon Leads	31
			Table 7-14	Dimensional Criteria - Area Array/Ball Grid Array	32
			Table 7-15	Dimensional Criteria - PQFN	33
			Table 7-16	Dimensional Criteria - Bottom Thermal Plane Terminations	34
			Table 8-1	Designation of Surfaces to be Cleaned	35
			Table 8-2	Cleanliness Testing Designators	35
			Table 10-1	Coating Thickness	38
			Table 11-1	Magnification Aid Applications for Solder Connections	39
			Table 11-2	Magnification Aid Applications - Other	39